

The Supplemental Isabelle/HOL Library

October 1, 2005

Contents

1	Accessible-Part: The accessible part of a relation	4
1.1	Inductive definition	4
1.2	Induction rules	4
2	SetsAndFunctions: Operations on sets and functions	5
2.1	Basic definitions	5
2.2	Basic properties	8
3	BigO: Big O notation	12
3.1	Definitions	13
3.2	Setsum	24
3.3	Misc useful stuff	26
3.4	Less than or equal to	27
4	Continuity: Continuity and iterations (of set transformers)	30
4.1	Chains	30
4.2	Continuity	31
4.3	Iteration	32
5	EfficientNat: Implementation of natural numbers by integers	35
5.1	Basic functions	35
5.2	Preprocessors	36
6	ExecutableSet: Implementation of finite sets by lists	37
7	FuncSet: Pi and Function Sets	38
7.1	Basic Properties of Pi	39
7.2	Composition With a Restricted Domain: <i>compose</i>	39
7.3	Bounded Abstraction: <i>restrict</i>	40
7.4	Bijections Between Sets	40
7.5	Extensionality	41
7.6	Cardinality	42

8 Multiset: Multisets	42
8.1 The type of multisets	42
8.2 Algebraic properties of multisets	44
8.2.1 Union	44
8.2.2 Difference	44
8.2.3 Count of elements	44
8.2.4 Set of elements	45
8.2.5 Size	45
8.2.6 Equality of multisets	46
8.2.7 Intersection	47
8.3 Induction over multisets	47
8.4 Multiset orderings	49
8.4.1 Well-foundedness	49
8.4.2 Closure-free presentation	52
8.4.3 Partial-order properties	54
8.4.4 Monotonicity of multiset union	55
8.5 Link with lists	56
8.6 Pointwise ordering induced by count	58
9 NatPair: Pairs of Natural Numbers	59
10 Nat-Infinity: Natural numbers with infinity	61
10.1 Definitions	61
10.2 Constructors	62
10.3 Ordering relations	62
11 Nested-Environment: Nested environments	64
11.1 The lookup operation	65
11.2 The update operation	69
12 Permutation: Permutations	75
12.1 Some examples of rule induction on permutations	75
12.2 Ways of making new permutations	76
12.3 Further results	76
12.4 Removing elements	76
13 Primes: Primality on nat	78
14 Quotient: Quotient types	79
14.1 Equivalence relations and quotient types	79
14.2 Equality on quotients	80
14.3 Picking representing elements	81
15 While-Combinator: A general “while” combinator	83

16 Word: Binary Words	86
16.1 Auxilary Lemmas	86
16.2 Bits	86
16.3 Bit Vectors	88
16.4 Unsigned Arithmetic Operations	104
16.5 Signed Vectors	105
16.6 Signed Arithmetic Operations	119
16.6.1 Conversion from unsigned to signed	119
16.6.2 Unary minus	119
16.7 Structural operations	132
17 Zorn: Zorn's Lemma	140
17.1 Mathematical Preamble	140
17.2 Hausdorff's Theorem: Every Set Contains a Maximal Chain.	142
17.3 Zorn's Lemma: If All Chains Have Upper Bounds Then There Is a Maximal Element	144
17.4 Alternative version of Zorn's Lemma	144
18 Product-ord: Order on product types	145
19 Char-ord: Order on characters	145
20 Commutative-Ring: Proving equalities in commutative rings	148
21 List-Prefix: List prefixes and postfixes	154
21.1 Prefix order on lists	154
21.2 Basic properties of prefixes	155
21.3 Parallel lists	157
21.4 Postfix order on lists	158
22 List-lexord: Lexicographic order on lists	159

1 Accessible-Part: The accessible part of a relation

```
theory Accessible-Part
imports Main
begin
```

1.1 Inductive definition

Inductive definition of the accessible part $acc\ r$ of a relation; see also [4].

```
consts
  acc :: ('a × 'a) set => 'a set
inductive acc r
  intros
    accI: (!!y. (y, x) ∈ r ==> y ∈ acc r) ==> x ∈ acc r

syntax
  termi :: ('a × 'a) set => 'a set
translations
  termi r == acc (r-1)
```

1.2 Induction rules

```
theorem acc-induct:
  a ∈ acc r ==>
    (!!x. x ∈ acc r ==> ∀ y. (y, x) ∈ r --> P y ==> P x) ==> P a
proof -
  assume major: a ∈ acc r
  assume hyp: !!x. x ∈ acc r ==> ∀ y. (y, x) ∈ r --> P y ==> P x
  show ?thesis
    apply (rule major [THEN acc.induct])
    apply (rule hyp)
    apply (rule accI)
    apply fast
    apply fast
  done
qed
```

```
theorems acc-induct-rule = acc-induct [rule-format, induct set: acc]
```

```
theorem acc-downward: b ∈ acc r ==> (a, b) ∈ r ==> a ∈ acc r
  apply (erule acc.elims)
  apply fast
  done
```

```
lemma acc-downwards-aux: (b, a) ∈ r* ==> a ∈ acc r --> b ∈ acc r
  apply (erule rtrancl-induct)
  apply blast
  apply (blast dest: acc-downward)
```

```

done

theorem acc-downwards:  $a \in \text{acc } r \implies (b, a) \in r^* \implies b \in \text{acc } r$ 
  apply (blast dest: acc-downwards-aux)
done

theorem acc-wfI:  $\forall x. x \in \text{acc } r \implies \text{wf } r$ 
  apply (rule wfUNIVI)
  apply (induct-tac P x rule: acc-induct)
  apply blast
  apply blast
done

theorem acc-wfD:  $\text{wf } r \implies x \in \text{acc } r$ 
  apply (erule wf-induct)
  apply (rule accI)
  apply blast
done

theorem wf-acc-iff:  $\text{wf } r = (\forall x. x \in \text{acc } r)$ 
  apply (blast intro: acc-wfI dest: acc-wfD)
done

end

```

2 SetsAndFunctions: Operations on sets and functions

```

theory SetsAndFunctions
imports Main
begin

```

This library lifts operations like addition and multiplication to sets and functions of appropriate types. It was designed to support asymptotic calculations. See the comments at the top of theory *BigO*.

2.1 Basic definitions

```

instance set :: (plus) plus ..
instance fun :: (type, plus) plus ..

defs (overloaded)
  func-plus:  $f + g == (\%x. f\ x + g\ x)$ 
  set-plus:  $A + B == \{c. \text{EX } a:A. \text{EX } b:B. c = a + b\}$ 

instance set :: (times) times ..
instance fun :: (type, times) times ..

```

defs (overloaded)

func-times: $f * g == (\%x. f\ x * g\ x)$
set-times: $A * B == \{c. \text{EX } a:A. \text{EX } b:B. c = a * b\}$

instance *fun* :: (*type*, *minus*) *minus* ..

defs (overloaded)

func-minus: $- f == (\%x. - f\ x)$
func-diff: $f - g == \%x. f\ x - g\ x$

instance *fun* :: (*type*, *zero*) *zero* ..

instance *set* :: (*zero*) *zero* ..

defs (overloaded)

func-zero: $0::('a::\text{type}) => ('b::\text{zero})) == \%x. 0$
set-zero: $0::('a::\text{zero})\text{set} == \{0\}$

instance *fun* :: (*type*, *one*) *one* ..

instance *set* :: (*one*) *one* ..

defs (overloaded)

func-one: $1::('a::\text{type}) => ('b::\text{one})) == \%x. 1$
set-one: $1::('a::\text{one})\text{set} == \{1\}$

constdefs

elt-set-plus :: $'a::\text{plus} => 'a\ \text{set} => 'a\ \text{set}$ (**infixl** +o 70)
 $a +_o B == \{c. \text{EX } b:B. c = a + b\}$

elt-set-times :: $'a::\text{times} => 'a\ \text{set} => 'a\ \text{set}$ (**infixl** *o 80)
 $a *_o B == \{c. \text{EX } b:B. c = a * b\}$

syntax

elt-set-eq :: $'a => 'a\ \text{set} => \text{bool}$ (**infix** =o 50)

translations

$x =_o A => x : A$

instance *fun* :: (*type*, *semigroup-add*) *semigroup-add*

apply *intro-classes*

apply (*auto simp add: func-plus add-assoc*)

done

instance *fun* :: (*type*, *comm-monoid-add*) *comm-monoid-add*

apply *intro-classes*

apply (*auto simp add: func-zero func-plus add-ac*)

done

instance *fun* :: (*type*, *ab-group-add*) *ab-group-add*

```

    apply intro-classes
    apply (simp add: func-minus func-plus func-zero)
    apply (simp add: func-minus func-plus func-diff diff-minus)
done

instance fun :: (type, semigroup-mult) semigroup-mult
  apply intro-classes
  apply (auto simp add: func-times mult-assoc)
done

instance fun :: (type, comm-monoid-mult) comm-monoid-mult
  apply intro-classes
  apply (auto simp add: func-one func-times mult-ac)
done

instance fun :: (type, comm-ring-1) comm-ring-1
  apply intro-classes
  apply (auto simp add: func-plus func-times func-minus func-diff ext
    func-one func-zero ring-eq-simps)
  apply (drule fun-cong)
  apply simp
done

instance set :: (semigroup-add) semigroup-add
  apply intro-classes
  apply (unfold set-plus)
  apply (force simp add: add-assoc)
done

instance set :: (semigroup-mult) semigroup-mult
  apply intro-classes
  apply (unfold set-times)
  apply (force simp add: mult-assoc)
done

instance set :: (comm-monoid-add) comm-monoid-add
  apply intro-classes
  apply (unfold set-plus)
  apply (force simp add: add-ac)
  apply (unfold set-zero)
  apply force
done

instance set :: (comm-monoid-mult) comm-monoid-mult
  apply intro-classes
  apply (unfold set-times)
  apply (force simp add: mult-ac)
  apply (unfold set-one)
  apply force

```

done

2.2 Basic properties

lemma *set-plus-intro* [intro]: $a : C \implies b : D \implies a + b : C + D$
by (auto simp add: set-plus)

lemma *set-plus-intro2* [intro]: $b : C \implies a + b : a + o C$
by (auto simp add: elt-set-plus-def)

lemma *set-plus-rearrange*: $((a::'a::comm-monoid-add) + o C) + (b + o D) = (a + b) + o (C + D)$
apply (auto simp add: elt-set-plus-def set-plus add-ac)
apply (rule-tac $x = ba + bb$ **in** *exI*)
apply (auto simp add: add-ac)
apply (rule-tac $x = aa + a$ **in** *exI*)
apply (auto simp add: add-ac)
done

lemma *set-plus-rearrange2*: $(a::'a::semigroup-add) + o (b + o C) = (a + b) + o C$
by (auto simp add: elt-set-plus-def add-assoc)

lemma *set-plus-rearrange3*: $((a::'a::semigroup-add) + o B) + C = a + o (B + C)$
apply (auto simp add: elt-set-plus-def set-plus)
apply (blast intro: add-ac)
apply (rule-tac $x = a + aa$ **in** *exI*)
apply (rule *conjI*)
apply (rule-tac $x = aa$ **in** *bexI*)
apply auto
apply (rule-tac $x = ba$ **in** *bexI*)
apply (auto simp add: add-ac)
done

theorem *set-plus-rearrange4*: $C + ((a::'a::comm-monoid-add) + o D) = a + o (C + D)$
apply (auto intro!: subsetI simp add: elt-set-plus-def set-plus add-ac)
apply (rule-tac $x = aa + ba$ **in** *exI*)
apply (auto simp add: add-ac)
done

theorems *set-plus-rearranges* = *set-plus-rearrange set-plus-rearrange2 set-plus-rearrange3 set-plus-rearrange4*

lemma *set-plus-mono* [intro!]: $C \leq D \implies a + o C \leq a + o D$
by (auto simp add: elt-set-plus-def)

lemma *set-plus-mono2* [intro]: $(C::('a::plus) set) \leq D \implies E \leq F \implies$

$C + E \leq D + F$
by (*auto simp add: set-plus*)

lemma *set-plus-mono3* [*intro*]: $a : C \implies a +_o D \leq C + D$
by (*auto simp add: elt-set-plus-def set-plus*)

lemma *set-plus-mono4* [*intro*]: $(a :: 'a :: \text{comm-monoid-add}) : C \implies$
 $a +_o D \leq D + C$
by (*auto simp add: elt-set-plus-def set-plus add-ac*)

lemma *set-plus-mono5*: $a : C \implies B \leq D \implies a +_o B \leq C + D$
apply (*subgoal-tac a +_o B \leq a +_o D*)
apply (*erule order-trans*)
apply (*erule set-plus-mono3*)
apply (*erule set-plus-mono*)
done

lemma *set-plus-mono-b*: $C \leq D \implies x : a +_o C$
 $\implies x : a +_o D$
apply (*frule set-plus-mono*)
apply *auto*
done

lemma *set-plus-mono2-b*: $C \leq D \implies E \leq F \implies x : C + E \implies$
 $x : D + F$
apply (*frule set-plus-mono2*)
prefer 2
apply *force*
apply *assumption*
done

lemma *set-plus-mono3-b*: $a : C \implies x : a +_o D \implies x : C + D$
apply (*frule set-plus-mono3*)
apply *auto*
done

lemma *set-plus-mono4-b*: $(a :: 'a :: \text{comm-monoid-add}) : C \implies$
 $x : a +_o D \implies x : D + C$
apply (*frule set-plus-mono4*)
apply *auto*
done

lemma *set-zero-plus* [*simp*]: $(0 :: 'a :: \text{comm-monoid-add}) +_o C = C$
by (*auto simp add: elt-set-plus-def*)

lemma *set-zero-plus2*: $(0 :: 'a :: \text{comm-monoid-add}) : A \implies B \leq A + B$
apply (*auto intro!: subsetI simp add: set-plus*)
apply (*rule-tac x = 0 in bexI*)
apply (*rule-tac x = x in bexI*)

apply (auto simp add: add-ac)
done

lemma set-plus-imp-minus: $(a::'a::ab\text{-group-add}) : b + o\ C ==> (a - b) : C$
by (auto simp add: elt-set-plus-def add-ac diff-minus)

lemma set-minus-imp-plus: $(a::'a::ab\text{-group-add}) - b : C ==> a : b + o\ C$
apply (auto simp add: elt-set-plus-def add-ac diff-minus)
apply (subgoal-tac $a = (a + -\ b) + b$)
apply (rule beXI, assumption, assumption)
apply (auto simp add: add-ac)
done

lemma set-minus-plus: $((a::'a::ab\text{-group-add}) - b : C) = (a : b + o\ C)$
by (rule iffI, rule set-minus-imp-plus, assumption, rule set-plus-imp-minus, assumption)

lemma set-times-intro [intro]: $a : C ==> b : D ==> a * b : C * D$
by (auto simp add: set-times)

lemma set-times-intro2 [intro!]: $b : C ==> a * b : a * o\ C$
by (auto simp add: elt-set-times-def)

lemma set-times-rearrange: $((a::'a::comm\text{-monoid-mult}) * o\ C) * (b * o\ D) = (a * b) * o\ (C * D)$
apply (auto simp add: elt-set-times-def set-times)
apply (rule-tac $x = ba * bb$ in exI)
apply (auto simp add: mult-ac)
apply (rule-tac $x = aa * a$ in exI)
apply (auto simp add: mult-ac)
done

lemma set-times-rearrange2: $(a::'a::semigroup-mult) * o\ (b * o\ C) = (a * b) * o\ C$
by (auto simp add: elt-set-times-def mult-assoc)

lemma set-times-rearrange3: $((a::'a::semigroup-mult) * o\ B) * C = a * o\ (B * C)$
apply (auto simp add: elt-set-times-def set-times)
apply (blast intro: mult-ac)
apply (rule-tac $x = a * aa$ in exI)
apply (rule conjI)
apply (rule-tac $x = aa$ in beXI)
apply auto
apply (rule-tac $x = ba$ in beXI)
apply (auto simp add: mult-ac)
done

theorem set-times-rearrange4: $C * ((a::'a::comm\text{-monoid-mult}) * o\ D) =$

```

  a *o (C * D)
apply (auto intro!: subsetI simp add: elt-set-times-def set-times
    mult-ac)
apply (rule-tac x = aa * ba in exI)
apply (auto simp add: mult-ac)
done

```

```

theorems set-times-rearranges = set-times-rearrange set-times-rearrange2
  set-times-rearrange3 set-times-rearrange4

```

```

lemma set-times-mono [intro]: C <= D ==> a *o C <= a *o D
by (auto simp add: elt-set-times-def)

```

```

lemma set-times-mono2 [intro]: (C::('a::times) set) <= D ==> E <= F ==>
  C * E <= D * F
by (auto simp add: set-times)

```

```

lemma set-times-mono3 [intro]: a : C ==> a *o D <= C * D
by (auto simp add: elt-set-times-def set-times)

```

```

lemma set-times-mono4 [intro]: (a::'a::comm-monoid-mult) : C ==>
  a *o D <= D * C
by (auto simp add: elt-set-times-def set-times mult-ac)

```

```

lemma set-times-mono5: a:C ==> B <= D ==> a *o B <= C * D
apply (subgoal-tac a *o B <= a *o D)
apply (erule order-trans)
apply (erule set-times-mono3)
apply (erule set-times-mono)
done

```

```

lemma set-times-mono-b: C <= D ==> x : a *o C
  ==> x : a *o D
apply (frule set-times-mono)
apply auto
done

```

```

lemma set-times-mono2-b: C <= D ==> E <= F ==> x : C * E ==>
  x : D * F
apply (frule set-times-mono2)
prefer 2
apply force
apply assumption
done

```

```

lemma set-times-mono3-b: a : C ==> x : a *o D ==> x : C * D
apply (frule set-times-mono3)
apply auto
done

```

```

lemma set-times-mono4-b: (a::'a::comm-monoid-mult) : C ==>
  x : a *o D ==> x : D * C
  apply (frule set-times-mono4)
  apply auto
done

lemma set-one-times [simp]: (1::'a::comm-monoid-mult) *o C = C
by (auto simp add: elt-set-times-def)

lemma set-times-plus-distrib: (a::'a::semiring) *o (b +o C) =
  (a * b) +o (a *o C)
by (auto simp add: elt-set-plus-def elt-set-times-def ring-distrib)

lemma set-times-plus-distrib2: (a::'a::semiring) *o (B + C) =
  (a *o B) + (a *o C)
  apply (auto simp add: set-plus elt-set-times-def ring-distrib)
  apply blast
  apply (rule-tac x = b + bb in exI)
  apply (auto simp add: ring-distrib)
done

lemma set-times-plus-distrib3: ((a::'a::semiring) +o C) * D <=
  a *o D + C * D
  apply (auto intro!: subsetI simp add:
    elt-set-plus-def elt-set-times-def set-times
    set-plus ring-distrib)
  apply auto
done

theorems set-times-plus-distrib3 = set-times-plus-distrib
  set-times-plus-distrib2

lemma set-neg-intro: (a::'a::ring-1) : (- 1) *o C ==>
  - a : C
by (auto simp add: elt-set-times-def)

lemma set-neg-intro2: (a::'a::ring-1) : C ==>
  - a : (- 1) *o C
by (auto simp add: elt-set-times-def)

end

```

3 BigO: Big O notation

```

theory BigO
imports SetsAndFunctions
begin

```

This library is designed to support asymptotic “big O” calculations, i.e. reasoning with expressions of the form $f = O(g)$ and $f = g + O(h)$. An earlier version of this library is described in detail in [2].

The main changes in this version are as follows:

- We have eliminated the O operator on sets. (Most uses of this seem to be inessential.)
- We no longer use $+$ as output syntax for $+o$
- Lemmas involving *sumr* have been replaced by more general lemmas involving *setsum*.
- The library has been expanded, with e.g. support for expressions of the form $f < g + O(h)$.

See `Complex/ex/BigO_Complex.thy` for additional lemmas that require the `HOL-Complex` logic image.

Note also since the Big O library includes rules that demonstrate set inclusion, to use the automated reasoners effectively with the library one should redeclare the theorem *subsetI* as an intro rule, rather than as an *intro!* rule, for example, using `declare subsetI [del, intro]`.

3.1 Definitions

constdefs

```

bigo :: ('a => 'b::ordered-idom) => ('a => 'b) set  ((1O'(-)))
O(f::('a => 'b)) ==
  {h. EX c. ALL x. abs (h x) <= c * abs (f x)}
```

```

lemma bigo-pos-const: (EX (c::'a::ordered-idom).
  ALL x. (abs (h x) <= (c * (abs (f x))))
  = (EX c. 0 < c & (ALL x. (abs(h x) <= (c * (abs (f x))))))
apply auto
apply (case-tac c = 0)
apply simp
apply (rule-tac x = 1 in exI)
apply simp
apply (rule-tac x = abs c in exI)
apply auto
apply (subgoal-tac c * abs(f x) <= abs c * abs (f x))
apply (erule-tac x = x in allE)
apply force
apply (rule mult-right-mono)
apply (rule abs-ge-self)
apply (rule abs-ge-zero)
done
```

```

lemma bigo-alt-def:  $O(f) =$ 
  { $h.$   $EX\ c. (0 < c \ \&\ (ALL\ x. abs\ (h\ x) \leq c * abs\ (f\ x)))$ }
by (auto simp add: bigo-def bigo-pos-const)

```

```

lemma bigo-elt-subset [intro]:  $f : O(g) \implies O(f) \leq O(g)$ 
  apply (auto simp add: bigo-alt-def)
  apply (rule-tac  $x = ca * c$  in exI)
  apply (rule conjI)
  apply (rule mult-pos-pos)
  apply (assumption)+
  apply (rule allI)
  apply (rule-tac  $x = xa$  in spec) +
  apply (subgoal-tac  $ca * abs(f\ xa) \leq ca * (c * abs(g\ xa))$ )
  apply (erule order-trans)
  apply (simp add: mult-ac)
  apply (rule mult-left-mono, assumption)
  apply (rule order-less-imp-le, assumption)
done

```

```

lemma bigo-refl [intro]:  $f : O(f)$ 
  apply (auto simp add: bigo-def)
  apply (rule-tac  $x = 1$  in exI)
  apply simp
done

```

```

lemma bigo-zero:  $0 : O(g)$ 
  apply (auto simp add: bigo-def func-zero)
  apply (rule-tac  $x = 0$  in exI)
  apply auto
done

```

```

lemma bigo-zero2:  $O(\%x.0) = \{\%x.0\}$ 
  apply (auto simp add: bigo-def)
  apply (rule ext)
  apply auto
done

```

```

lemma bigo-plus-self-subset [intro]:
   $O(f) + O(f) \leq O(f)$ 
  apply (auto simp add: bigo-alt-def set-plus)
  apply (rule-tac  $x = c + ca$  in exI)
  apply auto
  apply (simp add: ring-distrib func-plus)
  apply (rule order-trans)
  apply (rule abs-triangle-ineq)
  apply (rule add-mono)
  apply force
  apply force

```

done

lemma *bigo-plus-idemp* [simp]: $O(f) + O(f) = O(f)$

apply (rule equalityI)

apply (rule bigo-plus-self-subset)

apply (rule set-zero-plus2)

apply (rule bigo-zero)

done

lemma *bigo-plus-subset* [intro]: $O(f + g) \leq O(f) + O(g)$

apply (rule subsetI)

apply (auto simp add: bigo-def bigo-pos-const func-plus set-plus)

apply (subst bigo-pos-const [symmetric])

apply (rule-tac $x =$

$\%n. \text{ if } \text{abs } (g \ n) \leq (\text{abs } (f \ n)) \text{ then } x \ n \text{ else } 0 \text{ in } exI$)

apply (rule conjI)

apply (rule-tac $x = c + c \text{ in } exI$)

apply (clarsimp)

apply (auto)

apply (subgoal-tac $c * \text{abs } (f \ x) + g \ x) \leq (c + c) * \text{abs } (f \ x)$)

apply (erule-tac $x = x \text{ in } allE$)

apply (erule order-trans)

apply (simp)

apply (subgoal-tac $c * \text{abs } (f \ x) + g \ x) \leq c * (\text{abs } (f \ x) + \text{abs } (g \ x))$)

apply (erule order-trans)

apply (simp add: ring-distrib)

apply (rule mult-left-mono)

apply assumption

apply (simp add: order-less-le)

apply (rule mult-left-mono)

apply (simp add: abs-triangle-ineq)

apply (simp add: order-less-le)

apply (rule mult-nonneg-nonneg)

apply (rule add-nonneg-nonneg)

apply auto

apply (rule-tac $x = \%n. \text{ if } (\text{abs } (f \ n)) < \text{abs } (g \ n) \text{ then } x \ n \text{ else } 0$
 in exI)

apply (rule conjI)

apply (rule-tac $x = c + c \text{ in } exI$)

apply auto

apply (subgoal-tac $c * \text{abs } (f \ x) + g \ x) \leq (c + c) * \text{abs } (g \ x)$)

apply (erule-tac $x = x \text{ in } allE$)

apply (erule order-trans)

apply (simp)

apply (subgoal-tac $c * \text{abs } (f \ x) + g \ x) \leq c * (\text{abs } (f \ x) + \text{abs } (g \ x))$)

apply (erule order-trans)

apply (simp add: ring-distrib)

apply (rule mult-left-mono)

apply (simp add: order-less-le)

```

apply (simp add: order-less-le)
apply (rule mult-left-mono)
apply (rule abs-triangle-ineq)
apply (simp add: order-less-le)
apply (rule mult-nonneg-nonneg)
apply (rule add-nonneg-nonneg)
apply (erule order-less-imp-le)+
apply simp
apply (rule ext)
apply (auto simp add: if-splits linorder-not-le)
done

```

```

lemma bigo-plus-subset2 [intro]:  $A \leq O(f) \implies B \leq O(f) \implies A + B \leq O(f)$ 
apply (subgoal-tac  $A + B \leq O(f) + O(f)$ )
apply (erule order-trans)
apply simp
apply (auto del: subsetI simp del: bigo-plus-idemp)
done

```

```

lemma bigo-plus-eq:  $\text{ALL } x. 0 \leq f x \implies \text{ALL } x. 0 \leq g x \implies O(f + g) = O(f) + O(g)$ 
apply (rule equalityI)
apply (rule bigo-plus-subset)
apply (simp add: bigo-alt-def set-plus func-plus)
apply clarify
apply (rule-tac  $x = \max c \text{ ca in } exI$ )
apply (rule conjI)
apply (subgoal-tac  $c \leq \max c \text{ ca}$ )
apply (erule order-less-le-trans)
apply assumption
apply (rule le-maxI1)
apply clarify
apply (drule-tac  $x = xa \text{ in spec}$ )+
apply (subgoal-tac  $0 \leq f xa + g xa$ )
apply (simp add: ring-distrib)
apply (subgoal-tac  $\text{abs}(a xa + b xa) \leq \text{abs}(a xa) + \text{abs}(b xa)$ )
apply (subgoal-tac  $\text{abs}(a xa) + \text{abs}(b xa) \leq \max c \text{ ca} * f xa + \max c \text{ ca} * g xa$ )
apply (force)
apply (rule add-mono)
apply (subgoal-tac  $c * f xa \leq \max c \text{ ca} * f xa$ )
apply (force)
apply (rule mult-right-mono)
apply (rule le-maxI1)
apply assumption
apply (subgoal-tac  $\text{ca} * g xa \leq \max c \text{ ca} * g xa$ )
apply (force)
apply (rule mult-right-mono)

```



```

apply (rule le-maxI2)
apply assumption
apply (rule abs-triangle-ineq)
apply (rule add-nonneg-nonneg)
apply assumption+
done

```

```

lemma bigo-bounded-alt:  $ALL\ x.\ 0 \leq f\ x \implies ALL\ x.\ f\ x \leq c * g\ x \implies$ 
   $f : O(g)$ 
apply (auto simp add: bigo-def)
apply (rule-tac  $x = abs\ c$  in  $exI$ )
apply auto
apply (drule-tac  $x = x$  in  $spec$ ) +
apply (simp add: abs-mult [symmetric])
done

```

```

lemma bigo-bounded:  $ALL\ x.\ 0 \leq f\ x \implies ALL\ x.\ f\ x \leq g\ x \implies$ 
   $f : O(g)$ 
apply (erule bigo-bounded-alt [of  $f\ 1\ g$ ])
apply simp
done

```

```

lemma bigo-bounded2:  $ALL\ x.\ lb\ x \leq f\ x \implies ALL\ x.\ f\ x \leq lb\ x + g\ x \implies$ 
   $f : lb +_o O(g)$ 
apply (rule set-minus-imp-plus)
apply (rule bigo-bounded)
apply (auto simp add: diff-minus func-minus func-plus)
apply (drule-tac  $x = x$  in  $spec$ ) +
apply force
apply (drule-tac  $x = x$  in  $spec$ ) +
apply force
done

```

```

lemma bigo-abs:  $(\%x.\ abs(f\ x)) =_o O(f)$ 
apply (unfold bigo-def)
apply auto
apply (rule-tac  $x = 1$  in  $exI$ )
apply auto
done

```

```

lemma bigo-abs2:  $f =_o O(\%x.\ abs(f\ x))$ 
apply (unfold bigo-def)
apply auto
apply (rule-tac  $x = 1$  in  $exI$ )
apply auto
done

```

```

lemma bigo-abs3:  $O(f) = O(\%x.\ abs(f\ x))$ 
apply (rule equalityI)

```

```

apply (rule bigo-elt-subset)
apply (rule bigo-abs2)
apply (rule bigo-elt-subset)
apply (rule bigo-abs)
done

```

```

lemma bigo-abs4:  $f =_o g +_o O(h) \implies$ 
  ( $\%x. \text{abs } (f \ x) =_o (\%x. \text{abs } (g \ x)) +_o O(h)$ )
apply (drule set-plus-imp-minus)
apply (rule set-minus-imp-plus)
apply (subst func-diff)
proof –
  assume  $a: f - g : O(h)$ 
  have ( $\%x. \text{abs } (f \ x) - \text{abs } (g \ x) =_o O(\%x. \text{abs}(\text{abs } (f \ x) - \text{abs } (g \ x)))$ )
    by (rule bigo-abs2)
  also have  $\dots \leq O(\%x. \text{abs } (f \ x - g \ x))$ 
    apply (rule bigo-elt-subset)
    apply (rule bigo-bounded)
    apply force
    apply (rule allI)
    apply (rule abs-triangle-ineq3)
    done
  also have  $\dots \leq O(f - g)$ 
    apply (rule bigo-elt-subset)
    apply (subst func-diff)
    apply (rule bigo-abs)
    done
  also have  $\dots \leq O(h)$ 
    by (rule bigo-elt-subset)
  finally show ( $\%x. \text{abs } (f \ x) - \text{abs } (g \ x) : O(h)$ ).
qed

```

```

lemma bigo-abs5:  $f =_o O(g) \implies (\%x. \text{abs}(f \ x)) =_o O(g)$ 
by (unfold bigo-def, auto)

```

```

lemma bigo-elt-subset2 [intro]:  $f : g +_o O(h) \implies O(f) \leq O(g) + O(h)$ 
proof –
  assume  $f : g +_o O(h)$ 
  also have  $\dots \leq O(g) + O(h)$ 
    by (auto del: subsetI)
  also have  $\dots = O(\%x. \text{abs}(g \ x)) + O(\%x. \text{abs}(h \ x))$ 
    apply (subst bigo-abs3 [symmetric])
    apply (rule refl)
    done
  also have  $\dots = O((\%x. \text{abs}(g \ x)) + (\%x. \text{abs}(h \ x)))$ 
    by (rule bigo-plus-eq [symmetric], auto)
  finally have  $f : \dots$ 
  then have  $O(f) \leq \dots$ 
    by (elim bigo-elt-subset)

```

```

also have ... = O(%x. abs(g x)) + O(%x. abs(h x))
  by (rule bigo-plus-eq, auto)
finally show ?thesis
  by (simp add: bigo-abs3 [symmetric])
qed

```

```

lemma bigo-mult [intro]: O(f)*O(g) <= O(f * g)
  apply (rule subsetI)
  apply (subst bigo-def)
  apply (auto simp add: bigo-alt-def set-times func-times)
  apply (rule-tac x = c * ca in exI)
  apply (rule allI)
  apply (erule-tac x = x in allE)+
  apply (subgoal-tac c * ca * abs(f x * g x) =
    (c * abs(f x)) * (ca * abs(g x)))
  apply (erule ssubst)
  apply (subst abs-mult)
  apply (rule mult-mono)
  apply assumption+
  apply (rule mult-nonneg-nonneg)
  apply auto
  apply (simp add: mult-ac abs-mult)
done

```

```

lemma bigo-mult2 [intro]: f *o O(g) <= O(f * g)
  apply (auto simp add: bigo-def elt-set-times-def func-times abs-mult)
  apply (rule-tac x = c in exI)
  apply auto
  apply (drule-tac x = x in spec)
  apply (subgoal-tac abs(f x) * abs(b x) <= abs(f x) * (c * abs(g x)))
  apply (force simp add: mult-ac)
  apply (rule mult-left-mono, assumption)
  apply (rule abs-ge-zero)
done

```

```

lemma bigo-mult3: f : O(h) ==> g : O(j) ==> f * g : O(h * j)
  apply (rule subsetD)
  apply (rule bigo-mult)
  apply (erule set-times-intro, assumption)
done

```

```

lemma bigo-mult4 [intro]: f : k +o O(h) ==> g * f : (g * k) +o O(g * h)
  apply (drule set-plus-imp-minus)
  apply (rule set-minus-imp-plus)
  apply (drule bigo-mult3 [where g = g and j = g])
  apply (auto simp add: ring-eq-simps mult-ac)
done

```

```

lemma bigo-mult5: ALL x. f x ~ = 0 ==>

```

```

    O(f * g) <= (f::'a => ('b::ordered-field)) *o O(g)
proof -
  assume ALL x. f x ~ = 0
  show O(f * g) <= f *o O(g)
proof
  fix h
  assume h : O(f * g)
  then have (%x. 1 / (f x)) * h : (%x. 1 / f x) *o O(f * g)
    by auto
  also have ... <= O((%x. 1 / f x) * (f * g))
    by (rule bigo-mult2)
  also have (%x. 1 / f x) * (f * g) = g
    apply (simp add: func-times)
    apply (rule ext)
    apply (simp add: prems nonzero-divide-eq-eq mult-ac)
  done
  finally have (%x. (1::'b) / f x) * h : O(g).
  then have f * ((%x. (1::'b) / f x) * h) : f *o O(g)
    by auto
  also have f * ((%x. (1::'b) / f x) * h) = h
    apply (simp add: func-times)
    apply (rule ext)
    apply (simp add: prems nonzero-divide-eq-eq mult-ac)
  done
  finally show h : f *o O(g).
qed
qed

lemma bigo-mult6: ALL x. f x ~ = 0 ==>
  O(f * g) = (f::'a => ('b::ordered-field)) *o O(g)
  apply (rule equalityI)
  apply (erule bigo-mult5)
  apply (rule bigo-mult2)
done

lemma bigo-mult7: ALL x. f x ~ = 0 ==>
  O(f * g) <= O(f::'a => ('b::ordered-field)) * O(g)
  apply (subst bigo-mult6)
  apply assumption
  apply (rule set-times-mono3)
  apply (rule bigo-refl)
done

lemma bigo-mult8: ALL x. f x ~ = 0 ==>
  O(f * g) = O(f::'a => ('b::ordered-field)) * O(g)
  apply (rule equalityI)
  apply (erule bigo-mult7)
  apply (rule bigo-mult)
done

```

```

lemma bigo-minus [intro]:  $f : O(g) ==> -f : O(g)$ 
  by (auto simp add: bigo-def func-minus)

lemma bigo-minus2:  $f : g +o O(h) ==> -f : -g +o O(h)$ 
  apply (rule set-minus-imp-plus)
  apply (drule set-plus-imp-minus)
  apply (drule bigo-minus)
  apply (simp add: diff-minus)
done

lemma bigo-minus3:  $O(-f) = O(f)$ 
  by (auto simp add: bigo-def func-minus abs-minus-cancel)

lemma bigo-plus-absorb-lemma1:  $f : O(g) ==> f +o O(g) <= O(g)$ 
proof -
  assume a:  $f : O(g)$ 
  show  $f +o O(g) <= O(g)$ 
  proof -
    have  $f : O(f)$  by auto
    then have  $f +o O(g) <= O(f) + O(g)$ 
      by (auto del: subsetI)
    also have  $\dots <= O(g) + O(g)$ 
    proof -
      from a have  $O(f) <= O(g)$  by (auto del: subsetI)
      thus ?thesis by (auto del: subsetI)
    qed
    also have  $\dots <= O(g)$  by (simp add: bigo-plus-idemp)
    finally show ?thesis .
  qed
qed

lemma bigo-plus-absorb-lemma2:  $f : O(g) ==> O(g) <= f +o O(g)$ 
proof -
  assume a:  $f : O(g)$ 
  show  $O(g) <= f +o O(g)$ 
  proof -
    from a have  $-f : O(g)$  by auto
    then have  $-f +o O(g) <= O(g)$  by (elim bigo-plus-absorb-lemma1)
    then have  $f +o (-f +o O(g)) <= f +o O(g)$  by auto
    also have  $f +o (-f +o O(g)) = O(g)$ 
      by (simp add: set-plus-rearranges)
    finally show ?thesis .
  qed
qed

lemma bigo-plus-absorb [simp]:  $f : O(g) ==> f +o O(g) = O(g)$ 
  apply (rule equalityI)
  apply (erule bigo-plus-absorb-lemma1)

```

apply (erule bigo-plus-absorb-lemma2)
done

lemma bigo-plus-absorb2 [intro]: $f : O(g) \implies A \leq O(g) \implies f + o A \leq O(g)$
apply (subgoal-tac $f + o A \leq f + o O(g)$)
apply force+
done

lemma bigo-add-commute-imp: $f : g + o O(h) \implies g : f + o O(h)$
apply (subst set-minus-plus [symmetric])
apply (subgoal-tac $g - f = -(f - g)$)
apply (erule ssubst)
apply (rule bigo-minus)
apply (subst set-minus-plus)
apply assumption
apply (simp add: diff-minus add-ac)
done

lemma bigo-add-commute: $(f : g + o O(h)) = (g : f + o O(h))$
apply (rule iffI)
apply (erule bigo-add-commute-imp)+
done

lemma bigo-const1: $(\%x. c) : O(\%x. 1)$
by (auto simp add: bigo-def mult-ac)

lemma bigo-const2 [intro]: $O(\%x. c) \leq O(\%x. 1)$
apply (rule bigo-elt-subset)
apply (rule bigo-const1)
done

lemma bigo-const3: $(c::'a::ordered-field) \sim 0 \implies (\%x. 1) : O(\%x. c)$
apply (simp add: bigo-def)
apply (rule-tac $x = \text{abs}(\text{inverse } c)$ in exI)
apply (simp add: abs-mult [symmetric])
done

lemma bigo-const4: $(c::'a::ordered-field) \sim 0 \implies O(\%x. 1) \leq O(\%x. c)$
by (rule bigo-elt-subset, rule bigo-const3, assumption)

lemma bigo-const [simp]: $(c::'a::ordered-field) \sim 0 \implies O(\%x. c) = O(\%x. 1)$
by (rule equalityI, rule bigo-const2, rule bigo-const4, assumption)

lemma bigo-const-mult1: $(\%x. c * f x) : O(f)$
apply (simp add: bigo-def)
apply (rule-tac $x = \text{abs}(c)$ in exI)
apply (auto simp add: abs-mult [symmetric])

done

lemma *bigo-const-mult2*: $O(\%x. c * f x) \leq O(f)$
by (rule *bigo-elt-subset*, rule *bigo-const-mult1*)

lemma *bigo-const-mult3*: $(c::'a::\text{ordered-field}) \sim 0 \implies f : O(\%x. c * f x)$
apply (simp add: *bigo-def*)
apply (rule-tac $x = \text{abs}(\text{inverse } c)$ **in** *exI*)
apply (simp add: *abs-mult* [*symmetric*] *mult-assoc* [*symmetric*])
done

lemma *bigo-const-mult4*: $(c::'a::\text{ordered-field}) \sim 0 \implies$
 $O(f) \leq O(\%x. c * f x)$
by (rule *bigo-elt-subset*, rule *bigo-const-mult3*, *assumption*)

lemma *bigo-const-mult* [*simp*]: $(c::'a::\text{ordered-field}) \sim 0 \implies$
 $O(\%x. c * f x) = O(f)$
by (rule *equalityI*, rule *bigo-const-mult2*, *erule* *bigo-const-mult4*)

lemma *bigo-const-mult5* [*simp*]: $(c::'a::\text{ordered-field}) \sim 0 \implies$
 $(\%x. c) * o O(f) = O(f)$
apply (auto del: *subsetI*)
apply (rule *order-trans*)
apply (rule *bigo-mult2*)
apply (simp add: *func-times*)
apply (auto intro!: *subsetI* simp add: *bigo-def* *elt-set-times-def* *func-times*)
apply (rule-tac $x = \%y. \text{inverse } c * x y$ **in** *exI*)
apply (simp add: *mult-assoc* [*symmetric*] *abs-mult*)
apply (rule-tac $x = \text{abs}(\text{inverse } c) * ca$ **in** *exI*)
apply (rule *allI*)
apply (subst *mult-assoc*)
apply (rule *mult-left-mono*)
apply (*erule spec*)
apply *force*
done

lemma *bigo-const-mult6* [*intro*]: $(\%x. c) * o O(f) \leq O(f)$
apply (auto intro!: *subsetI*)
 simp add: *bigo-def* *elt-set-times-def* *func-times*
apply (rule-tac $x = ca * (\text{abs } c)$ **in** *exI*)
apply (rule *allI*)
apply (subgoal-tac $ca * \text{abs}(c) * \text{abs}(f x) = \text{abs}(c) * (ca * \text{abs}(f x))$)
apply (*erule ssubst*)
apply (subst *abs-mult*)
apply (rule *mult-left-mono*)
apply (*erule spec*)
apply *simp*
apply (simp add: *mult-ac*)
done

```

lemma bigo-const-mult7 [intro]:  $f =_o O(g) \implies (\%x. c * f x) =_o O(g)$ 
proof –
  assume  $f =_o O(g)$ 
  then have  $(\%x. c) * f =_o (\%x. c) *_o O(g)$ 
    by auto
  also have  $(\%x. c) * f = (\%x. c * f x)$ 
    by (simp add: func-times)
  also have  $(\%x. c) *_o O(g) \leq O(g)$ 
    by (auto del: subsetI)
  finally show ?thesis .
qed

lemma bigo-compose1:  $f =_o O(g) \implies (\%x. f(k x)) =_o O(\%x. g(k x))$ 
by (unfold bigo-def, auto)

lemma bigo-compose2:  $f =_o g +_o O(h) \implies (\%x. f(k x)) =_o (\%x. g(k x)) +_o O(\%x. h(k x))$ 
  apply (simp only: set-minus-plus [symmetric] diff-minus func-minus func-plus)
  apply (erule bigo-compose1)
done

```

3.2 Setsum

```

lemma bigo-setsum-main:  $\text{ALL } x. \text{ALL } y : A x. 0 \leq h x y \implies$ 
   $\text{EX } c. \text{ALL } x. \text{ALL } y : A x. \text{abs}(f x y) \leq c * (h x y) \implies$ 
   $(\%x. \text{SUM } y : A x. f x y) =_o O(\%x. \text{SUM } y : A x. h x y)$ 
  apply (auto simp add: bigo-def)
  apply (rule-tac x = abs c in exI)
  apply (subst abs-of-nonneg) back back
  apply (rule setsum-nonneg)
  apply force
  apply (subst setsum-mult)
  apply (rule allI)
  apply (rule order-trans)
  apply (rule setsum-abs)
  apply (rule setsum-mono)
  apply (rule order-trans)
  apply (drule spec) +
  apply (drule bspec) +
  apply assumption +
  apply (drule bspec)
  apply assumption +
  apply (rule mult-right-mono)
  apply (rule abs-ge-self)
  apply force
done

```



```

lemma bigo-setsum1:  $ALL\ x\ y.\ 0 \leq h\ x\ y \implies$ 
   $EX\ c.\ ALL\ x\ y.\ abs(f\ x\ y) \leq c * (h\ x\ y) \implies$ 
   $(\%x.\ SUM\ y : A\ x.\ f\ x\ y) =_o O(\%x.\ SUM\ y : A\ x.\ h\ x\ y)$ 
apply (rule bigo-setsum-main)
apply force
apply clarsimp
apply (rule-tac  $x = c$  in  $exI$ )
apply force
done

```

```

lemma bigo-setsum2:  $ALL\ y.\ 0 \leq h\ y \implies$ 
   $EX\ c.\ ALL\ y.\ abs(f\ y) \leq c * (h\ y) \implies$ 
   $(\%x.\ SUM\ y : A\ x.\ f\ y) =_o O(\%x.\ SUM\ y : A\ x.\ h\ y)$ 
by (rule bigo-setsum1, auto)

```

```

lemma bigo-setsum3:  $f =_o O(h) \implies$ 
   $(\%x.\ SUM\ y : A\ x.\ (l\ x\ y) * f(k\ x\ y)) =_o$ 
   $O(\%x.\ SUM\ y : A\ x.\ abs(l\ x\ y * h(k\ x\ y)))$ 
apply (rule bigo-setsum1)
apply (rule allI)+
apply (rule abs-ge-zero)
apply (unfold bigo-def)
apply auto
apply (rule-tac  $x = c$  in  $exI$ )
apply (rule allI)+
apply (subst abs-mult)+
apply (subst mult-left-commute)
apply (rule mult-left-mono)
apply (erule spec)
apply (rule abs-ge-zero)
done

```

```

lemma bigo-setsum4:  $f =_o g +_o O(h) \implies$ 
   $(\%x.\ SUM\ y : A\ x.\ l\ x\ y * f(k\ x\ y)) =_o$ 
   $(\%x.\ SUM\ y : A\ x.\ l\ x\ y * g(k\ x\ y)) +_o$ 
   $O(\%x.\ SUM\ y : A\ x.\ abs(l\ x\ y * h(k\ x\ y)))$ 
apply (rule set-minus-imp-plus)
apply (subst func-diff)
apply (subst setsum-subtractf [symmetric])
apply (subst right-diff-distrib [symmetric])
apply (rule bigo-setsum3)
apply (subst func-diff [symmetric])
apply (erule set-plus-imp-minus)
done

```

```

lemma bigo-setsum5:  $f =_o O(h) \implies ALL\ x\ y.\ 0 \leq l\ x\ y \implies$ 
   $ALL\ x.\ 0 \leq h\ x \implies$ 
   $(\%x.\ SUM\ y : A\ x.\ (l\ x\ y) * f(k\ x\ y)) =_o$ 
   $O(\%x.\ SUM\ y : A\ x.\ (l\ x\ y) * h(k\ x\ y))$ 

```

```

apply (subgoal-tac (%x. SUM y : A x. (l x y) * h(k x y)) =
  (%x. SUM y : A x. abs((l x y) * h(k x y))))
apply (erule ssubst)
apply (erule bigo-setsum3)
apply (rule ext)
apply (rule setsum-cong2)
apply (subst abs-of-nonneg)
apply (rule mult-nonneg-nonneg)
apply auto
done

```

```

lemma bigo-setsum6: f =o g +o O(h) ==> ALL x y. 0 <= l x y ==>
  ALL x. 0 <= h x ==>
  (%x. SUM y : A x. (l x y) * f(k x y)) =o
  (%x. SUM y : A x. (l x y) * g(k x y)) +o
  O(%x. SUM y : A x. (l x y) * h(k x y))
apply (rule set-minus-imp-plus)
apply (subst func-diff)
apply (subst setsum-subtractf [symmetric])
apply (subst right-diff-distrib [symmetric])
apply (rule bigo-setsum5)
apply (subst func-diff [symmetric])
apply (erule set-plus-imp-minus)
apply auto
done

```

3.3 Misc useful stuff

```

lemma bigo-useful-intro: A <= O(f) ==> B <= O(f) ==>
  A + B <= O(f)
apply (subst bigo-plus-idemp [symmetric])
apply (rule set-plus-mono2)
apply assumption+
done

```

```

lemma bigo-useful-add: f =o O(h) ==> g =o O(h) ==> f + g =o O(h)
apply (subst bigo-plus-idemp [symmetric])
apply (rule set-plus-intro)
apply assumption+
done

```

```

lemma bigo-useful-const-mult: (c::'a::ordered-field) ~= 0 ==>
  (%x. c) * f =o O(h) ==> f =o O(h)
apply (rule subsetD)
apply (subgoal-tac (%x. 1 / c) *o O(h) <= O(h))
apply assumption
apply (rule bigo-const-mult6)
apply (subgoal-tac f = (%x. 1 / c) * ((%x. c) * f))
apply (erule ssubst)

```

```

apply (erule set-times-intro2)
apply (simp add: func-times)
apply (erule ext)
apply (subst times-divide-eq-left [symmetric])
apply (subst divide-self)
apply (assumption, simp)
done

```

```

lemma bigo-fix: (%x. f ((x::nat) + 1)) =o O(%x. h(x + 1)) ==> f 0 = 0 ==>
  f =o O(h)
apply (simp add: bigo-alt-def)
apply auto
apply (rule-tac x = c in exI)
apply auto
apply (case-tac x = 0)
apply simp
apply (rule mult-nonneg-nonneg)
apply force
apply force
apply (subgoal-tac x = Suc (x - 1))
apply (erule ssubst) back
apply (erule spec)
apply simp
done

```

```

lemma bigo-fix2:
  (%x. f ((x::nat) + 1)) =o (%x. g(x + 1)) +o O(%x. h(x + 1)) ==>
  f 0 = g 0 ==> f =o g +o O(h)
apply (rule set-minus-imp-plus)
apply (rule bigo-fix)
apply (subst func-diff)
apply (subst func-diff [symmetric])
apply (rule set-plus-imp-minus)
apply simp
apply (simp add: func-diff)
done

```

3.4 Less than or equal to

constdefs

```

  lesso :: ('a => 'b::ordered-idom) => ('a => 'b) => ('a => 'b)
  (infixl <o 70)
  f <o g == (%x. max (f x - g x) 0)

```

```

lemma bigo-lesseq1: f =o O(h) ==> ALL x. abs (g x) <= abs (f x) ==>
  g =o O(h)
apply (unfold bigo-def)
apply clarsimp
apply (rule-tac x = c in exI)

```

```

  apply (rule allI)
  apply (rule order-trans)
  apply (erule spec)+
done

```

```

lemma bigo-lesseq2:  $f =_o O(h) \implies \text{ALL } x. \text{abs } (g \ x) \leq f \ x \implies$ 
   $g =_o O(h)$ 
  apply (erule bigo-lesseq1)
  apply (rule allI)
  apply (drule-tac  $x = x$  in spec)
  apply (rule order-trans)
  apply assumption
  apply (rule abs-ge-self)
done

```

```

lemma bigo-lesseq3:  $f =_o O(h) \implies \text{ALL } x. 0 \leq g \ x \implies \text{ALL } x. g \ x \leq f \ x \implies$ 
 $x \implies$ 
   $g =_o O(h)$ 
  apply (erule bigo-lesseq2)
  apply (rule allI)
  apply (subst abs-of-nonneg)
  apply (erule spec)+
done

```

```

lemma bigo-lesseq4:  $f =_o O(h) \implies$ 
   $\text{ALL } x. 0 \leq g \ x \implies \text{ALL } x. g \ x \leq \text{abs } (f \ x) \implies$ 
 $g =_o O(h)$ 
  apply (erule bigo-lesseq1)
  apply (rule allI)
  apply (subst abs-of-nonneg)
  apply (erule spec)+
done

```

```

lemma bigo-lesso1:  $\text{ALL } x. f \ x \leq g \ x \implies f <_o g =_o O(h)$ 
  apply (unfold less-def)
  apply (subgoal-tac (%x. max (f x - g x) 0) = 0)
  apply (erule ssubst)
  apply (rule bigo-zero)
  apply (unfold func-zero)
  apply (rule ext)
  apply (simp split: split-max)
done

```

```

lemma bigo-lesso2:  $f =_o g +_o O(h) \implies$ 
   $\text{ALL } x. 0 \leq k \ x \implies \text{ALL } x. k \ x \leq f \ x \implies$ 
 $k <_o g =_o O(h)$ 
  apply (unfold less-def)
  apply (rule bigo-lesseq4)
  apply (erule set-plus-imp-minus)

```

```

apply (rule allI)
apply (rule le-maxI2)
apply (rule allI)
apply (subst func-diff)
apply (case-tac 0 <= k x - g x)
apply simp
apply (subst abs-of-nonneg)
apply (drule-tac x = x in spec) back
apply (simp add: compare-rls)
apply (subst diff-minus)+
apply (rule add-right-mono)
apply (erule spec)
apply (rule order-trans)
prefer 2
apply (rule abs-ge-zero)
apply (simp add: compare-rls)
done

```

```

lemma bigo-lesso3: f =o g +o O(h) ==>
  ALL x. 0 <= k x ==> ALL x. g x <= k x ==>
  f <o k =o O(h)
apply (unfold lessso-def)
apply (rule bigo-lesseq4)
apply (erule set-plus-imp-minus)
apply (rule allI)
apply (rule le-maxI2)
apply (rule allI)
apply (subst func-diff)
apply (case-tac 0 <= f x - k x)
apply simp
apply (subst abs-of-nonneg)
apply (drule-tac x = x in spec) back
apply (simp add: compare-rls)
apply (subst diff-minus)+
apply (rule add-left-mono)
apply (rule le-imp-neg-le)
apply (erule spec)
apply (rule order-trans)
prefer 2
apply (rule abs-ge-zero)
apply (simp add: compare-rls)
done

```

```

lemma bigo-lesso4: f <o g =o O(k::'a=>'b::ordered-field) ==>
  g =o h +o O(k) ==> f <o h =o O(k)
apply (unfold lessso-def)
apply (drule set-plus-imp-minus)
apply (drule bigo-abs5) back
apply (simp add: func-diff)

```

```

apply (drule bigo-useful-add)
apply assumption
apply (erule bigo-lesseq2) back
apply (rule allI)
apply (auto simp add: func-plus func-diff compare-rls
  split: split-max abs-split)
done

lemma bigo-lesso5:  $f <_o g =_o O(h) \implies$ 
  EX C. ALL x.  $f\ x \leq g\ x + C * \text{abs}(h\ x)$ 
apply (simp only: less-def bigo-alt-def)
apply clarsimp
apply (rule-tac  $x = c$  in exI)
apply (rule allI)
apply (drule-tac  $x = x$  in spec)
apply (subgoal-tac  $\text{abs}(\max(f\ x - g\ x)\ 0) = \max(f\ x - g\ x)\ 0$ )
apply (clarsimp simp add: compare-rls add-ac)
apply (rule abs-of-nonneg)
apply (rule le-maxI2)
done

lemma less-add:  $f <_o g =_o O(h) \implies$ 
   $k <_o l =_o O(h) \implies (f + k) <_o (g + l) =_o O(h)$ 
apply (unfold less-def)
apply (rule bigo-lesseq3)
apply (erule bigo-useful-add)
apply assumption
apply (force split: split-max)
apply (auto split: split-max simp add: func-plus)
done

end

```

4 Continuity: Continuity and iterations (of set transformers)

```

theory Continuity
imports Main
begin

```

4.1 Chains

```

constdefs
  up-chain ::  $(\text{nat} \Rightarrow 'a\ \text{set}) \Rightarrow \text{bool}$ 
  up-chain F ==  $\forall i. F\ i \subseteq F\ (\text{Suc}\ i)$ 

lemma up-chainI:  $(!!i. F\ i \subseteq F\ (\text{Suc}\ i)) \implies \text{up-chain}\ F$ 

```

```

by (simp add: up-chain-def)

lemma up-chainD: up-chain F ==> F i ⊆ F (Suc i)
by (simp add: up-chain-def)

lemma up-chain-less-mono [rule-format]:
  up-chain F ==> x < y --> F x ⊆ F y
apply (induct-tac y)
apply (blast dest: up-chainD elim: less-SucE)+
done

lemma up-chain-mono: up-chain F ==> x ≤ y ==> F x ⊆ F y
apply (drule le-imp-less-or-eq)
apply (blast dest: up-chain-less-mono)
done

constdefs
  down-chain :: (nat => 'a set) => bool
  down-chain F == ∀ i. F (Suc i) ⊆ F i

lemma down-chainI: (!i. F (Suc i) ⊆ F i) ==> down-chain F
by (simp add: down-chain-def)

lemma down-chainD: down-chain F ==> F (Suc i) ⊆ F i
by (simp add: down-chain-def)

lemma down-chain-less-mono [rule-format]:
  down-chain F ==> x < y --> F y ⊆ F x
apply (induct-tac y)
apply (blast dest: down-chainD elim: less-SucE)+
done

lemma down-chain-mono: down-chain F ==> x ≤ y ==> F y ⊆ F x
apply (drule le-imp-less-or-eq)
apply (blast dest: down-chain-less-mono)
done

## 4.2 Continuity

constdefs
  up-cont :: ('a set => 'a set) => bool
  up-cont f == ∀ F. up-chain F --> f (⋃ (range F)) = ⋃ (f ` range F)

lemma up-contI:
  (!F. up-chain F ==> f (⋃ (range F)) = ⋃ (f ` range F)) ==> up-cont f
apply (unfold up-cont-def)
apply blast
done

```

lemma *up-contD*:

up-cont $f \implies$ *up-chain* $F \implies f (\bigcup (\text{range } F)) = \bigcup (f \text{ ‘ range } F)$
apply (*unfold up-cont-def*)
apply *auto*
done

lemma *up-cont-mono*: *up-cont* $f \implies$ *mono* f

apply (*rule monoI*)
apply (*drule-tac* $F = \lambda i. \text{ if } i = 0 \text{ then } A \text{ else } B$ **in** *up-contD*)
apply (*rule up-chainI*)
apply *simp+*
apply (*drule Un-absorb1*)
apply (*auto simp add: nat-not-singleton*)
done

constdefs

down-cont :: (*'a set* \implies *'a set*) \implies *bool*
down-cont $f ==$
 $\forall F. \text{ down-chain } F \dashrightarrow f (\text{Inter } (\text{range } F)) = \text{Inter } (f \text{ ‘ range } F)$

lemma *down-contI*:

($\forall F. \text{ down-chain } F \implies f (\text{Inter } (\text{range } F)) = \text{Inter } (f \text{ ‘ range } F)$) \implies
down-cont f
apply (*unfold down-cont-def*)
apply *blast*
done

lemma *down-contD*: *down-cont* $f \implies$ *down-chain* $F \implies$

$f (\text{Inter } (\text{range } F)) = \text{Inter } (f \text{ ‘ range } F)$
apply (*unfold down-cont-def*)
apply *auto*
done

lemma *down-cont-mono*: *down-cont* $f \implies$ *mono* f

apply (*rule monoI*)
apply (*drule-tac* $F = \lambda i. \text{ if } i = 0 \text{ then } B \text{ else } A$ **in** *down-contD*)
apply (*rule down-chainI*)
apply *simp+*
apply (*drule Int-absorb1*)
apply (*auto simp add: nat-not-singleton*)
done

4.3 Iteration

constdefs

up-iterate :: (*'a set* \implies *'a set*) \implies *nat* \implies *'a set*

$up\text{-}iterate\ f\ n == (f^n)\ \{\}$

lemma *up-iterate-0* [*simp*]: $up\text{-}iterate\ f\ 0 = \{\}$
by (*simp add: up-iterate-def*)

lemma *up-iterate-Suc* [*simp*]: $up\text{-}iterate\ f\ (Suc\ i) = f\ (up\text{-}iterate\ f\ i)$
by (*simp add: up-iterate-def*)

lemma *up-iterate-chain*: $mono\ F ==> up\text{-}chain\ (up\text{-}iterate\ F)$
apply (*rule up-chainI*)
apply (*induct-tac i*)
apply *simp+*
apply (*erule (1) monoD*)
done

lemma *UNION-up-iterate-is-fp*:
 $up\text{-}cont\ F ==>$
 $F\ (UNION\ UNIV\ (up\text{-}iterate\ F)) = UNION\ UNIV\ (up\text{-}iterate\ F)$
apply (*frule up-cont-mono [THEN up-iterate-chain]*)
apply (*drule (1) up-contD*)
apply *simp*
apply (*auto simp del: up-iterate-Suc simp add: up-iterate-Suc [symmetric]*)
apply (*case-tac xa*)
apply *auto*
done

lemma *UNION-up-iterate-lowerbound*:
 $mono\ F ==> F\ P = P ==> UNION\ UNIV\ (up\text{-}iterate\ F) \subseteq P$
apply (*subgoal-tac (!i. up-iterate F i \subseteq P)*)
apply *fast*
apply (*induct-tac i*)
prefer 2 **apply** (*drule (1) monoD*)
apply *auto*
done

lemma *UNION-up-iterate-is-lfp*:
 $up\text{-}cont\ F ==> lfp\ F = UNION\ UNIV\ (up\text{-}iterate\ F)$
apply (*rule set-eq-subset [THEN iffD2]*)
apply (*rule conjI*)
prefer 2
apply (*drule up-cont-mono*)
apply (*rule UNION-up-iterate-lowerbound*)
apply *assumption*
apply (*erule lfp-unfold [symmetric]*)
apply (*rule lfp-lowerbound*)
apply (*rule set-eq-subset [THEN iffD1, THEN conjunct2]*)
apply (*erule UNION-up-iterate-is-fp [symmetric]*)
done

constdefs

down-iterate :: ('a set => 'a set) => nat => 'a set
down-iterate f n == (f^n) UNIV

lemma *down-iterate-0* [simp]: *down-iterate* f 0 = UNIV
by (simp add: *down-iterate-def*)

lemma *down-iterate-Suc* [simp]:
down-iterate f (Suc i) = f (*down-iterate* f i)
by (simp add: *down-iterate-def*)

lemma *down-iterate-chain*: *mono* F ==> *down-chain* (*down-iterate* F)
apply (rule *down-chainI*)
apply (induct-tac i)
apply simp+
apply (erule (1) *monoD*)
done

lemma *INTER-down-iterate-is-fp*:
down-cont F ==>
 F (INTER UNIV (*down-iterate* F)) = INTER UNIV (*down-iterate* F)
apply (frule *down-cont-mono* [THEN *down-iterate-chain*])
apply (drule (1) *down-contD*)
apply simp
apply (auto simp del: *down-iterate-Suc* simp add: *down-iterate-Suc* [symmetric])
apply (case-tac xa)
apply auto
done

lemma *INTER-down-iterate-upperbound*:
mono F ==> F P = P ==> P ⊆ INTER UNIV (*down-iterate* F)
apply (subgoal-tac (!i. P ⊆ *down-iterate* F i))
apply fast
apply (induct-tac i)
prefer 2 **apply** (drule (1) *monoD*)
apply auto
done

lemma *INTER-down-iterate-is-gfp*:
down-cont F ==> *gfp* F = INTER UNIV (*down-iterate* F)
apply (rule *set-eq-subset* [THEN *iffD2*])
apply (rule *conjI*)
apply (drule *down-cont-mono*)
apply (rule *INTER-down-iterate-upperbound*)
apply assumption
apply (erule *gfp-unfold* [symmetric])
apply (rule *gfp-upperbound*)
apply (rule *set-eq-subset* [THEN *iffD1*, THEN *conjunct2*])

```

    apply (erule INTER-down-iterate-is-fp)
  done

end

```

5 EfficientNat: Implementation of natural numbers by integers

```

theory EfficientNat
imports Main
begin

```

When generating code for functions on natural numbers, the canonical representation using 0 and Suc is unsuitable for computations involving large numbers. The efficiency of the generated code can be improved drastically by implementing natural numbers by integers. To do this, just include this theory.

5.1 Basic functions

The implementation of 0 and Suc using the ML integers is straightforward. Since natural numbers are implemented using integers, the coercion function int of type $nat \Rightarrow int$ is simply implemented by the identity function. For the nat function for converting an integer to a natural number, we give a specific implementation using an ML function that returns its input value, provided that it is non-negative, and otherwise returns 0 .

```

types-code
  nat (int)
attach (term-of) ⟨
  fun term-of-nat 0 = Const (0, HOLogic.natT)
    | term-of-nat 1 = Const (1, HOLogic.natT)
    | term-of-nat i = HOLogic.number-of-const HOLogic.natT $
      HOLogic.mk-bin (IntInf.fromInt i);
  ⟩
attach (test) ⟨
  fun gen-nat i = random-range 0 i;
  ⟩

consts-code
  0 :: nat (0)
  Suc ((- + 1))
  nat ((module)nat)
attach ⟨
  fun nat i = if i < 0 then 0 else i;
  ⟩

```

int ((-))

Case analysis on natural numbers is rephrased using a conditional expression:

```
lemma [code unfold]: nat-case  $\equiv (\lambda f g n. \text{if } n = 0 \text{ then } f \text{ else } g (n - 1))$ 
  apply (rule eq-reflection ext)+
  apply (case-tac n)
  apply simp-all
done
```

Most standard arithmetic functions on natural numbers are implemented using their counterparts on the integers:

```
lemma [code]:  $m - n = \text{nat } (\text{int } m - \text{int } n)$  by arith
lemma [code]:  $m + n = \text{nat } (\text{int } m + \text{int } n)$  by arith
lemma [code]:  $m * n = \text{nat } (\text{int } m * \text{int } n)$ 
  by (simp add: zmult-int)
lemma [code]:  $m \text{ div } n = \text{nat } (\text{int } m \text{ div } \text{int } n)$ 
  by (simp add: zdiv-int [symmetric])
lemma [code]:  $m \bmod n = \text{nat } (\text{int } m \bmod \text{int } n)$ 
  by (simp add: zmod-int [symmetric])
lemma [code]:  $(m < n) = (\text{int } m < \text{int } n)$ 
  by simp
```

5.2 Preprocessors

In contrast to $\text{Suc } n$, the term $n + 1$ is no longer a constructor term. Therefore, all occurrences of this term in a position where a pattern is expected (i.e. on the left-hand side of a recursion equation or in the arguments of an inductive relation in an introduction rule) must be eliminated. This can be accomplished by applying the following transformation rules:

```
theorem Suc-if-eq:  $(\bigwedge n. f (\text{Suc } n) = h n) \implies f 0 = g \implies$ 
   $f n = (\text{if } n = 0 \text{ then } g \text{ else } h (n - 1))$ 
  by (case-tac n) simp-all
```

```
theorem Suc-clause:  $(\bigwedge n. P n (\text{Suc } n)) \implies n \neq 0 \implies P (n - 1) n$ 
  by (case-tac n) simp-all
```

The rules above are built into a preprocessor that is plugged into the code generator. Since the preprocessor for introduction rules does not know anything about modes, some of the modes that worked for the canonical representation of natural numbers may no longer work.

end

6 ExecutableSet: Implementation of finite sets by lists

```

theory ExecutableSet
imports Main
begin

lemma [code target: Set]:  $(A = B) = (A \subseteq B \wedge B \subseteq A)$ 
  by blast

declare bex-triv-one-point1 [symmetric, standard, code]

types-code
  set (- list)
attach (term-of) ⟨⟨
  fun term-of-set f T [] = Const ({}, Type (set, [T]))
    | term-of-set f T (x :: xs) = Const (insert,
      T --> Type (set, [T]) --> Type (set, [T])) $ f x $ term-of-set f T xs;
  ⟩⟩
attach (test) ⟨⟨
  fun gen-set' aG i j = frequency
    [(i, fn () => aG j :: gen-set' aG (i-1) j), (1, fn () => [])] ()
  and gen-set aG i = gen-set' aG i i;
  ⟩⟩

consts-code
  {}      ([])
  insert  ((- ins -))
  op Un   ((- union -))
  op Int  ((- inter -))
  op - :: 'a set => 'a set => 'a set ((- \\ -))
  image   ((module)image)
attach ⟨⟨
  fun image f S = distinct (map f S);
  ⟩⟩
  UNION  ((module)UNION)
attach ⟨⟨
  fun UNION S f = Library.foldr Library.union (map f S, []);
  ⟩⟩
  INTER  ((module)INTER)
attach ⟨⟨
  fun INTER S f = Library.foldr1 Library.inter (map f S);
  ⟩⟩
  Bex    ((module)Bex)
attach ⟨⟨
  fun Bex S P = Library.exists P S;
  ⟩⟩
  Ball   ((module)Ball)
attach ⟨⟨

```

```
fun Ball S P = Library.forall P S;
>>
```

```
end
```

7 FuncSet: Pi and Function Sets

```
theory FuncSet
imports Main
begin
```

```
constdefs
```

```
  Pi :: ['a set, 'a => 'b set] => ('a => 'b) set
  Pi A B == {f. ∀ x. x ∈ A --> f x ∈ B x}
```

```
  extensional :: 'a set => ('a => 'b) set
  extensional A == {f. ∀ x. x~:A --> f x = arbitrary}
```

```
  restrict :: ['a => 'b, 'a set] => ('a => 'b)
  restrict f A == (%x. if x ∈ A then f x else arbitrary)
```

```
syntax
```

```
  @Pi :: [pttrn, 'a set, 'b set] => ('a => 'b) set ((3PI :-./ -) 10)
  funcset :: ['a set, 'b set] => ('a => 'b) set (infixr -> 60)
  @lam :: [pttrn, 'a set, 'a => 'b] => ('a=>'b) ((3%-./ -) [0,0,3] 3)
```

```
syntax (xsymbols)
```

```
  @Pi :: [pttrn, 'a set, 'b set] => ('a => 'b) set ((3Π -∈./ -) 10)
  funcset :: ['a set, 'b set] => ('a => 'b) set (infixr → 60)
  @lam :: [pttrn, 'a set, 'a => 'b] => ('a=>'b) ((3λ-∈./ -) [0,0,3] 3)
```

```
syntax (HTML output)
```

```
  @Pi :: [pttrn, 'a set, 'b set] => ('a => 'b) set ((3Π -∈./ -) 10)
  @lam :: [pttrn, 'a set, 'a => 'b] => ('a=>'b) ((3λ-∈./ -) [0,0,3] 3)
```

```
translations
```

```
  PI x:A. B => Pi A (%x. B)
  A -> B => Pi A (-K B)
  %x:A. f == restrict (%x. f) A
```

```
constdefs
```

```
  compose :: ['a set, 'b => 'c, 'a => 'b] => ('a => 'c)
  compose A g f == λx∈A. g (f x)
```

```
print-translation << [(Pi, dependent-tr' (@Pi, funcset))] >>
```

7.1 Basic Properties of Pi

lemma *Pi-I*: $(!!x. x \in A \implies f x \in B x) \implies f \in Pi\ A\ B$
by (*simp add: Pi-def*)

lemma *funcsetI*: $(!!x. x \in A \implies f x \in B) \implies f \in A \multimap B$
by (*simp add: Pi-def*)

lemma *Pi-mem*: $[|f: Pi\ A\ B; x \in A|] \implies f x \in B\ x$
by (*simp add: Pi-def*)

lemma *funcset-mem*: $[|f \in A \multimap B; x \in A|] \implies f x \in B$
by (*simp add: Pi-def*)

lemma *funcset-image*: $f \in A \multimap B \implies f\ ` A \subseteq B$
by (*auto simp add: Pi-def*)

lemma *Pi-eq-empty*: $((PI\ x. A.\ B\ x) = \{\}) = (\exists x \in A. B(x) = \{\})$
apply (*simp add: Pi-def, auto*)

Converse direction requires Axiom of Choice to exhibit a function picking an element from each non-empty $B\ x$

apply (*drule-tac x = %u. SOME y. y \in B u in spec, auto*)
apply (*cut-tac P = %y. y \in B x in some-eq-ex, auto*)
done

lemma *Pi-empty* [*simp*]: $Pi\ \{\}\ B = UNIV$
by (*simp add: Pi-def*)

lemma *Pi-UNIV* [*simp*]: $A \multimap UNIV = UNIV$
by (*simp add: Pi-def*)

Covariance of Pi -sets in their second argument

lemma *Pi-mono*: $(!!x. x \in A \implies B\ x \leq C\ x) \implies Pi\ A\ B \leq Pi\ A\ C$
by (*simp add: Pi-def, blast*)

Contravariance of Pi -sets in their first argument

lemma *Pi-anti-mono*: $A' \leq A \implies Pi\ A\ B \leq Pi\ A'\ B$
by (*simp add: Pi-def, blast*)

7.2 Composition With a Restricted Domain: *compose*

lemma *funcset-compose*:
 $[|f \in A \multimap B; g \in B \multimap C|] \implies compose\ A\ g\ f \in A \multimap C$
by (*simp add: Pi-def compose-def restrict-def*)

lemma *compose-assoc*:
 $[|f \in A \multimap B; g \in B \multimap C; h \in C \multimap D|]$
 $\implies compose\ A\ h\ (compose\ A\ g\ f) = compose\ A\ (compose\ B\ h\ g)\ f$

by (*simp add: expand-fun-eq Pi-def compose-def restrict-def*)

lemma *compose-eq*: $x \in A \implies \text{compose } A \ g \ f \ x = g(f(x))$
by (*simp add: compose-def restrict-def*)

lemma *surj-compose*: $[[f \text{ ‘ } A = B; g \text{ ‘ } B = C]] \implies \text{compose } A \ g \ f \text{ ‘ } A = C$
by (*auto simp add: image-def compose-eq*)

7.3 Bounded Abstraction: *restrict*

lemma *restrict-in-funcset*: $(!!x. x \in A \implies f \ x \in B) \implies (\lambda x \in A. f \ x) \in A \multimap B$
by (*simp add: Pi-def restrict-def*)

lemma *restrictI*: $(!!x. x \in A \implies f \ x \in B \ x) \implies (\lambda x \in A. f \ x) \in \text{Pi } A \ B$
by (*simp add: Pi-def restrict-def*)

lemma *restrict-apply* [*simp*]:
 $(\lambda y \in A. f \ y) \ x = (\text{if } x \in A \text{ then } f \ x \text{ else arbitrary})$
by (*simp add: restrict-def*)

lemma *restrict-ext*:
 $(!!x. x \in A \implies f \ x = g \ x) \implies (\lambda x \in A. f \ x) = (\lambda x \in A. g \ x)$
by (*simp add: expand-fun-eq Pi-def Pi-def restrict-def*)

lemma *inj-on-restrict-eq* [*simp*]: $\text{inj-on } (\text{restrict } f \ A) \ A = \text{inj-on } f \ A$
by (*simp add: inj-on-def restrict-def*)

lemma *Id-compose*:
 $[[f \in A \multimap B; f \in \text{extensional } A]] \implies \text{compose } A \ (\lambda y \in B. y) \ f = f$
by (*auto simp add: expand-fun-eq compose-def extensional-def Pi-def*)

lemma *compose-Id*:
 $[[g \in A \multimap B; g \in \text{extensional } A]] \implies \text{compose } A \ g \ (\lambda x \in A. x) = g$
by (*auto simp add: expand-fun-eq compose-def extensional-def Pi-def*)

lemma *image-restrict-eq* [*simp*]: $(\text{restrict } f \ A) \text{ ‘ } A = f \text{ ‘ } A$
by (*auto simp add: restrict-def*)

7.4 Bijections Between Sets

The basic definition could be moved to *Fun.thy*, but most of the theorems belong here, or need at least *Hilbert-Choice*.

constdefs
 $\text{bij-betw} :: [\text{'a} \implies \text{'b}, \text{'a set}, \text{'b set}] \implies \text{bool}$
 $\text{bij-betw } f \ A \ B == \text{inj-on } f \ A \ \& \ f \text{ ‘ } A = B$

lemma *bij-betw-imp-inj-on*: $\text{bij-betw } f \ A \ B \implies \text{inj-on } f \ A$
by (*simp add: bij-betw-def*)

lemma *bij-betw-imp-funcset*: $\text{bij-betw } f \ A \ B \implies f \in A \rightarrow B$
by (*auto simp add: bij-betw-def inj-on-Inv Pi-def*)

lemma *bij-betw-Inv*: $\text{bij-betw } f \ A \ B \implies \text{bij-betw } (\text{Inv } A \ f) \ B \ A$
apply (*auto simp add: bij-betw-def inj-on-Inv Inv-mem*)
apply (*simp add: image-compose [symmetric] o-def*)
apply (*simp add: image-def Inv-f-f*)
done

lemma *inj-on-compose*:
 $\llbracket \text{bij-betw } f \ A \ B; \text{inj-on } g \ B \rrbracket \implies \text{inj-on } (\text{compose } A \ g \ f) \ A$
by (*auto simp add: bij-betw-def inj-on-def compose-eq*)

lemma *bij-betw-compose*:
 $\llbracket \text{bij-betw } f \ A \ B; \text{bij-betw } g \ B \ C \rrbracket \implies \text{bij-betw } (\text{compose } A \ g \ f) \ A \ C$
apply (*simp add: bij-betw-def compose-eq inj-on-compose*)
apply (*auto simp add: compose-def image-def*)
done

lemma *bij-betw-restrict-eq [simp]*:
 $\text{bij-betw } (\text{restrict } f \ A) \ A \ B = \text{bij-betw } f \ A \ B$
by (*simp add: bij-betw-def*)

7.5 Extensionality

lemma *extensional-arb*: $\llbracket f \in \text{extensional } A; x \notin A \rrbracket \implies f \ x = \text{arbitrary}$
by (*simp add: extensional-def*)

lemma *restrict-extensional [simp]*: $\text{restrict } f \ A \in \text{extensional } A$
by (*simp add: restrict-def extensional-def*)

lemma *compose-extensional [simp]*: $\text{compose } A \ f \ g \in \text{extensional } A$
by (*simp add: compose-def*)

lemma *extensionalityI*:
 $\llbracket f \in \text{extensional } A; g \in \text{extensional } A; \\ !!x. x \in A \implies f \ x = g \ x \rrbracket \implies f = g$
by (*force simp add: expand-fun-eq extensional-def*)

lemma *Inv-funcset*: $f \in A = B \implies (\lambda x \in B. \text{Inv } A \ f \ x) : B \rightarrow A$
by (*unfold Inv-def*) (*fast intro: restrict-in-funcset someI2*)

lemma *compose-Inv-id*:
 $\text{bij-betw } f \ A \ B \implies \text{compose } A \ (\lambda y \in B. \text{Inv } A \ f \ y) \ f = (\lambda x \in A. x)$
apply (*simp add: bij-betw-def compose-def*)
apply (*rule restrict-ext, auto*)
apply (*erule subst*)
apply (*simp add: Inv-f-f*)

done

lemma *compose-id-Inv*:

$f \circ A = B \implies \text{compose } B \circ f \ (\lambda y \in B. \text{Inv } A \circ f \ y) = (\lambda x \in B. x)$

apply (*simp add: compose-def*)

apply (*rule restrict-ext*)

apply (*simp add: f-Inv-f*)

done

7.6 Cardinality

lemma *card-inj*: $[[f \in A \rightarrow B; \text{inj-on } f \ A; \text{finite } B]] \implies \text{card}(A) \leq \text{card}(B)$

apply (*rule card-inj-on-le*)

apply (*auto simp add: Pi-def*)

done

lemma *card-bij*:

$[[f \in A \rightarrow B; \text{inj-on } f \ A;$

$g \in B \rightarrow A; \text{inj-on } g \ B; \text{finite } A; \text{finite } B]] \implies \text{card}(A) = \text{card}(B)$

by (*blast intro: card-inj order-antisym*)

end

8 Multiset: Multisets

theory *Multiset*

imports *Accessible-Part*

begin

8.1 The type of multisets

typedef *'a multiset* = $\{f :: 'a \Rightarrow \text{nat}. \text{finite } \{x. 0 < f \ x\}\}$

proof

show $(\lambda x. 0 :: \text{nat}) \in ?\text{multiset}$ **by** *simp*

qed

lemmas *multiset-typedef* [*simp*] =

Abs-multiset-inverse Rep-multiset-inverse Rep-multiset

and [*simp*] = *Rep-multiset-inject* [*symmetric*]

constdefs

Empty :: *'a multiset* $(\{\#\})$

$\{\#\} == \text{Abs-multiset } (\lambda a. 0)$

single :: *'a* \Rightarrow *'a multiset* $(\{\#- \#\})$

$\{\#a\# \} == \text{Abs-multiset } (\lambda b. \text{if } b = a \text{ then } 1 \text{ else } 0)$

count :: *'a multiset* \Rightarrow *'a* \Rightarrow *nat*

count == *Rep-multiset*

MCollect :: 'a multiset => ('a => bool) => 'a multiset

MCollect *M P* == *Abs-multiset* ($\lambda x. \text{if } P \ x \text{ then } \text{Rep-multiset } M \ x \text{ else } 0$)

syntax

-*Melem* :: 'a => 'a multiset => bool ((-/ :# -) [50, 51] 50)

-*MCollect* :: *pttrn* => 'a multiset => bool => 'a multiset ((1{# - : -/ -#}))

translations

a :# *M* == 0 < *count M a*

{#*x*:*M*. *P*#} == *MCollect M* ($\lambda x. P$)

constdefs

set-of :: 'a multiset => 'a set

set-of M == {*x*. *x* :# *M*}

instance *multiset* :: (type) {plus, minus, zero} ..

defs (overloaded)

union-def: *M* + *N* == *Abs-multiset* ($\lambda a. \text{Rep-multiset } M \ a + \text{Rep-multiset } N \ a$)

diff-def: *M* - *N* == *Abs-multiset* ($\lambda a. \text{Rep-multiset } M \ a - \text{Rep-multiset } N \ a$)

Zero-multiset-def [*simp*]: 0 == {#}

size-def: *size M* == *setsum* (*count M*) (*set-of M*)

constdefs

multiset-inter :: 'a multiset \Rightarrow 'a multiset \Rightarrow 'a multiset (**infixl** # \cap 70)

multiset-inter A B $\equiv A - (A - B)$

Preservation of the representing set *multiset*.

lemma *const0-in-multiset* [*simp*]: ($\lambda a. 0$) \in *multiset*

by (*simp add: multiset-def*)

lemma *only1-in-multiset* [*simp*]: ($\lambda b. \text{if } b = a \text{ then } 1 \text{ else } 0$) \in *multiset*

by (*simp add: multiset-def*)

lemma *union-preserves-multiset* [*simp*]:

M \in *multiset* \implies *N* \in *multiset* \implies ($\lambda a. M \ a + N \ a$) \in *multiset*

apply (*simp add: multiset-def*)

apply (*drule* (1) *finite-UnI*)

apply (*simp del: finite-Un add: Un-def*)

done

lemma *diff-preserves-multiset* [*simp*]:

M \in *multiset* \implies ($\lambda a. M \ a - N \ a$) \in *multiset*

apply (*simp add: multiset-def*)

apply (*rule finite-subset*)

apply *auto*

done

8.2 Algebraic properties of multisets

8.2.1 Union

lemma *union-empty* [simp]: $M + \{\#\} = M \wedge \{\#\} + M = M$
 by (simp add: union-def Mempty-def)

lemma *union-commute*: $M + N = N + (M::'a \text{ multiset})$
 by (simp add: union-def add-ac)

lemma *union-assoc*: $(M + N) + K = M + (N + (K::'a \text{ multiset}))$
 by (simp add: union-def add-ac)

lemma *union-lcomm*: $M + (N + K) = N + (M + (K::'a \text{ multiset}))$

proof –

have $M + (N + K) = (N + K) + M$

by (rule union-commute)

also have $\dots = N + (K + M)$

by (rule union-assoc)

also have $K + M = M + K$

by (rule union-commute)

finally show ?thesis .

qed

lemmas *union-ac* = *union-assoc union-commute union-lcomm*

instance *multiset* :: (type) *comm-monoid-add*

proof

fix $a \ b \ c :: 'a \text{ multiset}$

show $(a + b) + c = a + (b + c)$ by (rule union-assoc)

show $a + b = b + a$ by (rule union-commute)

show $0 + a = a$ by simp

qed

8.2.2 Difference

lemma *diff-empty* [simp]: $M - \{\#\} = M \wedge \{\#\} - M = \{\#\}$
 by (simp add: Mempty-def diff-def)

lemma *diff-union-inverse2* [simp]: $M + \{\#a\# \} - \{\#a\# \} = M$
 by (simp add: union-def diff-def)

8.2.3 Count of elements

lemma *count-empty* [simp]: $\text{count } \{\#\} \ a = 0$
 by (simp add: count-def Mempty-def)

lemma *count-single* [simp]: $\text{count } \{\#b\# \} \ a = (\text{if } b = a \text{ then } 1 \text{ else } 0)$
 by (simp add: count-def single-def)

lemma *count-union* [simp]: $\text{count } (M + N) \ a = \text{count } M \ a + \text{count } N \ a$
 by (simp add: count-def union-def)

lemma *count-diff* [simp]: $\text{count } (M - N) \ a = \text{count } M \ a - \text{count } N \ a$
 by (simp add: count-def diff-def)

8.2.4 Set of elements

lemma *set-of-empty* [simp]: $\text{set-of } \{\#\} = \{\}$
 by (simp add: set-of-def)

lemma *set-of-single* [simp]: $\text{set-of } \{\#b\# \} = \{b\}$
 by (simp add: set-of-def)

lemma *set-of-union* [simp]: $\text{set-of } (M + N) = \text{set-of } M \cup \text{set-of } N$
 by (auto simp add: set-of-def)

lemma *set-of-eq-empty-iff* [simp]: $(\text{set-of } M = \{\}) = (M = \{\#\})$
 by (auto simp add: set-of-def Mempty-def count-def expand-fun-eq)

lemma *mem-set-of-iff* [simp]: $(x \in \text{set-of } M) = (x : \# \ M)$
 by (auto simp add: set-of-def)

8.2.5 Size

lemma *size-empty* [simp]: $\text{size } \{\#\} = 0$
 by (simp add: size-def)

lemma *size-single* [simp]: $\text{size } \{\#b\# \} = 1$
 by (simp add: size-def)

lemma *finite-set-of* [iff]: $\text{finite } (\text{set-of } M)$
 using *Rep-multiset* [of M]
 by (simp add: multiset-def set-of-def count-def)

lemma *setsum-count-Int*:
 $\text{finite } A \implies \text{setsum } (\text{count } N) \ (A \cap \text{set-of } N) = \text{setsum } (\text{count } N) \ A$
 apply (erule finite-induct)
 apply simp
 apply (simp add: Int-insert-left set-of-def)
 done

lemma *size-union* [simp]: $\text{size } (M + N :: 'a \text{ multiset}) = \text{size } M + \text{size } N$
 apply (unfold size-def)
 apply (subgoal-tac $\text{count } (M + N) = (\lambda a. \text{count } M \ a + \text{count } N \ a)$)
 prefer 2
 apply (rule ext, simp)
 apply (simp (no-asm-simp) add: setsum-Un-nat setsum-addf setsum-count-Int)
 apply (subst Int-commute)
 apply (simp (no-asm-simp) add: setsum-count-Int)

done

lemma *size-eq-0-iff-empty* [iff]: $(\text{size } M = 0) = (M = \{\#\})$
apply (*unfold size-def Mempty-def count-def, auto*)
apply (*simp add: set-of-def count-def expand-fun-eq*)
done

lemma *size-eq-Suc-imp-elem*: $\text{size } M = \text{Suc } n \implies \exists a. a : \# M$
apply (*unfold size-def*)
apply (*drule setsum-SucD, auto*)
done

8.2.6 Equality of multisets

lemma *multiset-eq-conv-count-eq*: $(M = N) = (\forall a. \text{count } M a = \text{count } N a)$
by (*simp add: count-def expand-fun-eq*)

lemma *single-not-empty* [simp]: $\{\#a\# \} \neq \{\#\} \wedge \{\#\} \neq \{\#a\# \}$
by (*simp add: single-def Mempty-def expand-fun-eq*)

lemma *single-eq-single* [simp]: $(\{\#a\# \} = \{\#b\# \}) = (a = b)$
by (*auto simp add: single-def expand-fun-eq*)

lemma *union-eq-empty* [iff]: $(M + N = \{\#\}) = (M = \{\#\} \wedge N = \{\#\})$
by (*auto simp add: union-def Mempty-def expand-fun-eq*)

lemma *empty-eq-union* [iff]: $(\{\#\} = M + N) = (M = \{\#\} \wedge N = \{\#\})$
by (*auto simp add: union-def Mempty-def expand-fun-eq*)

lemma *union-right-cancel* [simp]: $(M + K = N + K) = (M = (N :: 'a \text{ multiset}))$
by (*simp add: union-def expand-fun-eq*)

lemma *union-left-cancel* [simp]: $(K + M = K + N) = (M = (N :: 'a \text{ multiset}))$
by (*simp add: union-def expand-fun-eq*)

lemma *union-is-single*:
 $(M + N = \{\#a\# \}) = (M = \{\#a\# \} \wedge N = \{\#\} \vee M = \{\#\} \wedge N = \{\#a\# \})$
apply (*simp add: Mempty-def single-def union-def add-is-1 expand-fun-eq*)
apply *blast*
done

lemma *single-is-union*:
 $(\{\#a\# \} = M + N) = (\{\#a\# \} = M \wedge N = \{\#\} \vee M = \{\#\} \wedge \{\#a\# \} = N)$
apply (*unfold Mempty-def single-def union-def*)
apply (*simp add: add-is-1 one-is-add expand-fun-eq*)
apply (*blast dest: sym*)
done

```

lemma add-eq-conv-diff:
  (M + {#a#} = N + {#b#}) =
    (M = N ∧ a = b ∨ M = N - {#a#} + {#b#} ∧ N = M - {#b#} +
    {#a#})
  apply (unfold single-def union-def diff-def)
  apply (simp (no-asm) add: expand-fun-eq)
  apply (rule conjI, force, safe, simp-all)
  apply (simp add: eq-sym-conv)
  done

declare Rep-multiset-inject [symmetric, simp del]

```

8.2.7 Intersection

```

lemma multiset-inter-count:
  count (A #∩ B) x = min (count A x) (count B x)
  by (simp add: multiset-inter-def min-def)

lemma multiset-inter-commute: A #∩ B = B #∩ A
  by (simp add: multiset-eq-conv-count-eq multiset-inter-count
    min-max.below-inf.inf-commute)

lemma multiset-inter-assoc: A #∩ (B #∩ C) = A #∩ B #∩ C
  by (simp add: multiset-eq-conv-count-eq multiset-inter-count
    min-max.below-inf.inf-assoc)

lemma multiset-inter-left-commute: A #∩ (B #∩ C) = B #∩ (A #∩ C)
  by (simp add: multiset-eq-conv-count-eq multiset-inter-count min-def)

lemmas multiset-inter-ac =
  multiset-inter-commute
  multiset-inter-assoc
  multiset-inter-left-commute

lemma multiset-union-diff-commute: B #∩ C = {#} ⇒ A + B - C = A - C
+ B
  apply (simp add: multiset-eq-conv-count-eq multiset-inter-count min-def
    split: split-if-asm)
  apply clarsimp
  apply (erule tac x = a in allE)
  apply auto
  done

```

8.3 Induction over multisets

```

lemma setsum-decr:
  finite F ==> (0::nat) < f a ==>
    setsum (f (a := f a - 1)) F = (if a∈F then setsum f F - 1 else setsum f F)
  apply (erule finite-induct, auto)
  apply (drule-tac a = a in mk-disjoint-insert, auto)

```

done

lemma *rep-multiset-induct-aux*:

assumes $P (\lambda a. (0 :: nat))$

and $!!f b. f \in \text{multiset} \implies P f \implies P (f (b := f b + 1))$

shows $\forall f. f \in \text{multiset} \longrightarrow \text{setsum } f \{x. 0 < f x\} = n \longrightarrow P f$

proof –

note *premises* = *prems* [unfolded multiset-def]

show *?thesis*

apply (*unfold multiset-def*)

apply (*induct-tac n, simp, clarify*)

apply (*subgoal-tac f = ($\lambda a. 0$)*)

apply *simp*

apply (*rule premises*)

apply (*rule ext, force, clarify*)

apply (*erule setsum-SucD, clarify*)

apply (*rename-tac a*)

apply (*subgoal-tac finite* $\{x. 0 < (f (a := f a - 1)) x\}$)

prefer 2

apply (*rule finite-subset*)

prefer 2

apply *assumption*

apply *simp*

apply *blast*

apply (*subgoal-tac f = (f (a := f a - 1))(a := (f (a := f a - 1)) a + 1)*)

prefer 2

apply (*rule ext*)

apply (*simp (no-asm-simp)*)

apply (*erule ssubst, rule premises, blast*)

apply (*erule allE, erule impE, erule-tac [2] mp, blast*)

apply (*simp (no-asm-simp) add: setsum-decr del: fun-upd-apply One-nat-def*)

apply (*subgoal-tac* $\{x. x \neq a \longrightarrow 0 < f x\} = \{x. 0 < f x\}$)

prefer 2

apply *blast*

apply (*subgoal-tac* $\{x. x \neq a \wedge 0 < f x\} = \{x. 0 < f x\} - \{a\}$)

prefer 2

apply *blast*

apply (*simp add: le-imp-diff-is-add setsum-diff1-nat cong: conj-cong*)

done

qed

theorem *rep-multiset-induct*:

$f \in \text{multiset} \implies P (\lambda a. 0) \implies$

$(!!f b. f \in \text{multiset} \implies P f \implies P (f (b := f b + 1))) \implies P f$

using *rep-multiset-induct-aux* **by** *blast*

theorem *multiset-induct* [*induct type: multiset*]:

assumes *prem1*: $P \{\#\}$

and *prem2*: $!!M x. P M \implies P (M + \{\#x\#\})$


```

shows P M
proof -
  note defns = union-def single-def Mempty-def
  show ?thesis
    apply (rule Rep-multiset-inverse [THEN subst])
    apply (rule Rep-multiset [THEN rep-multiset-induct])
    apply (rule prem1 [unfolded defns])
    apply (subgoal-tac f(b := f b + 1) = (λa. f a + (if a=b then 1 else 0)))
    prefer 2
    apply (simp add: expand-fun-eq)
    apply (erule ssubst)
    apply (erule Abs-multiset-inverse [THEN subst])
    apply (erule prem2 [unfolded defns, simplified])
  done
qed

```

```

lemma MCollect-preserves-multiset:
  M ∈ multiset ==> (λx. if P x then M x else 0) ∈ multiset
  apply (simp add: multiset-def)
  apply (rule finite-subset, auto)
  done

```

```

lemma count-MCollect [simp]:
  count {# x:M. P x #} a = (if P a then count M a else 0)
  by (simp add: count-def MCollect-def MCollect-preserves-multiset)

```

```

lemma set-of-MCollect [simp]: set-of {# x:M. P x #} = set-of M ∩ {x. P x}
  by (auto simp add: set-of-def)

```

```

lemma multiset-partition: M = {# x:M. P x #} + {# x:M. ¬ P x #}
  by (subst multiset-eq-conv-count-eq, auto)

```

```

lemma add-eq-conv-ex:
  (M + {#a#} = N + {#b#}) =
  (M = N ∧ a = b ∨ (∃ K. M = K + {#b#} ∧ N = K + {#a#}))
  by (auto simp add: add-eq-conv-diff)

```

```

declare multiset-tyedef [simp del]

```

8.4 Multiset orderings

8.4.1 Well-foundedness

```

constdefs
  mult1 :: ('a × 'a) set => ('a multiset × 'a multiset) set
  mult1 r ==
    {(N, M). ∃ a M0 K. M = M0 + {#a#} ∧ N = M0 + K ∧
     (∀ b. b :# K --> (b, a) ∈ r)}

  mult :: ('a × 'a) set => ('a multiset × 'a multiset) set

```

$mult\ r == (mult1\ r)^+$

lemma *not-less-empty* [iff]: $(M, \{\#\}) \notin mult1\ r$
by (*simp add: mult1-def*)

lemma *less-add*: $(N, M0 + \{\#a\# \}) \in mult1\ r ==>$
 $(\exists M. (M, M0) \in mult1\ r \wedge N = M + \{\#a\# \}) \vee$
 $(\exists K. (\forall b. b : \# K \longrightarrow (b, a) \in r) \wedge N = M0 + K)$
(concl is *?case1* (*mult1 r*) **\vee** *?case2*)

proof (*unfold mult1-def*)

let *?r* = $\lambda K\ a. \forall b. b : \# K \longrightarrow (b, a) \in r$

let *?R* = $\lambda N\ M. \exists a\ M0\ K. M = M0 + \{\#a\# \} \wedge N = M0 + K \wedge ?r\ K\ a$

let *?case1* = *?case1* $\{(N, M). ?R\ N\ M\}$

assume $(N, M0 + \{\#a\# \}) \in \{(N, M). ?R\ N\ M\}$

hence $\exists a'\ M0'\ K.$

$M0 + \{\#a\# \} = M0' + \{\#a'\# \} \wedge N = M0' + K \wedge ?r\ K\ a'$ **by** *simp*

thus *?case1* \vee *?case2*

proof (*elim exE conjE*)

fix *a' M0' K*

assume *N*: $N = M0' + K$ **and** *r*: *?r K a'*

assume $M0 + \{\#a\# \} = M0' + \{\#a'\# \}$

hence $M0 = M0' \wedge a = a' \vee$

$(\exists K'. M0 = K' + \{\#a'\# \} \wedge M0' = K' + \{\#a\# \})$

by (*simp only: add-eq-conv-ex*)

thus *?thesis*

proof (*elim disjE conjE exE*)

assume $M0 = M0'\ a = a'$

with *N r* **have** *?r K a* $\wedge N = M0 + K$ **by** *simp*

hence *?case2* **.. thus** *?thesis* **..**

next

fix *K'*

assume $M0' = K' + \{\#a\# \}$

with *N* **have** *n*: $N = K' + K + \{\#a\# \}$ **by** (*simp add: union-ac*)

assume $M0 = K' + \{\#a'\# \}$

with *r* **have** *?R* $(K' + K)\ M0$ **by** *blast*

with *n* **have** *?case1* **by** *simp* **thus** *?thesis* **..**

qed

qed

qed

lemma *all-accessible*: $wf\ r ==> \forall M. M \in acc\ (mult1\ r)$

proof

let *?R* = *mult1 r*

let *?W* = *acc ?R*

{

fix *M M0 a*

assume *M0*: $M0 \in ?W$

```

    and wf-hyp: !!b. (b, a) ∈ r ==> (∀ M ∈ ?W. M + {#b#} ∈ ?W)
    and acc-hyp: ∀ M. (M, M0) ∈ ?R --> M + {#a#} ∈ ?W
  have M0 + {#a#} ∈ ?W
  proof (rule accI [of M0 + {#a#}])
    fix N
    assume (N, M0 + {#a#}) ∈ ?R
    hence ((∃ M. (M, M0) ∈ ?R ∧ N = M + {#a#}) ∨
      (∃ K. (∀ b. b :# K --> (b, a) ∈ r) ∧ N = M0 + K))
      by (rule less-add)
    thus N ∈ ?W
  proof (elim exE disjE conjE)
    fix M assume (M, M0) ∈ ?R and N: N = M + {#a#}
    from acc-hyp have (M, M0) ∈ ?R --> M + {#a#} ∈ ?W ..
    hence M + {#a#} ∈ ?W ..
    thus N ∈ ?W by (simp only: N)
  next
    fix K
    assume N: N = M0 + K
    assume ∀ b. b :# K --> (b, a) ∈ r
    have ?this --> M0 + K ∈ ?W (is ?P K)
    proof (induct K)
      from M0 have M0 + {#} ∈ ?W by simp
      thus ?P {#} ..

      fix K x assume hyp: ?P K
      show ?P (K + {#x#})
      proof
        assume a: ∀ b. b :# (K + {#x#}) --> (b, a) ∈ r
        hence (x, a) ∈ r by simp
        with wf-hyp have b: ∀ M ∈ ?W. M + {#x#} ∈ ?W by blast

        from a hyp have M0 + K ∈ ?W by simp
        with b have (M0 + K) + {#x#} ∈ ?W ..
        thus M0 + (K + {#x#}) ∈ ?W by (simp only: union-assoc)
      qed
    qed
    hence M0 + K ∈ ?W ..
    thus N ∈ ?W by (simp only: N)
  qed
} note tedious-reasoning = this

assume wf: wf r
fix M
show M ∈ ?W
proof (induct M)
  show {#} ∈ ?W
  proof (rule accI)
    fix b assume (b, {#}) ∈ ?R

```

```

  with not-less-empty show  $b \in ?W$  by contradiction
qed

fix M a assume  $M \in ?W$ 
from wf have  $\forall M \in ?W. M + \{\#a\# \} \in ?W$ 
proof induct
  fix a
  assume !!b.  $(b, a) \in r \implies (\forall M \in ?W. M + \{\#b\# \} \in ?W)$ 
  show  $\forall M \in ?W. M + \{\#a\# \} \in ?W$ 
  proof
    fix M assume  $M \in ?W$ 
    thus  $M + \{\#a\# \} \in ?W$ 
    by (rule acc-induct) (rule tedious-reasoning)
  qed
qed
thus  $M + \{\#a\# \} \in ?W$  ..
qed
qed

theorem wf-mult1:  $wf\ r \implies wf\ (mult1\ r)$ 
  by (rule acc-wfI, rule all-accessible)

theorem wf-mult:  $wf\ r \implies wf\ (mult\ r)$ 
  by (unfold mult-def, rule wf-trancl, rule wf-mult1)

```

8.4.2 Closure-free presentation

```

lemma diff-union-single-conv:  $a : \# J \implies I + J - \{\#a\# \} = I + (J - \{\#a\# \})$ 
by (simp add: multiset-eq-conv-count-eq)

```

One direction.

```

lemma mult-implies-one-step:
  trans  $r \implies (M, N) \in mult\ r \implies$ 
     $\exists I\ J\ K. N = I + J \wedge M = I + K \wedge J \neq \{\# \} \wedge$ 
     $(\forall k \in set-of\ K. \exists j \in set-of\ J. (k, j) \in r)$ 
  apply (unfold mult-def mult1-def set-of-def)
  apply (erule converse-trancl-induct, clarify)
  apply (rule-tac  $x = M0$  in  $exI$ , simp, clarify)
  apply (case-tac  $a : \# K$ )
  apply (rule-tac  $x = I$  in  $exI$ )
  apply (simp (no-asm))
  apply (rule-tac  $x = (K - \{\#a\# \}) + Ka$  in  $exI$ )
  apply (simp (no-asm-simp) add: union-assoc [symmetric])
  apply (drule-tac  $f = \lambda M. M - \{\#a\# \}$  in  $arg-cong$ )
  apply (simp add: diff-union-single-conv)
  apply (simp (no-asm-use) add: trans-def)
  apply blast
  apply (subgoal-tac  $a : \# I$ )
  apply (rule-tac  $x = I - \{\#a\# \}$  in  $exI$ )

```

```

apply (rule-tac  $x = J + \{\#a\# \}$  in  $exI$ )
apply (rule-tac  $x = K + Ka$  in  $exI$ )
apply (rule conjI)
  apply (simp add: multiset-eq-conv-count-eq split: nat-diff-split)
apply (rule conjI)
  apply (drule-tac  $f = \lambda M. M - \{\#a\# \}$  in arg-cong, simp)
  apply (simp add: multiset-eq-conv-count-eq split: nat-diff-split)
apply (simp (no-asm-use) add: trans-def)
apply blast
apply (subgoal-tac  $a : \# (M0 + \{\#a\# \})$ )
apply simp
apply (simp (no-asm))
done

```

lemma elem-imp-eq-diff-union: $a : \# M \implies M = M - \{\#a\# \} + \{\#a\# \}$
by (simp add: multiset-eq-conv-count-eq)

lemma size-eq-Suc-imp-eq-union: $\text{size } M = \text{Suc } n \implies \exists a N. M = N + \{\#a\# \}$
apply (erule size-eq-Suc-imp-elem [THEN exE])
apply (drule elem-imp-eq-diff-union, auto)
done

lemma one-step-implies-mult-aux:

```

trans  $r \implies$ 
 $\forall I J K. (\text{size } J = n \wedge J \neq \{\#\} \wedge (\forall k \in \text{set-of } K. \exists j \in \text{set-of } J. (k, j) \in r))$ 
 $\implies (I + K, I + J) \in \text{mult } r$ 
apply (induct-tac  $n$ , auto)
apply (frule size-eq-Suc-imp-eq-union, clarify)
apply (rename-tac  $J'$ , simp)
apply (erule notE, auto)
apply (case-tac  $J' = \{\#\}$ )
apply (simp add: mult-def)
apply (rule r-into-trancl)
apply (simp add: mult1-def set-of-def, blast)

```

Now we know $J' \neq \{\#\}$.

```

apply (cut-tac  $M = K$  and  $P = \lambda x. (x, a) \in r$  in multiset-partition)
apply (erule-tac  $P = \forall k \in \text{set-of } K. ?P k$  in rev-mp)
apply (erule ssubst)
apply (simp add: Ball-def, auto)
apply (subgoal-tac
  ( $(I + \{\# x : K. (x, a) \in r \#\}) + \{\# x : K. (x, a) \notin r \#\},$ 
  ( $I + \{\# x : K. (x, a) \in r \#\}) + J') \in \text{mult } r$ )
prefer 2
apply force
apply (simp (no-asm-use) add: union-assoc [symmetric] mult-def)
apply (erule trancl-trans)
apply (rule r-into-trancl)
apply (simp add: mult1-def set-of-def)

```

```

apply (rule-tac  $x = a$  in  $exI$ )
apply (rule-tac  $x = I + J'$  in  $exI$ )
apply (simp add: union-ac)
done

```

```

lemma one-step-implies-mult:
   $trans\ r \implies J \neq \{\#\} \implies \forall k \in set-of\ K. \exists j \in set-of\ J. (k, j) \in r$ 
   $\implies (I + K, I + J) \in mult\ r$ 
apply (insert one-step-implies-mult-aux, blast)
done

```

8.4.3 Partial-order properties

```

instance multiset :: (type) ord ..

```

```

defs (overloaded)
  less-multiset-def:  $M' < M \implies (M', M) \in mult\ \{(x', x). x' < x\}$ 
  le-multiset-def:  $M' \leq M \implies M' = M \vee M' < (M::'a\ multiset)$ 

```

```

lemma trans-base-order:  $trans\ \{(x', x). x' < (x::'a::order)\}$ 
apply (unfold trans-def)
apply (blast intro: order-less-trans)
done

```

Irreflexivity.

```

lemma mult-irrefl-aux:
   $finite\ A \implies (\forall x \in A. \exists y \in A. x < (y::'a::order)) \longrightarrow A = \{\}$ 
apply (erule finite-induct)
apply (auto intro: order-less-trans)
done

```

```

lemma mult-less-not-refl:  $\neg M < (M::'a::order\ multiset)$ 
apply (unfold less-multiset-def, auto)
apply (drule trans-base-order [THEN mult-implies-one-step], auto)
apply (drule finite-set-of [THEN mult-irrefl-aux [rule-format (no-asm)])]
apply (simp add: set-of-eq-empty-iff)
done

```

```

lemma mult-less-irrefl [elim!]:  $M < (M::'a::order\ multiset) \implies R$ 
by (insert mult-less-not-refl, fast)

```

Transitivity.

```

theorem mult-less-trans:  $K < M \implies M < N \implies K < (N::'a::order\ multiset)$ 
apply (unfold less-multiset-def mult-def)
apply (blast intro: trancl-trans)
done

```

Asymmetry.

```

theorem mult-less-not-sym:  $M < N \implies \neg N < (M::'a::order\ multiset)$ 

```

```

apply auto
apply (rule mult-less-not-refl [THEN notE])
apply (erule mult-less-trans, assumption)
done

```

theorem *mult-less-asy*:

```

 $M < N \implies (\neg P \implies N < (M::'a::\text{order multiset})) \implies P$ 
by (insert mult-less-not-sym, blast)

```

theorem *mult-le-refl [iff]*: $M \leq (M::'a::\text{order multiset})$
by (*unfold le-multiset-def, auto*)

Anti-symmetry.

theorem *mult-le-antisym*:

```

 $M \leq N \implies N \leq M \implies M = (N::'a::\text{order multiset})$ 
apply (unfold le-multiset-def)
apply (blast dest: mult-less-not-sym)
done

```

Transitivity.

theorem *mult-le-trans*:

```

 $K \leq M \implies M \leq N \implies K \leq (N::'a::\text{order multiset})$ 
apply (unfold le-multiset-def)
apply (blast intro: mult-less-trans)
done

```

theorem *mult-less-le*: $(M < N) = (M \leq N \wedge M \neq (N::'a::\text{order multiset}))$
by (*unfold le-multiset-def, auto*)

Partial order.

instance *multiset :: (order) order*

```

apply intro-classes
apply (rule mult-le-refl)
apply (erule mult-le-trans, assumption)
apply (erule mult-le-antisym, assumption)
apply (rule mult-less-le)
done

```

8.4.4 Monotonicity of multiset union

lemma *mult1-union*:

```

 $(B, D) \in \text{mult1 } r \implies \text{trans } r \implies (C + B, C + D) \in \text{mult1 } r$ 
apply (unfold mult1-def, auto)
apply (rule-tac x = a in exI)
apply (rule-tac x = C + M0 in exI)
apply (simp add: union-assoc)
done

```

lemma *union-less-mono2*: $B < D \implies C + B < C + (D::'a::\text{order multiset})$

```

apply (unfold less-multiset-def mult-def)
apply (erule trancl-induct)
  apply (blast intro: mult1-union transI order-less-trans r-into-trancl)
apply (blast intro: mult1-union transI order-less-trans r-into-trancl trancl-trans)
done

```

```

lemma union-less-mono1:  $B < D \implies B + C < D + (C::'a::order\ multiset)$ 
apply (subst union-commute [of B C])
apply (subst union-commute [of D C])
apply (erule union-less-mono2)
done

```

```

lemma union-less-mono:
   $A < C \implies B < D \implies A + B < C + (D::'a::order\ multiset)$ 
apply (blast intro!: union-less-mono1 union-less-mono2 mult-less-trans)
done

```

```

lemma union-le-mono:
   $A \leq C \implies B \leq D \implies A + B \leq C + (D::'a::order\ multiset)$ 
apply (unfold le-multiset-def)
apply (blast intro: union-less-mono union-less-mono1 union-less-mono2)
done

```

```

lemma empty-leI [iff]:  $\{\#\} \leq (M::'a::order\ multiset)$ 
apply (unfold le-multiset-def less-multiset-def)
apply (case-tac  $M = \{\#\}$ )
prefer 2
apply (subgoal-tac ( $\{\#\} + \{\#\}, \{\#\} + M \in mult\ (Collect\ (split\ op\ <))$ )
prefer 2
apply (rule one-step-implies-mult)
apply (simp only: trans-def, auto)
done

```

```

lemma union-upper1:  $A \leq A + (B::'a::order\ multiset)$ 
proof –
  have  $A + \{\#\} \leq A + B$  by (blast intro: union-le-mono)
  thus ?thesis by simp
qed

```

```

lemma union-upper2:  $B \leq A + (B::'a::order\ multiset)$ 
by (subst union-commute, rule union-upper1)

```

8.5 Link with lists

```

consts
  multiset-of :: 'a list  $\Rightarrow$  'a multiset
primrec
  multiset-of [] =  $\{\#\}$ 
  multiset-of (a # x) = multiset-of x +  $\{\# a \#\}$ 

```



```

lemma multiset-of-zero-iff[simp]: (multiset-of  $x = \{\#\}$ ) = ( $x = []$ )
  by (induct-tac  $x$ , auto)

lemma multiset-of-zero-iff-right[simp]: ( $\{\#\} = \text{multiset-of } x$ ) = ( $x = []$ )
  by (induct-tac  $x$ , auto)

lemma set-of-multiset-of[simp]: set-of (multiset-of  $x$ ) = set  $x$ 
  by (induct-tac  $x$ , auto)

lemma mem-set-multiset-eq:  $x \in \text{set } xs = (x : \# \text{ multiset-of } xs)$ 
  by (induct  $xs$ ) auto

lemma multiset-of-append[simp]:
  multiset-of ( $xs @ ys$ ) = multiset-of  $xs + \text{multiset-of } ys$ 
  by (rule-tac  $x=ys$  in spec, induct-tac  $xs$ , auto simp: union-ac)

lemma surj-multiset-of: surj multiset-of
  apply (unfold surj-def, rule allI)
  apply (rule-tac  $M=y$  in multiset-induct, auto)
  apply (rule-tac  $x = x \# xa$  in exI, auto)
  done

lemma set-count-greater-0: set  $x = \{a. 0 < \text{count } (\text{multiset-of } x) a\}$ 
  by (induct-tac  $x$ , auto)

lemma distinct-count-atmost-1:
  distinct  $x = (! a. \text{count } (\text{multiset-of } x) a = (\text{if } a \in \text{set } x \text{ then } 1 \text{ else } 0))$ 
  apply (induct-tac  $x$ , simp, rule iffI, simp-all)
  apply (rule conjI)
  apply (simp-all add: set-of-multiset-of [THEN sym] del: set-of-multiset-of)
  apply (erule-tac  $x=a$  in allE, simp, clarify)
  apply (erule-tac  $x=aa$  in allE, simp)
  done

lemma multiset-of-eq-setD:
  multiset-of  $xs = \text{multiset-of } ys \implies \text{set } xs = \text{set } ys$ 
  by (rule) (auto simp add: multiset-eq-conv-count-eq set-count-greater-0)

lemma set-eq-iff-multiset-of-eq-distinct:
   $\llbracket \text{distinct } x; \text{distinct } y \rrbracket$ 
   $\implies (\text{set } x = \text{set } y) = (\text{multiset-of } x = \text{multiset-of } y)$ 
  by (auto simp: multiset-eq-conv-count-eq distinct-count-atmost-1)

lemma set-eq-iff-multiset-of-remdups-eq:
  ( $\text{set } x = \text{set } y$ ) = (multiset-of (remdups  $x$ ) = multiset-of (remdups  $y$ ))
  apply (rule iffI)
  apply (simp add: set-eq-iff-multiset-of-eq-distinct [THEN iffD1])
  apply (drule distinct-remdups [THEN distinct-remdups]

```

```

[THEN set-eq-iff-multiset-of-eq-distinct[THEN iffD2]]])
apply simp
done

lemma multiset-of-compl-union[simp]:
  multiset-of [x∈xs. P x] + multiset-of [x∈xs. ¬P x] = multiset-of xs
  by (induct xs) (auto simp: union-ac)

lemma count-filter:
  count (multiset-of xs) x = length [y ∈ xs. y = x]
  by (induct xs, auto)

```

8.6 Pointwise ordering induced by count

```

consts
  mset-le :: ['a multiset, 'a multiset] ⇒ bool

syntax
  -mset-le :: 'a multiset ⇒ 'a multiset ⇒ bool  (- ≤# - [50,51] 50)
translations
  x ≤# y == mset-le x y

defs
  mset-le-def: xs ≤# ys == (∀ a. count xs a ≤ count ys a)

lemma mset-le-refl[simp]: xs ≤# xs
  by (unfold mset-le-def) auto

lemma mset-le-trans: [ xs ≤# ys; ys ≤# zs ] ⇒ xs ≤# zs
  by (unfold mset-le-def) (fast intro: order-trans)

lemma mset-le-antisym: [ xs ≤# ys; ys ≤# xs ] ⇒ xs = ys
  apply (unfold mset-le-def)
  apply (rule multiset-eq-conv-count-eq[THEN iffD2])
  apply (blast intro: order-antisym)
  done

lemma mset-le-exists-conv:
  (xs ≤# ys) = (∃ zs. ys = xs + zs)
  apply (unfold mset-le-def, rule iffI, rule-tac x = ys - xs in exI)
  apply (auto intro: multiset-eq-conv-count-eq [THEN iffD2])
  done

lemma mset-le-mono-add-right-cancel[simp]: (xs + zs ≤# ys + zs) = (xs ≤# ys)
  by (unfold mset-le-def) auto

lemma mset-le-mono-add-left-cancel[simp]: (zs + xs ≤# zs + ys) = (xs ≤# ys)
  by (unfold mset-le-def) auto

```

```

lemma mset-le-mono-add:  $\llbracket xs \leq\# ys; vs \leq\# ws \rrbracket \implies xs + vs \leq\# ys + ws$ 
  apply (unfold mset-le-def)
  apply auto
  apply (erule-tac x=a in allE)+
  apply auto
  done

```

```

lemma mset-le-add-left[simp]:  $xs \leq\# xs + ys$ 
  by (unfold mset-le-def) auto

```

```

lemma mset-le-add-right[simp]:  $ys \leq\# xs + ys$ 
  by (unfold mset-le-def) auto

```

```

lemma multiset-of-remdups-le:  $\text{multiset-of } (\text{remdups } x) \leq\# \text{multiset-of } x$ 
  apply (induct x)
  apply auto
  apply (rule mset-le-trans)
  apply auto
  done

```

```

end

```

9 NatPair: Pairs of Natural Numbers

```

theory NatPair
imports Main
begin

```

An injective function from \mathbb{N}^2 to \mathbb{N} . Definition and proofs are from [3, page 85].

```

constdefs
  nat2-to-nat:: (nat * nat)  $\Rightarrow$  nat
  nat2-to-nat pair  $\equiv$  let (n,m) = pair in (n+m) * Suc (n+m) div 2 + n

```

```

lemma dvd2-a-x-suc-a:  $2 \text{ dvd } a * (\text{Suc } a)$ 

```

```

proof (cases 2 dvd a)
  case True
  thus ?thesis by (rule dvd-mult2)

```

```

next

```

```

  case False
  hence Suc (a mod 2) = 2 by (simp add: dvd-eq-mod-eq-0)
  hence Suc a mod 2 = 0 by (simp add: mod-Suc)
  hence 2 dvd Suc a by (simp only: dvd-eq-mod-eq-0)
  thus ?thesis by (rule dvd-mult)

```

```

qed

```

```

lemma
  assumes eq: nat2-to-nat (u,v) = nat2-to-nat (x,y)

```

shows *nat2-to-nat-help*: $u+v \leq x+y$
proof (*rule classical*)
assume $\neg ?thesis$
hence *contrapos*: $x+y < u+v$
by *simp*
have *nat2-to-nat* $(x,y) < (x+y) * Suc(x+y) \text{ div } 2 + Suc(x+y)$
by (*unfold nat2-to-nat-def*) (*simp add: Let-def*)
also have $\dots = (x+y)*Suc(x+y) \text{ div } 2 + 2 * Suc(x+y) \text{ div } 2$
by (*simp only: div-mult-self1-is-m*)
also have $\dots = (x+y)*Suc(x+y) \text{ div } 2 + 2 * Suc(x+y) \text{ div } 2$
 $+ ((x+y)*Suc(x+y) \text{ mod } 2 + 2 * Suc(x+y) \text{ mod } 2) \text{ div } 2$
proof –
have $2 \text{ dvd } (x+y)*Suc(x+y)$
by (*rule dvd2-a-x-suc-a*)
hence $(x+y)*Suc(x+y) \text{ mod } 2 = 0$
by (*simp only: dvd-eq-mod-eq-0*)
also
have $2 * Suc(x+y) \text{ mod } 2 = 0$
by (*rule mod-mult-self1-is-0*)
ultimately have
 $((x+y)*Suc(x+y) \text{ mod } 2 + 2 * Suc(x+y) \text{ mod } 2) \text{ div } 2 = 0$
by *simp*
thus *?thesis*
by *simp*
qed
also have $\dots = ((x+y)*Suc(x+y) + 2*Suc(x+y)) \text{ div } 2$
by (*rule div-add1-eq [symmetric]*)
also have $\dots = ((x+y+2)*Suc(x+y)) \text{ div } 2$
by (*simp only: add-mult-distrib [symmetric]*)
also from *contrapos* **have** $\dots \leq ((Suc(u+v))*(u+v)) \text{ div } 2$
by (*simp only: mult-le-mono div-le-mono*)
also have $\dots \leq \text{nat2-to-nat}(u,v)$
by (*unfold nat2-to-nat-def*) (*simp add: Let-def*)
finally show *?thesis*
by (*simp only: eq*)
qed

theorem *nat2-to-nat-inj*: *inj nat2-to-nat*

proof –
{
fix $u\ v\ x\ y$ **assume** $\text{nat2-to-nat}(u,v) = \text{nat2-to-nat}(x,y)$
hence $u+v \leq x+y$ **by** (*rule nat2-to-nat-help*)
also from *prems* [*symmetric*] **have** $x+y \leq u+v$
by (*rule nat2-to-nat-help*)
finally have *eq*: $u+v = x+y$.
with *prems* **have** *ux*: $u=x$
by (*simp add: nat2-to-nat-def Let-def*)
with *eq* **have** *vy*: $v=y$
by *simp*

```

    with  $ux$  have  $(u,v) = (x,y)$ 
    by simp
  }
  hence  $\bigwedge x y. \text{nat2-to-nat } x = \text{nat2-to-nat } y \implies x=y$ 
  by fast
  thus ?thesis
  by (unfold inj-on-def) simp
qed

end

```

10 Nat-Infinity: Natural numbers with infinity

```

theory Nat-Infinity
imports Main
begin

```

10.1 Definitions

We extend the standard natural numbers by a special value indicating infinity. This includes extending the ordering relations $op <$ and $op \leq$.

```

datatype inat = Fin nat | Infty

```

```

instance inat :: {ord, zero} ..

```

```

consts

```

```

  iSuc :: inat => inat

```

```

syntax (xsymbols)

```

```

  Infty :: inat    ( $\infty$ )

```

```

syntax (HTML output)

```

```

  Infty :: inat    ( $\infty$ )

```

```

defs

```

```

  Zero-inat-def:  $0 == \text{Fin } 0$ 

```

```

  iSuc-def:  $\text{iSuc } i == \text{case } i \text{ of } \text{Fin } n \Rightarrow \text{Fin } (\text{Suc } n) \mid \infty \Rightarrow \infty$ 

```

```

  iless-def:  $m < n ==$ 

```

```

     $\text{case } m \text{ of } \text{Fin } m1 \Rightarrow (\text{case } n \text{ of } \text{Fin } n1 \Rightarrow m1 < n1 \mid \infty \Rightarrow \text{True})$ 
     $\mid \infty \Rightarrow \text{False}$ 

```

```

  ile-def:  $(m::\text{inat}) \leq n == \neg (n < m)$ 

```

```

lemmas inat-defs = Zero-inat-def iSuc-def illess-def ile-def

```

```

lemmas inat-splits = inat.split inat.split-asm

```

Below is a not quite complete set of theorems. Use the method (*simp add: inat-defs split:inat-splits, arith?*) to prove new theorems or solve arithmetic

subgoals involving *inat* on the fly.

10.2 Constructors

lemma *Fin-0*: $Fin\ 0 = 0$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *Infty-ne-i0* [*simp*]: $\infty \neq 0$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *i0-ne-Infty* [*simp*]: $0 \neq \infty$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *iSuc-Fin* [*simp*]: $iSuc\ (Fin\ n) = Fin\ (Suc\ n)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *iSuc-Infty* [*simp*]: $iSuc\ \infty = \infty$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *iSuc-ne-0* [*simp*]: $iSuc\ n \neq 0$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *iSuc-inject* [*simp*]: $(iSuc\ x = iSuc\ y) = (x = y)$
by (*simp add: inat-defs split:inat-splits, arith?*)

10.3 Ordering relations

lemma *Infty-ilessE* [*elim!*]: $\infty < Fin\ m \implies R$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *iless-linear*: $m < n \vee m = n \vee n < (m::inat)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *iless-not-refl* [*simp*]: $\neg n < (n::inat)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *iless-trans*: $i < j \implies j < k \implies i < (k::inat)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *iless-not-sym*: $n < m \implies \neg m < (n::inat)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *Fin-iless-mono* [*simp*]: $(Fin\ n < Fin\ m) = (n < m)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *Fin-iless-Infty* [*simp*]: $Fin\ n < \infty$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *Infty-eq* [*simp*]: $(n < \infty) = (n \neq \infty)$

by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *i0-eq* [*simp*]: $((0::inat) < n) = (n \neq 0)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *i0-iless-iSuc* [*simp*]: $0 < iSuc\ n$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *not-ilessi0* [*simp*]: $\neg n < (0::inat)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *Fin-iless*: $n < Fin\ m \implies \exists k. n = Fin\ k$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *iSuc-mono* [*simp*]: $(iSuc\ n < iSuc\ m) = (n < m)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *ile-def2*: $(m \leq n) = (m < n \vee m = (n::inat))$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *ile-refl* [*simp*]: $n \leq (n::inat)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *ile-trans*: $i \leq j \implies j \leq k \implies i \leq (k::inat)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *ile-iless-trans*: $i \leq j \implies j < k \implies i < (k::inat)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *iless-ile-trans*: $i < j \implies j \leq k \implies i < (k::inat)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *Infty-ub* [*simp*]: $n \leq \infty$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *i0-lb* [*simp*]: $(0::inat) \leq n$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *Infty-ileE* [*elim!*]: $\infty \leq Fin\ m \implies R$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *Fin-ile-mono* [*simp*]: $(Fin\ n \leq Fin\ m) = (n \leq m)$
by (*simp add: inat-defs split:inat-splits, arith?*)

lemma *ilessI1*: $n \leq m \implies n \neq m \implies n < (m::inat)$
by (*simp add: inat-defs split:inat-splits, arith?*)

```

lemma ileI1:  $m < n \implies iSuc\ m \leq n$ 
  by (simp add: inat-defs split:inat_splits, arith?)

lemma Suc-ile-eq:  $(Fin\ (Suc\ m) \leq n) = (Fin\ m < n)$ 
  by (simp add: inat-defs split:inat_splits, arith?)

lemma iSuc-ile-mono [simp]:  $(iSuc\ n \leq iSuc\ m) = (n \leq m)$ 
  by (simp add: inat-defs split:inat_splits, arith?)

lemma iless-Suc-eq [simp]:  $(Fin\ m < iSuc\ n) = (Fin\ m \leq n)$ 
  by (simp add: inat-defs split:inat_splits, arith?)

lemma not-iSuc-ilei0 [simp]:  $\neg iSuc\ n \leq 0$ 
  by (simp add: inat-defs split:inat_splits, arith?)

lemma ile-iSuc [simp]:  $n \leq iSuc\ n$ 
  by (simp add: inat-defs split:inat_splits, arith?)

lemma Fin-ile:  $n \leq Fin\ m \implies \exists k. n = Fin\ k$ 
  by (simp add: inat-defs split:inat_splits, arith?)

lemma chain-incr:  $\forall i. \exists j. Y\ i < Y\ j \implies \exists j. Fin\ k < Y\ j$ 
  apply (induct-tac k)
  apply (simp (no-asm) only: Fin-0)
  apply (fast intro: ile-iless-trans i0-lb)
  apply (erule exE)
  apply (drule spec)
  apply (erule exE)
  apply (erule exE)
  apply (erule ileI1)
  apply (rule iSuc-Fin [THEN subst])
  apply (rule exI)
  apply (erule (1) ile-iless-trans)
  done

end

```

11 Nested-Environment: Nested environments

```

theory Nested-Environment
imports Main
begin

```

Consider a partial function $e :: 'a \Rightarrow 'b\ option$; this may be understood as an *environment* mapping indexes $'a$ to optional entry values $'b$ (cf. the basic theory *Map* of Isabelle/HOL). This basic idea is easily generalized to that of a *nested environment*, where entries may be either basic values or again proper environments. Then each entry is accessed by a *path*, i.e. a list

of indexes leading to its position within the structure.

datatype ('a, 'b, 'c) env =
 Val 'a
 | Env 'b 'c => ('a, 'b, 'c) env option

In the type ('a, 'b, 'c) env the parameter 'a refers to basic values (occurring in terminal positions), type 'b to values associated with proper (inner) environments, and type 'c with the index type for branching. Note that there is no restriction on any of these types. In particular, arbitrary branching may yield rather large (transfinite) tree structures.

11.1 The lookup operation

Lookup in nested environments works by following a given path of index elements, leading to an optional result (a terminal value or nested environment). A *defined position* within a nested environment is one where *lookup* at its path does not yield *None*.

consts
 lookup :: ('a, 'b, 'c) env => 'c list => ('a, 'b, 'c) env option
 lookup-option :: ('a, 'b, 'c) env option => 'c list => ('a, 'b, 'c) env option

primrec (lookup)
 lookup (Val a) xs = (if xs = [] then Some (Val a) else None)
 lookup (Env b es) xs =
 (case xs of
 [] => Some (Env b es)
 | y # ys => lookup-option (es y) ys)
 lookup-option None xs = None
 lookup-option (Some e) xs = lookup e xs

hide const lookup-option

The characteristic cases of *lookup* are expressed by the following equalities.

theorem lookup-nil: lookup e [] = Some e
 by (cases e) simp-all

theorem lookup-val-cons: lookup (Val a) (x # xs) = None
 by simp

theorem lookup-env-cons:
 lookup (Env b es) (x # xs) =
 (case es x of
 None => None
 | Some e => lookup e xs)
 by (cases es x) simp-all

lemmas *lookup.simps* [*simp del*]
and *lookup-simps* [*simp*] = *lookup-nil lookup-val-cons lookup-env-cons*

theorem *lookup-eq*:

```
lookup env xs =
  (case xs of
    [] => Some env
  | x # xs =>
    (case env of
      Val a => None
    | Env b es =>
      (case es x of
        None => None
      | Some e => lookup e xs)))
by (simp split: list.split env.split)
```

Displaced *lookup* operations, relative to a certain base path prefix, may be reduced as follows. There are two cases, depending whether the environment actually extends far enough to follow the base path.

theorem *lookup-append-none*:

```
!!env. lookup env xs = None ==> lookup env (xs @ ys) = None
(is PROP ?P xs)
```

proof (*induct xs*)

```
fix env :: ('a, 'b, 'c) env
{
  assume lookup env [] = None
  hence False by simp
  thus lookup env ([] @ ys) = None ..
```

next

```
fix x xs
assume hyp: PROP ?P xs
assume asm: lookup env (x # xs) = None
show lookup env ((x # xs) @ ys) = None
proof (cases env)
```

```
  case Val
  thus ?thesis by simp
```

next

```
fix b es assume env: env = Env b es
show ?thesis
```

```
proof (cases es x)
  assume es x = None
  with env show ?thesis by simp
```

next

```
fix e assume es: es x = Some e
show ?thesis
proof (cases lookup e xs)
  case None
  hence lookup e (xs @ ys) = None by (rule hyp)
  with env es show ?thesis by simp
```

```

    next
    case Some
    with asm env es have False by simp
    thus ?thesis ..
  qed
qed
qed
}
qed

theorem lookup-append-some:
  !!env e. lookup env xs = Some e ==> lookup env (xs @ ys) = lookup e ys
  (is PROP ?P xs)
proof (induct xs)
  fix env e :: ('a, 'b, 'c) env
  {
    assume lookup env [] = Some e
    hence env = e by simp
    thus lookup env ([] @ ys) = lookup e ys by simp
  }
next
  fix x xs
  assume hyp: PROP ?P xs
  assume asm: lookup env (x # xs) = Some e
  show lookup env ((x # xs) @ ys) = lookup e ys
proof (cases env)
  fix a assume env = Val a
  with asm have False by simp
  thus ?thesis ..
next
  fix b es assume env: env = Env b es
  show ?thesis
proof (cases es x)
  assume es x = None
  with asm env have False by simp
  thus ?thesis ..
next
  fix e' assume es: es x = Some e'
  show ?thesis
proof (cases lookup e' xs)
  case None
  with asm env es have False by simp
  thus ?thesis ..
next
  case Some
  with asm env es have lookup e' xs = Some e
  by simp
  hence lookup e' (xs @ ys) = lookup e ys by (rule hyp)
  with env es show ?thesis by simp
qed

```

```

      qed
    qed
  }
qed

```

Successful *lookup* deeper down an environment structure means we are able to peek further up as well. Note that this is basically just the contrapositive statement of *lookup-append-none* above.

theorem *lookup-some-append*:

$lookup\ env\ (xs\ @\ ys) = Some\ e ==> \exists e. lookup\ env\ xs = Some\ e$

proof –

assume $lookup\ env\ (xs\ @\ ys) = Some\ e$

hence $lookup\ env\ (xs\ @\ ys) \neq None$ **by** *simp*

hence $lookup\ env\ xs \neq None$

by (*rule contrapos-nn*) (*simp only: lookup-append-none*)

thus *?thesis* **by** *simp*

qed

The subsequent statement describes in more detail how a successful *lookup* with a non-empty path results in a certain situation at any upper position.

theorem *lookup-some-upper*: $!!env\ e.$

$lookup\ env\ (xs\ @\ y\ \# \ ys) = Some\ e ==>$

$\exists b'\ es'\ env'.$

$lookup\ env\ xs = Some\ (Env\ b'\ es') \wedge$

$es'\ y = Some\ env' \wedge$

$lookup\ env'\ ys = Some\ e$

(**is** *PROP* *?P xs* **is** $!!env\ e.$ *?A env e xs* $==>$ *?C env e xs*)

proof (*induct xs*)

fix *env e* **let** *?A = ?A env e* **and** *?C = ?C env e*

{

assume *?A* []

hence $lookup\ env\ (y\ \# \ ys) = Some\ e$ **by** *simp*

then obtain *b' es' env'* **where**

env: $env = Env\ b'\ es'$ **and**

es': $es'\ y = Some\ env'$ **and**

look': $lookup\ env'\ ys = Some\ e$

by (*auto simp add: lookup-eq split: option.splits env.splits*)

from *env* **have** $lookup\ env\ [] = Some\ (Env\ b'\ es')$ **by** *simp*

with *es' look'* **show** *?C* [] **by** *blast*

next

fix *x xs*

assume *hyp*: *PROP* *?P xs*

assume *?A* (*x* # *xs*)

then obtain *b' es' env'* **where**

env: $env = Env\ b'\ es'$ **and**

es': $es'\ x = Some\ env'$ **and**

look': $lookup\ env'\ (xs\ @\ y\ \# \ ys) = Some\ e$

by (*auto simp add: lookup-eq split: option.splits env.splits*)

```

from hyp [OF look'] obtain b'' es'' env'' where
  upper': lookup env' xs = Some (Env b'' es'') and
  es'': es'' y = Some env'' and
  look'': lookup env'' ys = Some e
by blast
from env es' upper' have lookup env (x # xs) = Some (Env b'' es'')
by simp
with es'' look'' show ?C (x # xs) by blast
}
qed

```

11.2 The update operation

Update at a certain position in a nested environment may either delete an existing entry, or overwrite an existing one. Note that update at undefined positions is simple absorbed, i.e. the environment is left unchanged.

```

consts
  update :: 'c list => ('a, 'b, 'c) env option
  => ('a, 'b, 'c) env => ('a, 'b, 'c) env
  update-option :: 'c list => ('a, 'b, 'c) env option
  => ('a, 'b, 'c) env option => ('a, 'b, 'c) env option

primrec (update)
  update xs opt (Val a) =
    (if xs = [] then (case opt of None => Val a | Some e => e)
     else Val a)
  update xs opt (Env b es) =
    (case xs of
     [] => (case opt of None => Env b es | Some e => e)
     | y # ys => Env b (es (y := update-option ys opt (es y))))
  update-option xs opt None =
    (if xs = [] then opt else None)
  update-option xs opt (Some e) =
    (if xs = [] then opt else Some (update xs opt e))

```

hide const update-option

The characteristic cases of *update* are expressed by the following equalities.

theorem update-nil-none: $\text{update } [] \text{ None } \text{env} = \text{env}$
by (cases env) simp-all

theorem update-nil-some: $\text{update } [] \text{ (Some } e) \text{ env} = e$
by (cases env) simp-all

theorem update-cons-val: $\text{update } (x \# xs) \text{ opt } (\text{Val } a) = \text{Val } a$
by simp

theorem update-cons-nil-env:

```

  update [x] opt (Env b es) = Env b (es (x := opt))
by (cases es x) simp-all

```

theorem *update-cons-cons-env*:

```

  update (x # y # ys) opt (Env b es) =
    Env b (es (x :=
      (case es x of
        None => None
        | Some e => Some (update (y # ys) opt e))))
by (cases es x) simp-all

```

lemmas *update.simps* [simp del]
and *update-simps* [simp] = *update-nil-none* *update-nil-some*
update-cons-val *update-cons-nil-env* *update-cons-cons-env*

lemma *update-eq*:

```

  update xs opt env =
    (case xs of
      [] =>
        (case opt of
          None => env
          | Some e => e)
    | x # xs =>
      (case env of
        Val a => Val a
        | Env b es =>
          (case xs of
            [] => Env b (es (x := opt))
            | y # ys =>
              Env b (es (x :=
                (case es x of
                  None => None
                  | Some e => Some (update (y # ys) opt e)))))))
by (simp split: list.split env.split option.split)

```

The most basic correspondence of *lookup* and *update* states that after *update* at a defined position, subsequent *lookup* operations would yield the new value.

theorem *lookup-update-some*:

```

  !!env e. lookup env xs = Some e ==>
    lookup (update xs (Some env') env) xs = Some env'
(is PROP ?P xs)
proof (induct xs)
  fix env e :: ('a, 'b, 'c) env
  {
    assume lookup env [] = Some e
    hence env = e by simp
    thus lookup (update [] (Some env') env) [] = Some env'
    by simp
  }

```

```

next
  fix x xs
  assume hyp: PROP ?P xs
  assume asm: lookup env (x # xs) = Some e
  show lookup (update (x # xs) (Some env') env) (x # xs) = Some env'
  proof (cases env)
    fix a assume env = Val a
    with asm have False by simp
    thus ?thesis ..
  next
  fix b es assume env: env = Env b es
  show ?thesis
  proof (cases es x)
    assume es x = None
    with asm env have False by simp
    thus ?thesis ..
  next
  fix e' assume es: es x = Some e'
  show ?thesis
  proof (cases xs)
    assume xs = []
    with env show ?thesis by simp
  next
  fix x' xs' assume xs: xs = x' # xs'
  from asm env es have lookup e' xs = Some e by simp
  hence lookup (update xs (Some env') e') xs = Some env' by (rule hyp)
  with env es xs show ?thesis by simp
  qed
qed
qed
}
qed

```

The properties of displaced *update* operations are analogous to those of *lookup* above. There are two cases: below an undefined position *update* is absorbed altogether, and below a defined positions *update* affects subsequent *lookup* operations in the obvious way.

theorem *update-append-none*:

!!env. lookup env xs = None ==> update (xs @ y # ys) opt env = env
 (is PROP ?P xs)

proof (induct xs)

```

fix env :: ('a, 'b, 'c) env
{
  assume lookup env [] = None
  hence False by simp
  thus update ([] @ y # ys) opt env = env ..

```

next

```

fix x xs
assume hyp: PROP ?P xs

```

```

assume asm: lookup env (x # xs) = None
show update ((x # xs) @ y # ys) opt env = env
proof (cases env)
  fix a assume env = Val a
  thus ?thesis by simp
next
  fix b es assume env: env = Env b es
  show ?thesis
  proof (cases es x)
    assume es: es x = None
    show ?thesis
    by (cases xs) (simp-all add: es env fun-upd-idem-iff)
  next
    fix e assume es: es x = Some e
    show ?thesis
    proof (cases xs)
      assume xs = []
      with asm env es have False by simp
      thus ?thesis ..
    next
      fix x' xs' assume xs: xs = x' # xs'
      from asm env es have lookup e xs = None by simp
      hence update (xs @ y # ys) opt e = e by (rule hyp)
      with env es xs show update ((x # xs) @ y # ys) opt env = env
      by (simp add: fun-upd-idem-iff)
    qed
  qed
qed
}
qed

```

theorem *update-append-some*:

```

!!env e. lookup env xs = Some e ==>
  lookup (update (xs @ y # ys) opt env) xs = Some (update (y # ys) opt e)
(is PROP ?P xs)
proof (induct xs)
  fix env e :: ('a, 'b, 'c) env
  {
    assume lookup env [] = Some e
    hence env = e by simp
    thus lookup (update ([] @ y # ys) opt env) [] = Some (update (y # ys) opt e)
    by simp
  }
next
  fix x xs
  assume hyp: PROP ?P xs
  assume asm: lookup env (x # xs) = Some e
  show lookup (update ((x # xs) @ y # ys) opt env) (x # xs)
    = Some (update (y # ys) opt e)
  proof (cases env)

```



```

fix a assume env = Val a
with asm have False by simp
thus ?thesis ..
next
fix b es assume env: env = Env b es
show ?thesis
proof (cases es x)
  assume es x = None
  with asm env have False by simp
  thus ?thesis ..
next
fix e' assume es: es x = Some e'
show ?thesis
proof (cases xs)
  assume xs: xs = []
  from asm env es xs have e = e' by simp
  with env es xs show ?thesis by simp
next
fix x' xs' assume xs: xs = x' # xs'
from asm env es have lookup e' xs = Some e by simp
hence lookup (update (xs @ y # ys) opt e') xs =
  Some (update (y # ys) opt e) by (rule hyp)
with env es xs show ?thesis by simp
qed
qed
qed
}
qed

```

Apparently, *update* does not affect the result of subsequent *lookup* operations at independent positions, i.e. in case that the paths for *update* and *lookup* fork at a certain point.

theorem *lookup-update-other*:

!!env. $y \neq (z::'c) \implies \text{lookup } (\text{update } (xs @ z \# zs) \text{ opt env}) (xs @ y \# ys) =$
 $\text{lookup env } (xs @ y \# ys)$
(is PROP ?P xs)

proof (induct xs)

fix env :: ('a, 'b, 'c) env

assume neq: $y \neq z$

{
 show lookup (update ([] @ z # zs) opt env) ([] @ y # ys) =
 lookup env ([] @ y # ys)

proof (cases env)

case Val

thus ?thesis by simp

next

case Env

show ?thesis

proof (cases zs)

```

      case Nil
      with neq Env show ?thesis by simp
    next
      case Cons
      with neq Env show ?thesis by simp
    qed
  qed
next
  fix x xs
  assume hyp: PROP ?P xs
  show lookup (update ((x # xs) @ z # zs) opt env) ((x # xs) @ y # ys) =
    lookup env ((x # xs) @ y # ys)
  proof (cases env)
    case Val
    thus ?thesis by simp
  next
    fix y es assume env: env = Env y es
    show ?thesis
    proof (cases xs)
      assume xs: xs = []
      show ?thesis
      proof (cases es x)
        case None
        with env xs show ?thesis by simp
      next
        case Some
        with hyp env xs and neq show ?thesis by simp
      qed
    next
      fix x' xs' assume xs: xs = x' # xs'
      show ?thesis
      proof (cases es x)
        case None
        with env xs show ?thesis by simp
      next
        case Some
        with hyp env xs neq show ?thesis by simp
      qed
    qed
  qed
}
qed
end

```

12 Permutation: Permutations

theory *Permutation*

imports *Multiset*

begin

consts

perm :: ('a list * 'a list) set

syntax

-perm :: 'a list ==> 'a list ==> bool (- <~~> - [50, 50] 50)

translations

$x <~~> y == (x, y) \in perm$

inductive *perm*

intros

Nil [intro!]: [] <~~> []

swap [intro!]: $y \# x \# l <~~> x \# y \# l$

Cons [intro!]: $xs <~~> ys ==> z \# xs <~~> z \# ys$

trans [intro]: $xs <~~> ys ==> ys <~~> zs ==> xs <~~> zs$

lemma *perm-refl* [iff]: $l <~~> l$

by (*induct* *l*) *auto*

12.1 Some examples of rule induction on permutations

lemma *xperm-empty-imp-aux*: $xs <~~> ys ==> xs = [] \dashv\vdash ys = []$

— the form of the premise lets the induction bind *xs* and *ys*

apply (*erule perm.induct*)

apply (*simp-all* (*no-asm-simp*))

done

lemma *xperm-empty-imp*: $[] <~~> ys ==> ys = []$

using *xperm-empty-imp-aux* **by** *blast*

This more general theorem is easier to understand!

lemma *perm-length*: $xs <~~> ys ==> length\ xs = length\ ys$

by (*erule perm.induct*) *simp-all*

lemma *perm-empty-imp*: $[] <~~> xs ==> xs = []$

by (*drule perm-length*) *auto*

lemma *perm-sym*: $xs <~~> ys ==> ys <~~> xs$

by (*erule perm.induct*) *auto*

lemma *perm-mem* [rule-format]: $xs <~~> ys ==> x\ mem\ xs \dashv\vdash x\ mem\ ys$

by (*erule perm.induct*) *auto*

12.2 Ways of making new permutations

We can insert the head anywhere in the list.

```
lemma perm-append-Cons:  $a \# xs @ ys <\sim\sim> xs @ a \# ys$   

by (induct xs) auto
```

```
lemma perm-append-swap:  $xs @ ys <\sim\sim> ys @ xs$   

apply (induct xs)  

apply simp-all  

apply (blast intro: perm-append-Cons)  

done
```

```
lemma perm-append-single:  $a \# xs <\sim\sim> xs @ [a]$   

by (rule perm.trans [OF - perm-append-swap]) simp
```

```
lemma perm-rev:  $rev xs <\sim\sim> xs$   

apply (induct xs)  

apply simp-all  

apply (blast intro!: perm-append-single intro: perm-sym)  

done
```

```
lemma perm-append1:  $xs <\sim\sim> ys ==> l @ xs <\sim\sim> l @ ys$   

by (induct l) auto
```

```
lemma perm-append2:  $xs <\sim\sim> ys ==> xs @ l <\sim\sim> ys @ l$   

by (blast intro!: perm-append-swap perm-append1)
```

12.3 Further results

```
lemma perm-empty [iff]:  $([] <\sim\sim> xs) = (xs = [])$   

by (blast intro: perm-empty-imp)
```

```
lemma perm-empty2 [iff]:  $(xs <\sim\sim> []) = (xs = [])$   

apply auto  

apply (erule perm-sym [THEN perm-empty-imp])  

done
```

```
lemma perm-sing-imp [rule-format]:  $ys <\sim\sim> xs ==> xs = [y] \dashv\vdash ys = [y]$   

by (erule perm.induct) auto
```

```
lemma perm-sing-eq [iff]:  $(ys <\sim\sim> [y]) = (ys = [y])$   

by (blast intro: perm-sing-imp)
```

```
lemma perm-sing-eq2 [iff]:  $([y] <\sim\sim> ys) = (ys = [y])$   

by (blast dest: perm-sym)
```

12.4 Removing elements

consts

```

remove :: 'a => 'a list => 'a list
primrec
  remove x [] = []
  remove x (y # ys) = (if x = y then ys else y # remove x ys)

```

```

lemma perm-remove:  $x \in \text{set } ys \implies ys <\sim\sim> x \# \text{remove } x \text{ } ys$ 
by (induct ys) auto

```

```

lemma remove-commute:  $\text{remove } x (\text{remove } y \text{ } l) = \text{remove } y (\text{remove } x \text{ } l)$ 
by (induct l) auto

```

```

lemma multiset-of-remove[simp]:
  multiset-of (remove a x) = multiset-of x - {#a#}
apply (induct x)
apply (auto simp: multiset-eq-conv-count-eq)
done

```

Congruence rule

```

lemma perm-remove-perm:  $xs <\sim\sim> ys \implies \text{remove } z \text{ } xs <\sim\sim> \text{remove } z \text{ } ys$ 
by (erule perm.induct) auto

```

```

lemma remove-hd [simp]:  $\text{remove } z (z \# xs) = xs$ 
by auto

```

```

lemma cons-perm-imp-perm:  $z \# xs <\sim\sim> z \# ys \implies xs <\sim\sim> ys$ 
by (drule-tac z = z in perm-remove-perm) auto

```

```

lemma cons-perm-eq [iff]:  $(z \# xs <\sim\sim> z \# ys) = (xs <\sim\sim> ys)$ 
by (blast intro: cons-perm-imp-perm)

```

```

lemma append-perm-imp-perm:  $!!xs \text{ } ys. zs @ xs <\sim\sim> zs @ ys \implies xs <\sim\sim> ys$ 
apply (induct zs rule: rev-induct)
apply (simp-all (no-asm-use))
apply blast
done

```

```

lemma perm-append1-eq [iff]:  $(zs @ xs <\sim\sim> zs @ ys) = (xs <\sim\sim> ys)$ 
by (blast intro: append-perm-imp-perm perm-append1)

```

```

lemma perm-append2-eq [iff]:  $(xs @ zs <\sim\sim> ys @ zs) = (xs <\sim\sim> ys)$ 
apply (safe intro!: perm-append2)
apply (rule append-perm-imp-perm)
apply (rule perm-append-swap [THEN perm.trans])
  — the previous step helps this blast call succeed quickly
apply (blast intro: perm-append-swap)
done

```

```

lemma multiset-of-eq-perm:  $(\text{multiset-of } xs = \text{multiset-of } ys) = (xs <\sim\sim> ys)$ 

```

```

apply (rule iffI)
apply (erule-tac [2] perm.induct, simp-all add: union-ac)
apply (erule rev-mp, rule-tac x=ys in spec)
apply (induct-tac xs, auto)
apply (erule-tac x = remove a x in allE, drule sym, simp)
apply (subgoal-tac a ∈ set x)
apply (drule-tac z=a in perm.Cons)
apply (erule perm.trans, rule perm-sym, erule perm-remove)
apply (drule-tac f=set-of in arg-cong, simp)
done

lemma multiset-of-le-perm-append:
  (multiset-of xs ≤# multiset-of ys) = (∃ zs. xs @ zs <~~> ys)
apply (auto simp: multiset-of-eq-perm[THEN sym] mset-le-exists-conv)
apply (insert surj-multiset-of, drule surjD)
apply (blast intro: sym)+
done

end

```

13 Primes: Primality on nat

```

theory Primes
imports Main
begin

```

```

constdefs
  coprime :: nat => nat => bool
  coprime m n == gcd (m, n) = 1

  prime :: nat => bool
  prime p == 1 < p ∧ (∀ m. m dvd p --> m = 1 ∨ m = p)

```

```

lemma two-is-prime: prime 2
apply (auto simp add: prime-def)
apply (case-tac m)
apply (auto dest!: dvd-imp-le)
done

```

```

lemma prime-imp-relprime: prime p ==> ¬ p dvd n ==> gcd (p, n) = 1
apply (auto simp add: prime-def)
apply (drule-tac x = gcd (p, n) in spec)
apply auto
apply (insert gcd-dvd2 [of p n])
apply simp
done

```

This theorem leads immediately to a proof of the uniqueness of factorization. If p divides a product of primes then it is one of those primes.

lemma *prime-dvd-mult*: $\text{prime } p \implies p \text{ dvd } m * n \implies p \text{ dvd } m \vee p \text{ dvd } n$
by (*blast intro: relprime-dvd-mult prime-imp-relprime*)

lemma *prime-dvd-square*: $\text{prime } p \implies p \text{ dvd } m^{\text{Suc } 0} \implies p \text{ dvd } m$
by (*auto dest: prime-dvd-mult*)

lemma *prime-dvd-power-two*: $\text{prime } p \implies p \text{ dvd } m^2 \implies p \text{ dvd } m$
by (*rule prime-dvd-square*) (*simp-all add: power2-eq-square*)

end

14 Quotient: Quotient types

theory *Quotient*
imports *Main*
begin

We introduce the notion of quotient types over equivalence relations via axiomatic type classes.

14.1 Equivalence relations and quotient types

Type class *equiv* models equivalence relations $\sim :: 'a \Rightarrow 'a \Rightarrow \text{bool}$.

axclass *eqv* \subseteq *type*

consts

eqv :: $('a::\text{eqv}) \Rightarrow 'a \Rightarrow \text{bool}$ (**infixl** \sim 50)

axclass *equiv* \subseteq *eqv*

equiv-refl [*intro*]: $x \sim x$

equiv-trans [*trans*]: $x \sim y \implies y \sim z \implies x \sim z$

equiv-sym [*sym*]: $x \sim y \implies y \sim x$

lemma *equiv-not-sym* [*sym*]: $\neg (x \sim y) \implies \neg (y \sim (x::'a::\text{equiv}))$

proof –

assume $\neg (x \sim y)$ **thus** $\neg (y \sim x)$

by (*rule contrapos-nn*) (*rule equiv-sym*)

qed

lemma *not-equiv-trans1* [*trans*]: $\neg (x \sim y) \implies y \sim z \implies \neg (x \sim (z::'a::\text{equiv}))$

proof –

assume $\neg (x \sim y)$ **and** *yz*: $y \sim z$

show $\neg (x \sim z)$

proof

```

    assume  $x \sim z$ 
    also from  $yz$  have  $z \sim y$  ..
    finally have  $x \sim y$  .
    thus False by contradiction
  qed
qed

```

```

lemma not-equiv-trans2 [trans]:  $x \sim y \implies \neg (y \sim z) \implies \neg (x \sim (z::'a::equiv))$ 
proof -
  assume  $\neg (y \sim z)$  hence  $\neg (z \sim y)$  ..
  also assume  $x \sim y$  hence  $y \sim x$  ..
  finally have  $\neg (z \sim x)$  . thus  $(\neg x \sim z)$  ..
qed

```

The quotient type $'a \text{ quot}$ consists of all *equivalence classes* over elements of the base type $'a$.

```

typedef 'a quot = { {x. a ~ x} | a::'a::eqv. True }
by blast

```

```

lemma quotI [intro]:  $\{x. a \sim x\} \in \text{quot}$ 
by (unfold quot-def) blast

```

```

lemma quotE [elim]:  $R \in \text{quot} \implies (!a. R = \{x. a \sim x\} \implies C) \implies C$ 
by (unfold quot-def) blast

```

Abstracted equivalence classes are the canonical representation of elements of a quotient type.

```

constdefs
  class :: 'a::equiv => 'a quot    ([_])
  [a] == Abs-quot {x. a ~ x}

```

```

theorem quot-exhaust:  $\exists a. A = [a]$ 
proof (cases A)
  fix R assume R:  $A = \text{Abs-quot } R$ 
  assume  $R \in \text{quot}$  hence  $\exists a. R = \{x. a \sim x\}$  by blast
  with R have  $\exists a. A = \text{Abs-quot } \{x. a \sim x\}$  by blast
  thus ?thesis by (unfold class-def)
qed

```

```

lemma quot-cases [cases type: quot]:  $(!a. A = [a] \implies C) \implies C$ 
by (insert quot-exhaust) blast

```

14.2 Equality on quotients

Equality of canonical quotient elements coincides with the original relation.

```

theorem quot-equality [iff?]:  $([a] = [b]) = (a \sim b)$ 
proof

```



```

assume  $eq: \lfloor a \rfloor = \lfloor b \rfloor$ 
show  $a \sim b$ 
proof –
  from  $eq$  have  $\{x. a \sim x\} = \{x. b \sim x\}$ 
    by (simp only: class-def Abs-quot-inject quotI)
  moreover have  $a \sim a$  ..
  ultimately have  $a \in \{x. b \sim x\}$  by blast
  hence  $b \sim a$  by blast
  thus ?thesis ..
qed
next
assume  $ab: a \sim b$ 
show  $\lfloor a \rfloor = \lfloor b \rfloor$ 
proof –
  have  $\{x. a \sim x\} = \{x. b \sim x\}$ 
  proof (rule Collect-cong)
    fix  $x$  show  $(a \sim x) = (b \sim x)$ 
    proof
      from  $ab$  have  $b \sim a$  ..
      also assume  $a \sim x$ 
      finally show  $b \sim x$  .
    next
      note  $ab$ 
      also assume  $b \sim x$ 
      finally show  $a \sim x$  .
    qed
  qed
thus ?thesis by (simp only: class-def)
qed
qed

```

14.3 Picking representing elements

```

constdefs
   $pick :: 'a::equiv quot \Rightarrow 'a$ 
   $pick\ A == SOME\ a. A = \lfloor a \rfloor$ 

theorem pick-equiv [intro]:  $pick\ \lfloor a \rfloor \sim a$ 
proof (unfold pick-def)
  show  $(SOME\ x. \lfloor a \rfloor = \lfloor x \rfloor) \sim a$ 
  proof (rule someI2)
    show  $\lfloor a \rfloor = \lfloor a \rfloor$  ..
    fix  $x$  assume  $\lfloor a \rfloor = \lfloor x \rfloor$ 
    hence  $a \sim x$  .. thus  $x \sim a$  ..
  qed
qed

```

```

theorem pick-inverse [intro]:  $\lfloor pick\ A \rfloor = A$ 
proof (cases A)

```

```

fix  $a$  assume  $a: A = \lfloor a \rfloor$ 
hence  $\text{pick } A \sim a$  by (simp only: pick-equiv)
hence  $\lfloor \text{pick } A \rfloor = \lfloor a \rfloor$  ..
with  $a$  show ?thesis by simp
qed

```

The following rules support canonical function definitions on quotient types (with up to two arguments). Note that the stripped-down version without additional conditions is sufficient most of the time.

theorem *quot-cond-function*:

```

( $!!X Y. P X Y \implies f X Y == g (\text{pick } X) (\text{pick } Y) \implies$ 
 $(!!x x' y y'. \lfloor x \rfloor = \lfloor x' \rfloor \implies \lfloor y \rfloor = \lfloor y' \rfloor \implies$ 
 $\implies P \lfloor x \rfloor \lfloor y \rfloor \implies P \lfloor x' \rfloor \lfloor y' \rfloor \implies g x y = g x' y' \implies$ 
 $P \lfloor a \rfloor \lfloor b \rfloor \implies f \lfloor a \rfloor \lfloor b \rfloor = g a b$ 
 $(\text{is } PROP \text{ ?eq} \implies PROP \text{ ?cong} \implies - \implies -)$ )

```

proof –

```

assume cong: PROP ?cong
assume  $PROP \text{ ?eq}$  and  $P \lfloor a \rfloor \lfloor b \rfloor$ 
hence  $f \lfloor a \rfloor \lfloor b \rfloor = g (\text{pick } \lfloor a \rfloor) (\text{pick } \lfloor b \rfloor)$  by (simp only:)
also have  $\dots = g a b$ 
proof (rule cong)
  show  $\lfloor \text{pick } \lfloor a \rfloor \rfloor = \lfloor a \rfloor$  ..
  moreover
  show  $\lfloor \text{pick } \lfloor b \rfloor \rfloor = \lfloor b \rfloor$  ..
  moreover
  show  $P \lfloor a \rfloor \lfloor b \rfloor$  .
  ultimately show  $P \lfloor \text{pick } \lfloor a \rfloor \rfloor \lfloor \text{pick } \lfloor b \rfloor \rfloor$  by (simp only:)
qed
finally show ?thesis .
qed

```

theorem *quot-function*:

```

( $!!X Y. f X Y == g (\text{pick } X) (\text{pick } Y) \implies$ 
 $(!!x x' y y'. \lfloor x \rfloor = \lfloor x' \rfloor \implies \lfloor y \rfloor = \lfloor y' \rfloor \implies g x y = g x' y' \implies$ 
 $f \lfloor a \rfloor \lfloor b \rfloor = g a b$ )

```

proof –

```

case rule-context from this TrueI
show ?thesis by (rule quot-cond-function)
qed

```

theorem *quot-function'*:

```

( $!!X Y. f X Y == g (\text{pick } X) (\text{pick } Y) \implies$ 
 $(!!x x' y y'. x \sim x' \implies y \sim y' \implies g x y = g x' y' \implies$ 
 $f \lfloor a \rfloor \lfloor b \rfloor = g a b$ 
by (rule quot-function) (simp only: quot-equality)+

```

end

15 While-Combinator: A general “while” combinator

```
theory While-Combinator
imports Main
begin
```

We define a while-combinator *while* and prove: (a) an unrestricted unfolding law (even if *while* diverges!) (I got this idea from Wolfgang Goerigk), and (b) the invariant rule for reasoning about *while*.

```
consts while-aux :: ('a => bool) × ('a => 'a) × 'a => 'a
recdef (permissive) while-aux
  same-fst (λb. True) (λb. same-fst (λc. True) (λc.
    {(t, s). b s ∧ c s = t ∧
      ¬ (∃f. f (0::nat) = s ∧ (∀i. b (f i) ∧ c (f i) = f (i + 1))})))
  while-aux (b, c, s) =
    (if (∃f. f (0::nat) = s ∧ (∀i. b (f i) ∧ c (f i) = f (i + 1)))
      then arbitrary
      else if b s then while-aux (b, c, c s)
      else s)
```

```
recdef-tc while-aux-tc: while-aux
  apply (rule wf-same-fst)
  apply (rule wf-same-fst)
  apply (simp add: wf-iff-no-infinite-down-chain)
  apply blast
done
```

```
constdefs
  while :: ('a => bool) => ('a => 'a) => 'a => 'a
  while b c s == while-aux (b, c, s)
```

```
lemma while-aux-unfold:
  while-aux (b, c, s) =
    (if ∃f. f (0::nat) = s ∧ (∀i. b (f i) ∧ c (f i) = f (i + 1))
      then arbitrary
      else if b s then while-aux (b, c, c s)
      else s)
  apply (rule while-aux-tc [THEN while-aux.simps [THEN trans]])
  apply (rule refl)
done
```

The recursion equation for *while*: directly executable!

```
theorem while-unfold [code]:
  while b c s = (if b s then while b c (c s) else s)
  apply (unfold while-def)
  apply (rule while-aux-unfold [THEN trans])
  apply auto
```

```

apply (subst while-aux-unfold)
apply simp
apply clarify
apply (erule-tac x =  $\lambda i. f \text{ (Suc } i)$  in allE)
apply blast
done

hide const while-aux

lemma def-while-unfold: assumes fdef:  $f == \text{while test do}$ 
  shows  $f\ x = (\text{if test } x \text{ then } f(\text{do } x) \text{ else } x)$ 
proof –
  have  $f\ x = \text{while test do } x$  using fdef by simp
  also have  $\dots = (\text{if test } x \text{ then while test do (do } x) \text{ else } x)$ 
    by(rule while-unfold)
  also have  $\dots = (\text{if test } x \text{ then } f(\text{do } x) \text{ else } x)$  by(simp add:fdef[symmetric])
  finally show ?thesis .
qed

```

The proof rule for *while*, where P is the invariant.

```

theorem while-rule-lemma[rule-format]:
  [| !!s.  $P\ s ==> b\ s ==> P\ (c\ s);$ 
    !!s.  $P\ s ==> \neg b\ s ==> Q\ s;$ 
    wf  $\{(t, s). P\ s \wedge b\ s \wedge t = c\ s\}$  |] ==>
     $P\ s \dashv\dashv Q\ (\text{while } b\ c\ s)$ 
proof –
  case rule-context
  assume wf: wf  $\{(t, s). P\ s \wedge b\ s \wedge t = c\ s\}$ 
  show ?thesis
    apply (induct s rule: wf [THEN wf-induct])
    apply simp
    apply clarify
    apply (subst while-unfold)
    apply (simp add: rule-context)
    done
qed

```

```

theorem while-rule:
  [|  $P\ s;$ 
    !!s. [|  $P\ s; b\ s$  |] ==>  $P\ (c\ s);$ 
    !!s. [|  $P\ s; \neg b\ s$  |] ==>  $Q\ s;$ 
    wf  $r;$ 
    !!s. [|  $P\ s; b\ s$  |] ==>  $(c\ s, s) \in r$  |] ==>
     $Q\ (\text{while } b\ c\ s)$ 
apply (rule while-rule-lemma)
prefer 4 apply assumption
apply blast
apply blast
apply(erule wf-subset)

```

apply *blast*
done

An application: computation of the *lfp* on finite sets via iteration.

theorem *lfp-conv-while*:
 $[[\text{mono } f; \text{finite } U; f \ U = U]] ==>$
 $\text{lfp } f = \text{fst } (\text{while } (\lambda(A, fA). A \neq fA) (\lambda(A, fA). (fA, f fA)) (\{\}, f \{\}))$
apply (*rule-tac* $P = \lambda(A, B). (A \subseteq U \wedge B = f \ A \wedge A \subseteq B \wedge B \subseteq \text{lfp } f)$ **and**
 $r = ((\text{Pow } U \times \text{UNIV}) \times (\text{Pow } U \times \text{UNIV})) \cap$
 $\text{inv-image finite-psubset } (op - U \circ \text{fst})$ **in** *while-rule*)
apply (*subst lfp-unfold*)
apply *assumption*
apply (*simp add: monoD*)
apply (*subst lfp-unfold*)
apply *assumption*
apply *clarsimp*
apply (*blast dest: monoD*)
apply (*fastsimp intro!: lfp-lowerbound*)
apply (*blast intro: wf-finite-psubset Int-lower2 [THEN [2] wf-subset]*)
apply (*clarsimp simp add: inv-image-def finite-psubset-def order-less-le*)
apply (*blast intro!: finite-Diff dest: monoD*)
done

An example of using the *while* combinator.

Cannot use *set-eq-subset* because it leads to looping because the antisymmetry simproc turns the subset relationship back into equality.

lemma *seteq*: $(A = B) = (!a : A. a:B) \ \& \ (!b:B. b:A)$
by *blast*

theorem $P (\text{lfp } (\lambda N::\text{int set. } \{0\} \cup \{(n + 2) \bmod 6 \mid n. n \in N\})) =$
 $P \{0, 4, 2\}$
proof –
have *aux*: $!!f \ A \ B. \{f \ n \mid n. A \ n \vee B \ n\} = \{f \ n \mid n. A \ n\} \cup \{f \ n \mid n. B \ n\}$
apply *blast*
done
show *?thesis*
apply (*subst lfp-conv-while [where ?U = {0, 1, 2, 3, 4, 5}]*)
apply (*rule monoI*)
apply *blast*
apply *simp*
apply (*simp add: aux set-eq-subset*)

The fixpoint computation is performed purely by rewriting:

apply (*simp add: while-unfold aux seteq del: subset-empty*)
done
qed

end

16 Word: Binary Words

```
theory Word
imports Main
uses word-setup.ML
begin
```

16.1 Auxiliary Lemmas

```
lemma max-le [intro!]: [| x ≤ z; y ≤ z |] ==> max x y ≤ z
  by (simp add: max-def)
```

```
lemma max-mono:
  fixes x :: 'a::linorder
  assumes mf: mono f
  shows      max (f x) (f y) ≤ f (max x y)
proof -
  from mf and le-maxI1 [of x y]
  have fx: f x ≤ f (max x y)
    by (rule monoD)
  from mf and le-maxI2 [of y x]
  have fy: f y ≤ f (max x y)
    by (rule monoD)
  from fx and fy
  show max (f x) (f y) ≤ f (max x y)
    by auto
qed
```

```
declare zero-le-power [intro]
      and zero-less-power [intro]
```

```
lemma int-nat-two-exp: 2 ^ k = int (2 ^ k)
  by (simp add: zpower-int [symmetric])
```

16.2 Bits

```
datatype bit
  = Zero (0)
  | One (1)

consts
  bitval :: bit => nat

primrec
  bitval 0 = 0
  bitval 1 = 1
```

consts

```

bitnot :: bit => bit
bitand :: bit => bit => bit (infixr bitand 35)
bitor  :: bit => bit => bit (infixr bitor 30)
bitxor :: bit => bit => bit (infixr bitxor 30)

```

syntax (*xsymbols*)

```

bitnot :: bit => bit      ( $\neg_b$  - [40] 40)
bitand :: bit => bit => bit (infixr  $\wedge_b$  35)
bitor  :: bit => bit => bit (infixr  $\vee_b$  30)
bitxor :: bit => bit => bit (infixr  $\oplus_b$  30)

```

syntax (*HTML output*)

```

bitnot :: bit => bit      ( $\neg_b$  - [40] 40)
bitand :: bit => bit => bit (infixr  $\wedge_b$  35)
bitor  :: bit => bit => bit (infixr  $\vee_b$  30)
bitxor :: bit => bit => bit (infixr  $\oplus_b$  30)

```

primrec

```

bitnot-zero: (bitnot 0) = 1
bitnot-one : (bitnot 1) = 0

```

primrec

```

bitand-zero: (0 bitand y) = 0
bitand-one:  (1 bitand y) = y

```

primrec

```

bitor-zero: (0 bitor y) = y
bitor-one:  (1 bitor y) = 1

```

primrec

```

bitxor-zero: (0 bitxor y) = y
bitxor-one:  (1 bitxor y) = (bitnot y)

```

lemma *bitnot-bitnot* [simp]: (bitnot (bitnot b)) = b
by (cases b, simp-all)

lemma *bitand-cancel* [simp]: (b bitand b) = b
by (cases b, simp-all)

lemma *bitor-cancel* [simp]: (b bitor b) = b
by (cases b, simp-all)

lemma *bitxor-cancel* [simp]: (b bitxor b) = 0
by (cases b, simp-all)

16.3 Bit Vectors

First, a couple of theorems expressing case analysis and induction principles for bit vectors.

lemma *bit-list-cases*:

```

  assumes empty:  $w = [] \implies P\ w$ 
  and zero:  $!!bs. w = 0 \# bs \implies P\ w$ 
  and one:  $!!bs. w = 1 \# bs \implies P\ w$ 
  shows  $P\ w$ 
proof (cases  $w$ )
  assume  $w = []$ 
  thus ?thesis
    by (rule empty)
next
  fix  $b\ bs$ 
  assume [simp]:  $w = b \# bs$ 
  show  $P\ w$ 
  proof (cases  $b$ )
  assume  $b = 0$ 
  hence  $w = 0 \# bs$ 
    by simp
  thus ?thesis
    by (rule zero)
next
  assume  $b = 1$ 
  hence  $w = 1 \# bs$ 
    by simp
  thus ?thesis
    by (rule one)
qed
qed

```

lemma *bit-list-induct*:

```

  assumes empty:  $P\ []$ 
  and zero:  $!!bs. P\ bs \implies P\ (0 \# bs)$ 
  and one:  $!!bs. P\ bs \implies P\ (1 \# bs)$ 
  shows  $P\ w$ 
proof (induct  $w$ , simp-all add: empty)
  fix  $b\ bs$ 
  assume [intro!]:  $P\ bs$ 
  show  $P\ (b \# bs)$ 
    by (cases  $b$ , auto intro!: zero one)
qed

```

constdefs

```

  bv-msb :: bit list => bit
  bv-msb  $w ==$  if  $w = []$  then 0 else hd  $w$ 
  bv-extend :: [nat, bit, bit list] => bit list
  bv-extend  $i\ b\ w ==$  (replicate ( $i - \text{length } w$ )  $b$ ) @  $w$ 

```


bv-not :: *bit list* ==> *bit list*
bv-not w == *map bitnot w*

lemma *bv-length-extend* [*simp*]: *length w* ≤ *i* ==> *length (bv-extend i b w)* = *i*
by (*simp add: bv-extend-def*)

lemma *bv-not-Nil* [*simp*]: *bv-not []* = []
by (*simp add: bv-not-def*)

lemma *bv-not-Cons* [*simp*]: *bv-not (b#bs)* = (*bitnot b*) # *bv-not bs*
by (*simp add: bv-not-def*)

lemma *bv-not-bv-not* [*simp*]: *bv-not (bv-not w)* = *w*
by (*rule bit-list-induct [of - w], simp-all*)

lemma *bv-msb-Nil* [*simp*]: *bv-msb []* = 0
by (*simp add: bv-msb-def*)

lemma *bv-msb-Cons* [*simp*]: *bv-msb (b#bs)* = *b*
by (*simp add: bv-msb-def*)

lemma *bv-msb-bv-not* [*simp*]: *0 < length w* ==> *bv-msb (bv-not w)* = (*bitnot (bv-msb w)*)
by (*cases w, simp-all*)

lemma *bv-msb-one-length* [*simp, intro*]: *bv-msb w* = 1 ==> *0 < length w*
by (*cases w, simp-all*)

lemma *length-bv-not* [*simp*]: *length (bv-not w)* = *length w*
by (*induct w, simp-all*)

constdefs

bv-to-nat :: *bit list* ==> *nat*
bv-to-nat == *foldl (%bn b. 2 * bn + bitval b) 0*

lemma *bv-to-nat-Nil* [*simp*]: *bv-to-nat []* = 0
by (*simp add: bv-to-nat-def*)

lemma *bv-to-nat-helper* [*simp*]: *bv-to-nat (b # bs)* = *bitval b * 2 ^ length bs + bv-to-nat bs*

proof –

let *?bv-to-nat'* = *foldl (λbn b. 2 * bn + bitval b)*

have *helper*: $\bigwedge \text{base. } ?bv\text{-to-nat}' \text{ base } bs = \text{base} * 2 ^ \text{length } bs + ?bv\text{-to-nat}' 0$
bs

proof (*induct bs*)

case *Nil* **show** *?case* **by** *simp*

next

case (*Cons x xs base*)

show *?case*

```

    apply (simp only: foldl.simps)
    apply (subst Cons [of 2 * base + bitval x])
    apply simp
    apply (subst Cons [of bitval x])
    apply (simp add: add-mult-distrib)
    done
  qed
  show ?thesis by (simp add: bv-to-nat-def) (rule helper)
  qed

```

```

lemma bv-to-nat0 [simp]: bv-to-nat (0#bs) = bv-to-nat bs
  by simp

```

```

lemma bv-to-nat1 [simp]: bv-to-nat (1#bs) = 2 ^ length bs + bv-to-nat bs
  by simp

```

```

lemma bv-to-nat-upper-range: bv-to-nat w < 2 ^ length w
proof (induct w, simp-all)
  fix b bs
  assume bv-to-nat bs < 2 ^ length bs
  show bitval b * 2 ^ length bs + bv-to-nat bs < 2 * 2 ^ length bs
  proof (cases b, simp-all)
    have bv-to-nat bs < 2 ^ length bs
    .
    also have ... < 2 * 2 ^ length bs
    by auto
    finally show bv-to-nat bs < 2 * 2 ^ length bs
    by simp
  next
    have bv-to-nat bs < 2 ^ length bs
    .
    hence 2 ^ length bs + bv-to-nat bs < 2 ^ length bs + 2 ^ length bs
    by arith
    also have ... = 2 * (2 ^ length bs)
    by simp
    finally show bv-to-nat bs < 2 ^ length bs
    by simp
  qed
  qed

```

```

lemma bv-extend-longer [simp]:
  assumes wn: n ≤ length w
  shows      bv-extend n b w = w
  by (simp add: bv-extend-def wn)

```

```

lemma bv-extend-shorter [simp]:
  assumes wn: length w < n
  shows      bv-extend n b w = bv-extend n b (b#w)
proof -

```

```

from  $wn$ 
have  $s: n - \text{Suc} (\text{length } w) + 1 = n - \text{length } w$ 
  by arith
have  $\text{bv-extend } n \ b \ w = \text{replicate } (n - \text{length } w) \ b \ @ \ w$ 
  by (simp add: bv-extend-def)
also have  $\dots = \text{replicate } (n - \text{Suc} (\text{length } w) + 1) \ b \ @ \ w$ 
  by (subst s,rule)
also have  $\dots = (\text{replicate } (n - \text{Suc} (\text{length } w)) \ b \ @ \ \text{replicate } 1 \ b) \ @ \ w$ 
  by (subst replicate-add,rule)
also have  $\dots = \text{replicate } (n - \text{Suc} (\text{length } w)) \ b \ @ \ b \ \# \ w$ 
  by simp
also have  $\dots = \text{bv-extend } n \ b \ (b \ \# \ w)$ 
  by (simp add: bv-extend-def)
finally show  $\text{bv-extend } n \ b \ w = \text{bv-extend } n \ b \ (b \ \# \ w)$ 

```

qed

consts

rem-initial :: *bit* => *bit list* => *bit list*

primrec

rem-initial *b* [] = []
rem-initial *b* (*x* # *xs*) = (if *b* = *x* then *rem-initial* *b* *xs* else *x* # *xs*)

lemma *rem-initial-length*: $\text{length} (\text{rem-initial } b \ w) \leq \text{length } w$
by (*rule bit-list-induct [of - w],simp-all (no-asm),safe,simp-all*)

lemma *rem-initial-equal*:

assumes *p*: $\text{length} (\text{rem-initial } b \ w) = \text{length } w$
shows $\text{rem-initial } b \ w = w$

proof –

have $\text{length} (\text{rem-initial } b \ w) = \text{length } w \ \longrightarrow \ \text{rem-initial } b \ w = w$

proof (*induct w,simp-all,clarify*)

fix *xs*

assume $\text{length} (\text{rem-initial } b \ xs) = \text{length } xs \ \longrightarrow \ \text{rem-initial } b \ xs = xs$

assume *f*: $\text{length} (\text{rem-initial } b \ xs) = \text{Suc} (\text{length } xs)$

with *rem-initial-length* [*of b xs*]

show $\text{rem-initial } b \ xs = b \ \# \ xs$

by *auto*

qed

thus *?thesis*

..

qed

lemma *bv-extend-rem-initial*: $\text{bv-extend} (\text{length } w) \ b \ (\text{rem-initial } b \ w) = w$

proof (*induct w,simp-all,safe*)

fix *xs*

assume *ind*: $\text{bv-extend} (\text{length } xs) \ b \ (\text{rem-initial } b \ xs) = xs$

from *rem-initial-length* [*of b xs*]

```

have [simp]: Suc (length xs) - length (rem-initial b xs) = 1 + (length xs -
length (rem-initial b xs))
  by arith
have bv-extend (Suc (length xs)) b (rem-initial b xs) = replicate (Suc (length xs)
- length (rem-initial b xs)) b @ (rem-initial b xs)
  by (simp add: bv-extend-def)
also have ... = replicate (1 + (length xs - length (rem-initial b xs))) b @
rem-initial b xs
  by simp
also have ... = (replicate 1 b @ replicate (length xs - length (rem-initial b xs))
b) @ rem-initial b xs
  by (subst replicate-add, rule refl)
also have ... = b # bv-extend (length xs) b (rem-initial b xs)
  by (auto simp add: bv-extend-def [symmetric])
also have ... = b # xs
  by (simp add: ind)
finally show bv-extend (Suc (length xs)) b (rem-initial b xs) = b # xs
  .
qed

```

```

lemma rem-initial-append1:
  assumes rem-initial b xs ~ = []
  shows rem-initial b (xs @ ys) = rem-initial b xs @ ys
proof -
  have rem-initial b xs ~ = [] --> rem-initial b (xs @ ys) = rem-initial b xs @ ys
  (is ?P xs ys)
  by (induct xs, auto)
  thus ?thesis
  ..
qed

```

```

lemma rem-initial-append2:
  assumes rem-initial b xs = []
  shows rem-initial b (xs @ ys) = rem-initial b ys
proof -
  have rem-initial b xs = [] --> rem-initial b (xs @ ys) = rem-initial b ys (is ?P
xs ys)
  by (induct xs, auto)
  thus ?thesis
  ..
qed

```

```

constdefs
  norm-unsigned :: bit list => bit list
  norm-unsigned == rem-initial 0

```

```

lemma norm-unsigned-Nil [simp]: norm-unsigned [] = []
  by (simp add: norm-unsigned-def)

```

lemma *norm-unsigned-Cons0* [simp]: *norm-unsigned* (**0**#*bs*) = *norm-unsigned* *bs*
by (*simp add: norm-unsigned-def*)

lemma *norm-unsigned-Cons1* [simp]: *norm-unsigned* (**1**#*bs*) = **1**#*bs*
by (*simp add: norm-unsigned-def*)

lemma *norm-unsigned-idem* [simp]: *norm-unsigned* (*norm-unsigned* *w*) = *norm-unsigned* *w*
by (*rule bit-list-induct [of - w], simp-all*)

consts

nat-to-bv-helper :: *nat* ==> *bit list* ==> *bit list*

recdef *nat-to-bv-helper measure* ($\lambda n. n$)
nat-to-bv-helper *n* = (%*bs*. (if *n* = 0 then *bs*
else *nat-to-bv-helper* (*n* div 2) ((if *n* mod 2 = 0 then **0**
else **1**)#*bs*)))

constdefs

nat-to-bv :: *nat* ==> *bit list*

nat-to-bv *n* == *nat-to-bv-helper* *n* []

lemma *nat-to-bv0* [simp]: *nat-to-bv* 0 = []
by (*simp add: nat-to-bv-def*)

lemmas [simp del] = *nat-to-bv-helper.simps*

lemma *n-div-2-cases*:

assumes *zero*: (*n*::*nat*) = 0 ==> *R*

and *div* : [] *n* div 2 < *n* ; 0 < *n* [] ==> *R*

shows *R*

proof (*cases n = 0*)

assume *n* = 0

thus *R*

by (*rule zero*)

next

assume *n* ~ = 0

hence *nn0*: 0 < *n*

by *simp*

hence *n* div 2 < *n*

by *arith*

from this and *nn0*

show *R*

by (*rule div*)

qed

lemma *int-wf-ge-induct*:

assumes *base*: *P* (*k*::*int*)

and *ind* : !!*i*. (!!*j*. [] *k* ≤ *j* ; *j* < *i* [] ==> *P j*) ==> *P i*

```

and      valid:  $k \leq i$ 
shows     $P\ i$ 
proof -
  have a:  $\forall j. k \leq j \wedge j < i \longrightarrow P\ j$ 
  proof (rule int-ge-induct)
    show  $k \leq i$ 
    .
  next
    show  $\forall j. k \leq j \wedge j < k \longrightarrow P\ j$ 
    by auto
  next
    fix i
    assume  $k \leq i$ 
    assume a:  $\forall j. k \leq j \wedge j < i \longrightarrow P\ j$ 
    have pi:  $P\ i$ 
    proof (rule ind)
      fix j
      assume  $k \leq j$  and  $j < i$ 
      with a
      show  $P\ j$ 
      by auto
    qed
    show  $\forall j. k \leq j \wedge j < i + 1 \longrightarrow P\ j$ 
    proof auto
      fix j
      assume kj:  $k \leq j$ 
      assume ji:  $j \leq i$ 
      show  $P\ j$ 
      proof (cases  $j = i$ )
        assume  $j = i$ 
        with pi
        show  $P\ j$ 
        by simp
      next
        assume  $j \sim i$ 
        with ji
        have  $j < i$ 
        by simp
        with kj and a
        show  $P\ j$ 
        by blast
      qed
    qed
  qed
  show  $P\ i$ 
  proof (rule ind)
    fix j
    assume  $k \leq j$  and  $j < i$ 
    with a

```

```

    show  $P\ j$ 
    by auto
  qed
qed

lemma unfold-nat-to-bv-helper:
  nat-to-bv-helper  $b\ l = nat-to-bv-helper\ b\ [] @ l$ 
proof -
  have  $\forall l. nat-to-bv-helper\ b\ l = nat-to-bv-helper\ b\ [] @ l$ 
  proof (induct  $b$  rule: less-induct)
    fix  $n$ 
    assume ind:  $!!j. j < n \implies \forall l. nat-to-bv-helper\ j\ l = nat-to-bv-helper\ j\ [] @ l$ 
    show  $\forall l. nat-to-bv-helper\ n\ l = nat-to-bv-helper\ n\ [] @ l$ 
    proof
      fix  $l$ 
      show  $nat-to-bv-helper\ n\ l = nat-to-bv-helper\ n\ [] @ l$ 
      proof (cases  $n < 0$ )
        assume  $n < 0$ 
        thus ?thesis
          by (simp add: nat-to-bv-helper.simps)
      next
        assume  $\sim n < 0$ 
        show ?thesis
          proof (rule n-div-2-cases [of  $n$ ])
            assume [simp]:  $n = 0$ 
            show ?thesis
              apply (simp only: nat-to-bv-helper.simps [of  $n$ ])
              apply simp
              done
          next
            assume  $n2n: n\ div\ 2 < n$ 
            assume [simp]:  $0 < n$ 
            hence  $n20: 0 \leq n\ div\ 2$ 
            by arith
            from ind [of  $n\ div\ 2$ ] and  $n2n\ n20$ 
            have ind':  $\forall l. nat-to-bv-helper\ (n\ div\ 2)\ l = nat-to-bv-helper\ (n\ div\ 2)\ [] @ l$ 
            by blast
          show ?thesis
            apply (simp only: nat-to-bv-helper.simps [of  $n$ ])
            apply (cases  $n=0$ )
            apply simp
            apply (simp only: if-False)
            apply simp
            apply (subst spec [OF ind', of  $0\#l$ ])
            apply (subst spec [OF ind', of  $1\#l$ ])
            apply (subst spec [OF ind', of  $[1]$ ])
            apply (subst spec [OF ind', of  $[0]$ ])
            apply simp
          done
        done
      next
        assume  $n \geq 0$ 
        show ?thesis
          by (simp only: nat-to-bv-helper.simps [of  $n$ ])
      done
    done
  done

```

```

      done
    qed
  qed
  qed
  qed
  thus ?thesis
..
qed

```

lemma *nat-to-bv-non0* [simp]: $0 < n \implies \text{nat-to-bv } n = \text{nat-to-bv } (n \text{ div } 2) @$
 $[\text{if } n \bmod 2 = 0 \text{ then } \mathbf{0} \text{ else } \mathbf{1}]$

```

proof -
  assume [simp]:  $0 < n$ 
  show ?thesis
    apply (subst nat-to-bv-def [of n])
    apply (simp only: nat-to-bv-helper.simps [of n])
    apply (subst unfold-nat-to-bv-helper)
    using prems
    apply simp
    apply (subst nat-to-bv-def [of n div 2])
    apply auto
    done
qed

```

lemma *bv-to-nat-dist-append*: $\text{bv-to-nat } (l1 @ l2) = \text{bv-to-nat } l1 * 2^{\text{length } l2} + \text{bv-to-nat } l2$

```

proof -
  have  $\forall l2. \text{bv-to-nat } (l1 @ l2) = \text{bv-to-nat } l1 * 2^{\text{length } l2} + \text{bv-to-nat } l2$ 
  proof (induct l1, simp-all)
    fix x xs
    assume ind:  $\forall l2. \text{bv-to-nat } (xs @ l2) = \text{bv-to-nat } xs * 2^{\text{length } l2} + \text{bv-to-nat } l2$ 
    show  $\forall l2. \text{bitval } x * 2^{(\text{length } xs + \text{length } l2)} + \text{bv-to-nat } xs * 2^{\text{length } l2} =$   

 $(\text{bitval } x * 2^{\text{length } xs} + \text{bv-to-nat } xs) * 2^{\text{length } l2}$ 
    proof
      fix l2
      show  $\text{bitval } x * 2^{(\text{length } xs + \text{length } l2)} + \text{bv-to-nat } xs * 2^{\text{length } l2} =$   

 $(\text{bitval } x * 2^{\text{length } xs} + \text{bv-to-nat } xs) * 2^{\text{length } l2}$ 
      proof -
        have  $(2::\text{nat})^{(\text{length } xs + \text{length } l2)} = 2^{\text{length } xs} * 2^{\text{length } l2}$ 
        by (induct length xs, simp-all)
        hence  $\text{bitval } x * 2^{(\text{length } xs + \text{length } l2)} + \text{bv-to-nat } xs * 2^{\text{length } l2} =$   

 $\text{bitval } x * 2^{\text{length } xs} * 2^{\text{length } l2} + \text{bv-to-nat } xs * 2^{\text{length } l2}$ 
        by simp
        also have  $\dots = (\text{bitval } x * 2^{\text{length } xs} + \text{bv-to-nat } xs) * 2^{\text{length } l2}$ 
        by (simp add: ring-distrib)
        finally show ?thesis .
      qed
    qed
  qed

```


qed
 thus ?thesis

..
 qed

lemma *bv-nat-bv* [simp]: *bv-to-nat* (*nat-to-bv* *n*) = *n*
proof (*induct* *n* *rule*: *less-induct*)
fix *n*
assume *ind*: $\forall j. j < n \implies \text{bv-to-nat} (\text{nat-to-bv } j) = j$
show *bv-to-nat* (*nat-to-bv* *n*) = *n*
proof (*rule* *n-div-2-cases* [of *n*])
assume [simp]: *n* = 0
show ?thesis
by *simp*
next
assume *nn*: *n* div 2 < *n*
assume *n0*: 0 < *n*
from *ind* **and** *nn*
have *ind'*: *bv-to-nat* (*nat-to-bv* (*n* div 2)) = *n* div 2
by *blast*
from *n0* **have** *n0'*: *n* ≠ 0
by *simp*
show ?thesis
apply (*subst* *nat-to-bv-def*)
apply (*simp* *only*: *nat-to-bv-helper.simps* [of *n*])
apply (*simp* *only*: *n0' if-False*)
apply (*subst* *unfold-nat-to-bv-helper*)
apply (*subst* *bv-to-nat-dist-append*)
apply (*fold* *nat-to-bv-def*)
apply (*simp* *add*: *ind'* *split* *del*: *split-if*)
apply (*cases* *n mod 2 = 0*)
proof *simp-all*
assume *n mod 2 = 0*
with *mod-div-equality* [of *n* 2]
show *n* div 2 * 2 = *n*
by *simp*
next
assume *n mod 2 = Suc 0*
with *mod-div-equality* [of *n* 2]
show *Suc* (*n* div 2 * 2) = *n*
by *simp*
 qed
 qed
 qed

lemma *bv-to-nat-type* [simp]: *bv-to-nat* (*norm-unsigned* *w*) = *bv-to-nat* *w*
by (*rule* *bit-list-induct, simp-all*)

lemma *length-norm-unsigned-le* [simp]: *length* (*norm-unsigned* *w*) ≤ *length* *w*

```

by (rule bit-list-induct,simp-all)

lemma bv-to-nat-rew-msb: bv-msb w = 1 ==> bv-to-nat w = 2 ^ (length w - 1)
+ bv-to-nat (tl w)
by (rule bit-list-cases [of w],simp-all)

lemma norm-unsigned-result: norm-unsigned xs = [] ∨ bv-msb (norm-unsigned xs)
= 1
proof (rule length-induct [of - xs])
  fix xs :: bit list
  assume ind: ∀ ys. length ys < length xs --> norm-unsigned ys = [] ∨ bv-msb
(norm-unsigned ys) = 1
  show norm-unsigned xs = [] ∨ bv-msb (norm-unsigned xs) = 1
  proof (rule bit-list-cases [of xs],simp-all)
    fix bs
    assume [simp]: xs = 0#bs
    from ind
    have length bs < length xs --> norm-unsigned bs = [] ∨ bv-msb (norm-unsigned
bs) = 1
    ..
    thus norm-unsigned bs = [] ∨ bv-msb (norm-unsigned bs) = 1
    by simp
  qed
qed
qed

lemma norm-empty-bv-to-nat-zero:
  assumes nw: norm-unsigned w = []
  shows      bv-to-nat w = 0
proof -
  have bv-to-nat w = bv-to-nat (norm-unsigned w)
  by simp
  also have ... = bv-to-nat []
  by (subst nw,rule)
  also have ... = 0
  by simp
  finally show ?thesis .
qed

lemma bv-to-nat-lower-limit:
  assumes w0: 0 < bv-to-nat w
  shows      2 ^ (length (norm-unsigned w) - 1) ≤ bv-to-nat w
proof -
  from w0 and norm-unsigned-result [of w]
  have msbw: bv-msb (norm-unsigned w) = 1
  by (auto simp add: norm-empty-bv-to-nat-zero)
  have 2 ^ (length (norm-unsigned w) - 1) ≤ bv-to-nat (norm-unsigned w)
  by (subst bv-to-nat-rew-msb [OF msbw],simp)
  thus ?thesis
  by simp

```

qed

lemmas [simp del] = nat-to-bv-non0

lemma norm-unsigned-length [intro!]: length (norm-unsigned w) ≤ length w
by (subst norm-unsigned-def, rule rem-initial-length)

lemma norm-unsigned-equal: length (norm-unsigned w) = length w ==> norm-unsigned w = w
by (simp add: norm-unsigned-def, rule rem-initial-equal)

lemma bv-extend-norm-unsigned: bv-extend (length w) 0 (norm-unsigned w) = w
by (simp add: norm-unsigned-def, rule bv-extend-rem-initial)

lemma norm-unsigned-append1 [simp]: norm-unsigned xs ≠ [] ==> norm-unsigned (xs @ ys) = norm-unsigned xs @ ys
by (simp add: norm-unsigned-def, rule rem-initial-append1)

lemma norm-unsigned-append2 [simp]: norm-unsigned xs = [] ==> norm-unsigned (xs @ ys) = norm-unsigned ys
by (simp add: norm-unsigned-def, rule rem-initial-append2)

lemma bv-to-nat-zero-imp-empty [rule-format]:
bv-to-nat w = 0 → norm-unsigned w = []
by (rule bit-list-induct [of - w], simp-all)

lemma bv-to-nat-nzero-imp-nempty:
assumes bv-to-nat w ≠ 0
shows norm-unsigned w ≠ []
proof –
have bv-to-nat w ≠ 0 --> norm-unsigned w ≠ []
by (rule bit-list-induct [of - w], simp-all)
thus ?thesis

..

qed

lemma nat-helper1:
assumes ass: nat-to-bv (bv-to-nat w) = norm-unsigned w
shows nat-to-bv (2 * bv-to-nat w + bitval x) = norm-unsigned (w @ [x])
proof (cases x)
assume [simp]: x = 1
show ?thesis
apply (simp add: nat-to-bv-non0)
apply safe
proof –
fix q
assume Suc (2 * bv-to-nat w) = 2 * q
hence orig: (2 * bv-to-nat w + 1) mod 2 = 2 * q mod 2 (is ?lhs = ?rhs)
by simp

```

have ?lhs = (1 + 2 * bv-to-nat w) mod 2
  by (simp add: add-commute)
also have ... = 1
  by (subst mod-add1-eq) simp
finally have eq1: ?lhs = 1 .
have ?rhs = 0
  by simp
with orig and eq1
show nat-to-bv (Suc (2 * bv-to-nat w) div 2) @ [0] = norm-unsigned (w @ [1])
  by simp
next
  have nat-to-bv (Suc (2 * bv-to-nat w) div 2) @ [1] = nat-to-bv ((1 + 2 *
bv-to-nat w) div 2) @ [1]
    by (simp add: add-commute)
  also have ... = nat-to-bv (bv-to-nat w) @ [1]
    by (subst div-add1-eq, simp)
  also have ... = norm-unsigned w @ [1]
    by (subst ass, rule refl)
  also have ... = norm-unsigned (w @ [1])
    by (cases norm-unsigned w, simp-all)
  finally show nat-to-bv (Suc (2 * bv-to-nat w) div 2) @ [1] = norm-unsigned
(w @ [1])
  .
qed
next
assume [simp]: x = 0
show ?thesis
proof (cases bv-to-nat w = 0)
  assume bv-to-nat w = 0
  thus ?thesis
    by (simp add: bv-to-nat-zero-imp-empty)
next
  assume bv-to-nat w ≠ 0
  thus ?thesis
    apply simp
    apply (subst nat-to-bv-non0)
    apply simp
    apply auto
    apply (subst ass)
    apply (cases norm-unsigned w)
    apply (simp-all add: norm-empty-bv-to-nat-zero)
    done
qed
qed

lemma nat-helper2: nat-to-bv (2 ^ length xs + bv-to-nat xs) = 1 # xs
proof -
  have ∀ xs. nat-to-bv (2 ^ length (rev xs) + bv-to-nat (rev xs)) = 1 # (rev xs)
  (is ∀ xs. ?P xs)

```

```

proof
  fix xs
  show ?P xs
proof (rule length-induct [of - xs])
  fix xs :: bit list
  assume ind:  $\forall ys. \text{length } ys < \text{length } xs \longrightarrow ?P \text{ } ys$ 
  show ?P xs
proof (cases xs)
  assume [simp]: xs = []
  show ?thesis
    by (simp add: nat-to-bv-non0)
next
  fix y ys
  assume [simp]: xs = y # ys
  show ?thesis
    apply simp
    apply (subst bv-to-nat-dist-append)
    apply simp
  proof –
    have nat-to-bv ( $2 * 2^{\text{length } ys} + (\text{bv-to-nat } (\text{rev } ys)) * 2 + \text{bitval } y$ ) =
      nat-to-bv ( $2 * (2^{\text{length } ys} + \text{bv-to-nat } (\text{rev } ys)) + \text{bitval } y$ )
      by (simp add: add-ac mult-ac)
    also have ... = nat-to-bv ( $2 * (\text{bv-to-nat } (1 \# \text{rev } ys)) + \text{bitval } y$ )
      by simp
    also have ... = norm-unsigned ( $1 \# \text{rev } ys$ ) @ [y]
  proof –
    from ind
    have nat-to-bv ( $2^{\text{length } (\text{rev } ys)} + \text{bv-to-nat } (\text{rev } ys)$ ) =  $1 \# \text{rev } ys$ 
      by auto
    hence [simp]: nat-to-bv ( $2^{\text{length } ys} + \text{bv-to-nat } (\text{rev } ys)$ ) =  $1 \# \text{rev } ys$ 
      by simp
    show ?thesis
      apply (subst nat-helper1)
      apply simp-all
      done
    qed
    also have ... =  $(1 \# \text{rev } ys) @ [y]$ 
      by simp
    also have ... =  $1 \# \text{rev } ys @ [y]$ 
      by simp
    finally show nat-to-bv ( $2 * 2^{\text{length } ys} + (\text{bv-to-nat } (\text{rev } ys)) * 2 +$ 
bitval y) =  $1 \# \text{rev } ys @ [y]$ 
    .
  qed
qed
qed
qed
hence nat-to-bv ( $2^{\text{length } (\text{rev } (\text{rev } xs))} + \text{bv-to-nat } (\text{rev } (\text{rev } xs)))$ ) =  $1 \# \text{rev } (\text{rev } xs)$ 

```

..
 thus ?thesis
 by simp
 qed

lemma nat-bv-nat [simp]: nat-to-bv (bv-to-nat w) = norm-unsigned w
 proof (rule bit-list-induct [of - w], simp-all)
 fix xs
 assume nat-to-bv (bv-to-nat xs) = norm-unsigned xs
 have bv-to-nat xs = bv-to-nat (norm-unsigned xs)
 by simp
 have bv-to-nat xs < 2 ^ length xs
 by (rule bv-to-nat-upper-range)
 show nat-to-bv (2 ^ length xs + bv-to-nat xs) = 1 # xs
 by (rule nat-helper2)
 qed

lemma bv-to-nat-qinj:
 assumes one: bv-to-nat xs = bv-to-nat ys
 and len: length xs = length ys
 shows xs = ys
 proof -
 from one
 have nat-to-bv (bv-to-nat xs) = nat-to-bv (bv-to-nat ys)
 by simp
 hence xsys: norm-unsigned xs = norm-unsigned ys
 by simp
 have xs = bv-extend (length xs) 0 (norm-unsigned xs)
 by (simp add: bv-extend-norm-unsigned)
 also have ... = bv-extend (length ys) 0 (norm-unsigned ys)
 by (simp add: xsys len)
 also have ... = ys
 by (simp add: bv-extend-norm-unsigned)
 finally show ?thesis .
 qed

lemma norm-unsigned-nat-to-bv [simp]:
 norm-unsigned (nat-to-bv n) = nat-to-bv n
 proof -
 have norm-unsigned (nat-to-bv n) = nat-to-bv (bv-to-nat (norm-unsigned (nat-to-bv n)))
 by (subst nat-bv-nat, simp)
 also have ... = nat-to-bv n
 by simp
 finally show ?thesis .
 qed

lemma length-nat-to-bv-upper-limit:
 assumes nk: $n \leq 2^k - 1$

```

  shows      length (nat-to-bv n) ≤ k
proof (cases n = 0)
  case True
  thus ?thesis
    by (simp add: nat-to-bv-def nat-to-bv-helper.simps)
next
  case False
  hence n0: 0 < n by simp
  show ?thesis
  proof (rule ccontr)
    assume ~ length (nat-to-bv n) ≤ k
    hence k < length (nat-to-bv n)
      by simp
    hence k ≤ length (nat-to-bv n) - 1
      by arith
    hence (2::nat) ^ k ≤ 2 ^ (length (nat-to-bv n) - 1)
      by simp
    also have ... = 2 ^ (length (norm-unsigned (nat-to-bv n)) - 1)
      by simp
    also have ... ≤ bv-to-nat (nat-to-bv n)
      by (rule bv-to-nat-lower-limit,simp add: n0)
    also have ... = n
      by simp
    finally have 2 ^ k ≤ n .
  with n0
  have 2 ^ k - 1 < n
    by arith
  with nk
  show False
    by simp
qed
qed

```

```

lemma length-nat-to-bv-lower-limit:
  assumes nk: 2 ^ k ≤ n
  shows      k < length (nat-to-bv n)
proof (rule ccontr)
  assume ~ k < length (nat-to-bv n)
  hence lnk: length (nat-to-bv n) ≤ k
    by simp
  have n = bv-to-nat (nat-to-bv n)
    by simp
  also have ... < 2 ^ length (nat-to-bv n)
    by (rule bv-to-nat-upper-range)
  also from lnk have ... ≤ 2 ^ k
    by simp
  finally have n < 2 ^ k .
  with nk
  show False

```

by *simp*
qed

16.4 Unsigned Arithmetic Operations

constdefs

bv-add :: [*bit list*, *bit list*] => *bit list*
bv-add w1 w2 == *nat-to-bv (bv-to-nat w1 + bv-to-nat w2)*

lemma *bv-add-type1* [*simp*]: *bv-add (norm-unsigned w1) w2* = *bv-add w1 w2*
 by (*simp add: bv-add-def*)

lemma *bv-add-type2* [*simp*]: *bv-add w1 (norm-unsigned w2)* = *bv-add w1 w2*
 by (*simp add: bv-add-def*)

lemma *bv-add-returntype* [*simp*]: *norm-unsigned (bv-add w1 w2)* = *bv-add w1 w2*
 by (*simp add: bv-add-def*)

lemma *bv-add-length*: *length (bv-add w1 w2)* ≤ *Suc (max (length w1) (length w2))*

proof (*unfold bv-add-def, rule length-nat-to-bv-upper-limit*)

from *bv-to-nat-upper-range* [*of w1*] and *bv-to-nat-upper-range* [*of w2*]

have *bv-to-nat w1 + bv-to-nat w2* ≤ ($2^{\text{length } w1 - 1}$) + ($2^{\text{length } w2 - 1}$)

by *arith*

also have ... ≤ $\max (2^{\text{length } w1 - 1} (2^{\text{length } w2 - 1}) + \max (2^{\text{length } w1 - 1} (2^{\text{length } w2 - 1}))$

by (*rule add-mono, safe intro!: le-maxI1 le-maxI2*)

also have ... = $2 * \max (2^{\text{length } w1 - 1} (2^{\text{length } w2 - 1}))$

by *simp*

also have ... ≤ $2^{\text{Suc (max (length w1) (length w2))} - 2}$

proof (*cases length w1 ≤ length w2*)

assume *w1w2*: *length w1* ≤ *length w2*

hence $(2::\text{nat})^{\text{length } w1} \leq 2^{\text{length } w2}$

by *simp*

hence $(2::\text{nat})^{\text{length } w1 - 1} \leq 2^{\text{length } w2 - 1}$

by *arith*

with *w1w2* **show** ?thesis

by (*simp add: diff-mult-distrib2 split: split-max*)

next

assume [*simp*]: ~ (*length w1* ≤ *length w2*)

have ~ $((2::\text{nat})^{\text{length } w1 - 1} \leq 2^{\text{length } w2 - 1})$

proof

assume $(2::\text{nat})^{\text{length } w1 - 1} \leq 2^{\text{length } w2 - 1}$

hence $((2::\text{nat})^{\text{length } w1 - 1} + 1) \leq (2^{\text{length } w2 - 1} + 1)$

by (*rule add-right-mono*)

hence $(2::\text{nat})^{\text{length } w1} \leq 2^{\text{length } w2}$

by *simp*

hence *length w1* ≤ *length w2*

by *simp*

thus *False*


```

    by simp
  qed
  thus ?thesis
    by (simp add: diff-mult-distrib2 split: split-max)
  qed
  finally show  $bv\text{-}to\text{-}nat\ w1 + bv\text{-}to\text{-}nat\ w2 \leq 2^{\wedge} Suc\ (max\ (length\ w1)\ (length\ w2)) - 1$ 
    by arith
  qed

constdefs
  bv-mult :: [bit list, bit list] => bit list
  bv-mult w1 w2 == nat-to-bv (bv-to-nat w1 * bv-to-nat w2)

lemma bv-mult-type1 [simp]:  $bv\text{-}mult\ (norm\text{-}unsigned\ w1)\ w2 = bv\text{-}mult\ w1\ w2$ 
  by (simp add: bv-mult-def)

lemma bv-mult-type2 [simp]:  $bv\text{-}mult\ w1\ (norm\text{-}unsigned\ w2) = bv\text{-}mult\ w1\ w2$ 
  by (simp add: bv-mult-def)

lemma bv-mult-returntype [simp]:  $norm\text{-}unsigned\ (bv\text{-}mult\ w1\ w2) = bv\text{-}mult\ w1\ w2$ 
  by (simp add: bv-mult-def)

lemma bv-mult-length:  $length\ (bv\text{-}mult\ w1\ w2) \leq length\ w1 + length\ w2$ 
proof (unfold bv-mult-def, rule length-nat-to-bv-upper-limit)
  from bv-to-nat-upper-range [of w1] and bv-to-nat-upper-range [of w2]
  have h:  $bv\text{-}to\text{-}nat\ w1 \leq 2^{\wedge} length\ w1 - 1 \wedge bv\text{-}to\text{-}nat\ w2 \leq 2^{\wedge} length\ w2 - 1$ 
    by arith
  have  $bv\text{-}to\text{-}nat\ w1 * bv\text{-}to\text{-}nat\ w2 \leq (2^{\wedge} length\ w1 - 1) * (2^{\wedge} length\ w2 - 1)$ 
    apply (cut-tac h)
    apply (rule mult-mono)
    apply auto
  done
  also have  $\dots < 2^{\wedge} length\ w1 * 2^{\wedge} length\ w2$ 
    by (rule mult-strict-mono, auto)
  also have  $\dots = 2^{\wedge} (length\ w1 + length\ w2)$ 
    by (simp add: power-add)
  finally show  $bv\text{-}to\text{-}nat\ w1 * bv\text{-}to\text{-}nat\ w2 \leq 2^{\wedge} (length\ w1 + length\ w2) - 1$ 
    by arith
qed

```

16.5 Signed Vectors

```

consts
  norm-signed :: bit list => bit list

primrec
  norm-signed-Nil:  $norm\text{-}signed\ [] = []$ 

```

norm-signed-Cons: $\text{norm-signed } (b\#bs) = (\text{case } b \text{ of } \mathbf{0} \Rightarrow \text{if norm-unsigned } bs = [] \text{ then } [] \text{ else } b\#\text{norm-unsigned } bs \mid \mathbf{1} \Rightarrow b\#\text{rem-initial } b \text{ } bs)$

lemma *norm-signed0* [simp]: $\text{norm-signed } [\mathbf{0}] = []$
by *simp*

lemma *norm-signed1* [simp]: $\text{norm-signed } [\mathbf{1}] = [\mathbf{1}]$
by *simp*

lemma *norm-signed01* [simp]: $\text{norm-signed } (\mathbf{0}\#\mathbf{1}\#xs) = \mathbf{0}\#\mathbf{1}\#xs$
by *simp*

lemma *norm-signed00* [simp]: $\text{norm-signed } (\mathbf{0}\#\mathbf{0}\#xs) = \text{norm-signed } (\mathbf{0}\#xs)$
by *simp*

lemma *norm-signed10* [simp]: $\text{norm-signed } (\mathbf{1}\#\mathbf{0}\#xs) = \mathbf{1}\#\mathbf{0}\#xs$
by *simp*

lemma *norm-signed11* [simp]: $\text{norm-signed } (\mathbf{1}\#\mathbf{1}\#xs) = \text{norm-signed } (\mathbf{1}\#xs)$
by *simp*

lemmas [simp del] = *norm-signed-Cons*

constdefs

int-to-bv :: $\text{int} \Rightarrow \text{bit list}$

int-to-bv $n == \text{if } 0 \leq n$

$\text{then norm-signed } (\mathbf{0}\#\text{nat-to-bv } (\text{nat } n))$

$\text{else norm-signed } (\text{bv-not } (\mathbf{0}\#\text{nat-to-bv } (\text{nat } (-n - 1))))$

lemma *int-to-bv-ge0* [simp]: $0 \leq n \Rightarrow \text{int-to-bv } n = \text{norm-signed } (\mathbf{0}\#\text{nat-to-bv } (\text{nat } n))$
by (*simp add: int-to-bv-def*)

lemma *int-to-bv-lt0* [simp]: $n < 0 \Rightarrow \text{int-to-bv } n = \text{norm-signed } (\text{bv-not } (\mathbf{0}\#\text{nat-to-bv } (\text{nat } (-n - 1))))$
by (*simp add: int-to-bv-def*)

lemma *norm-signed-idem* [simp]: $\text{norm-signed } (\text{norm-signed } w) = \text{norm-signed } w$
proof (*rule bit-list-induct [of - w], simp-all*)

fix xs

assume $\text{norm-signed } (\text{norm-signed } xs) = \text{norm-signed } xs$

show $\text{norm-signed } (\text{norm-signed } (\mathbf{0}\#xs)) = \text{norm-signed } (\mathbf{0}\#xs)$

proof (*rule bit-list-cases [of xs], simp-all*)

fix ys

assume [*symmetric, simp*]: $xs = \mathbf{0}\#ys$

show $\text{norm-signed } (\text{norm-signed } (\mathbf{0}\#ys)) = \text{norm-signed } (\mathbf{0}\#ys)$

by *simp*

qed

next

```

fix xs
assume norm-signed (norm-signed xs) = norm-signed xs
show norm-signed (norm-signed (1#xs)) = norm-signed (1#xs)
proof (rule bit-list-cases [of xs],simp-all)
  fix ys
  assume [symmetric, simp]: xs = 1#ys
  show norm-signed (norm-signed (1#ys)) = norm-signed (1#ys)
    by simp
  qed
qed

constdefs
  bv-to-int :: bit list => int
  bv-to-int w == case bv-msb w of 0 => int (bv-to-nat w) | 1 => - int (bv-to-nat
(bv-not w) + 1)

lemma bv-to-int-Nil [simp]: bv-to-int [] = 0
  by (simp add: bv-to-int-def)

lemma bv-to-int-Cons0 [simp]: bv-to-int (0#bs) = int (bv-to-nat bs)
  by (simp add: bv-to-int-def)

lemma bv-to-int-Cons1 [simp]: bv-to-int (1#bs) = - int (bv-to-nat (bv-not bs) +
1)
  by (simp add: bv-to-int-def)

lemma bv-to-int-type [simp]: bv-to-int (norm-signed w) = bv-to-int w
proof (rule bit-list-induct [of - w],simp-all)
  fix xs
  assume ind: bv-to-int (norm-signed xs) = bv-to-int xs
  show bv-to-int (norm-signed (0#xs)) = int (bv-to-nat xs)
  proof (rule bit-list-cases [of xs],simp-all)
    fix ys
    assume [simp]: xs = 0#ys
    from ind
    show bv-to-int (norm-signed (0#ys)) = int (bv-to-nat ys)
      by simp
    qed
  next
  fix xs
  assume ind: bv-to-int (norm-signed xs) = bv-to-int xs
  show bv-to-int (norm-signed (1#xs)) = -1 - int (bv-to-nat (bv-not xs))
  proof (rule bit-list-cases [of xs],simp-all)
    fix ys
    assume [simp]: xs = 1#ys
    from ind
    show bv-to-int (norm-signed (1#ys)) = -1 - int (bv-to-nat (bv-not ys))
      by simp
    qed

```

qed

lemma *bv-to-int-upper-range*: $bv\text{-}to\text{-}int\ w < 2^{\wedge} (length\ w - 1)$

proof (rule *bit-list-cases* [of *w*], *simp-all*)

fix *bs*

from *bv-to-nat-upper-range*

show $int\ (bv\text{-}to\text{-}nat\ bs) < 2^{\wedge} length\ bs$

by (*simp add: int-nat-two-exp*)

next

fix *bs*

have $-1 - int\ (bv\text{-}to\text{-}nat\ (bv\text{-}not\ bs)) \leq 0$

by *simp*

also have $\dots < 2^{\wedge} length\ bs$

by (*induct bs, simp-all*)

finally show $-1 - int\ (bv\text{-}to\text{-}nat\ (bv\text{-}not\ bs)) < 2^{\wedge} length\ bs$

.

qed

lemma *bv-to-int-lower-range*: $-(2^{\wedge} (length\ w - 1)) \leq bv\text{-}to\text{-}int\ w$

proof (rule *bit-list-cases* [of *w*], *simp-all*)

fix *bs* :: *bit list*

have $-(2^{\wedge} length\ bs) \leq (0::int)$

by (*induct bs, simp-all*)

also have $\dots \leq int\ (bv\text{-}to\text{-}nat\ bs)$

by *simp*

finally show $-(2^{\wedge} length\ bs) \leq int\ (bv\text{-}to\text{-}nat\ bs)$

.

next

fix *bs*

from *bv-to-nat-upper-range* [of *bv-not bs*]

show $-(2^{\wedge} length\ bs) \leq -1 - int\ (bv\text{-}to\text{-}nat\ (bv\text{-}not\ bs))$

by (*simp add: int-nat-two-exp*)

qed

lemma *int-bv-int* [*simp*]: $int\text{-}to\text{-}bv\ (bv\text{-}to\text{-}int\ w) = norm\text{-}signed\ w$

proof (rule *bit-list-cases* [of *w*], *simp*)

fix *xs*

assume [*simp*]: $w = 0\#xs$

show ?thesis

apply *simp*

apply (*subst norm-signed-Cons* [of $0\ xs$])

apply *simp*

using *norm-unsigned-result* [of *xs*]

apply *safe*

apply (*rule bit-list-cases* [of *norm-unsigned xs*])

apply *simp-all*

done

next

fix *xs*

```

assume [simp]:  $w = 1\#xs$ 
show ?thesis
  apply (simp del: int-to-bv-lt0)
  apply (rule bit-list-induct [of - xs])
  apply simp
  apply (subst int-to-bv-lt0)
  apply (subgoal-tac - int (bv-to-nat (bv-not (0 # bs))) + -1 < 0 + 0)
  apply simp
  apply (rule add-le-less-mono)
  apply simp
  apply simp
  apply (simp del: bv-to-nat1 bv-to-nat-helper)
  apply simp
  done
qed

lemma bv-int-bv [simp]:  $bv\text{-}to\text{-}int\ (int\text{-}to\text{-}bv\ i) = i$ 
  by (cases 0 ≤ i, simp-all)

lemma bv-msb-norm [simp]:  $bv\text{-}msb\ (norm\text{-}signed\ w) = bv\text{-}msb\ w$ 
  by (rule bit-list-cases [of w], simp-all add: norm-signed-Cons)

lemma norm-signed-length:  $length\ (norm\text{-}signed\ w) \leq length\ w$ 
  apply (cases w, simp-all)
  apply (subst norm-signed-Cons)
  apply (case-tac a, simp-all)
  apply (rule rem-initial-length)
  done

lemma norm-signed-equal:  $length\ (norm\text{-}signed\ w) = length\ w \implies norm\text{-}signed\ w = w$ 
proof (rule bit-list-cases [of w], simp-all)
  fix xs
  assume  $length\ (norm\text{-}signed\ (0\#xs)) = Suc\ (length\ xs)$ 
  thus  $norm\text{-}signed\ (0\#xs) = 0\#xs$ 
    apply (simp add: norm-signed-Cons)
    apply safe
    apply simp-all
    apply (rule norm-unsigned-equal)
    apply assumption
    done
next
  fix xs
  assume  $length\ (norm\text{-}signed\ (1\#xs)) = Suc\ (length\ xs)$ 
  thus  $norm\text{-}signed\ (1\#xs) = 1\#xs$ 
    apply (simp add: norm-signed-Cons)
    apply (rule rem-initial-equal)
    apply assumption
    done

```

qed

lemma *bv-extend-norm-signed*: $bv_msb\ w = b \implies bv_extend\ (length\ w)\ b\ (norm_signed\ w) = w$

proof (rule *bit-list-cases* [of *w*], *simp-all*)

fix *xs*

show $bv_extend\ (Suc\ (length\ xs))\ 0\ (norm_signed\ (0\#xs)) = 0\#xs$

proof (*simp add: norm-signed-list-def, auto*)

assume $norm_unsigned\ xs = []$

hence $xs: rem_initial\ 0\ xs = []$

by (*simp add: norm-unsigned-def*)

have $bv_extend\ (Suc\ (length\ xs))\ 0\ (0\#rem_initial\ 0\ xs) = 0\#xs$

apply (*simp add: bv-extend-def replicate-app-Cons-same*)

apply (*fold bv-extend-def*)

apply (rule *bv-extend-rem-initial*)

done

thus $bv_extend\ (Suc\ (length\ xs))\ 0\ [0] = 0\#xs$

by (*simp add: xs*)

next

show $bv_extend\ (Suc\ (length\ xs))\ 0\ (0\#norm_unsigned\ xs) = 0\#xs$

apply (*simp add: norm-unsigned-def*)

apply (*simp add: bv-extend-def replicate-app-Cons-same*)

apply (*fold bv-extend-def*)

apply (rule *bv-extend-rem-initial*)

done

qed

next

fix *xs*

show $bv_extend\ (Suc\ (length\ xs))\ 1\ (norm_signed\ (1\#xs)) = 1\#xs$

apply (*simp add: norm-signed-Cons*)

apply (*simp add: bv-extend-def replicate-app-Cons-same*)

apply (*fold bv-extend-def*)

apply (rule *bv-extend-rem-initial*)

done

qed

lemma *bv-to-int-qinj*:

assumes *one*: $bv_to_int\ xs = bv_to_int\ ys$

and *len*: $length\ xs = length\ ys$

shows $xs = ys$

proof –

from *one*

have $int_to_bv\ (bv_to_int\ xs) = int_to_bv\ (bv_to_int\ ys)$

by *simp*

hence $xs: norm_signed\ xs = norm_signed\ ys$

by *simp*

hence $xs: bv_msb\ xs = bv_msb\ ys$

proof –

have $bv_msb\ xs = bv_msb\ (norm_signed\ xs)$

```

    by simp
  also have ... = bv-msb (norm-signed ys)
    by (simp add: xsys)
  also have ... = bv-msb ys
    by simp
  finally show ?thesis .
qed
have xs = bv-extend (length xs) (bv-msb xs) (norm-signed xs)
  by (simp add: bv-extend-norm-signed)
also have ... = bv-extend (length ys) (bv-msb ys) (norm-signed ys)
  by (simp add: xsys xsys' len)
also have ... = ys
  by (simp add: bv-extend-norm-signed)
finally show ?thesis .
qed

lemma int-to-bv-returntype [simp]: norm-signed (int-to-bv w) = int-to-bv w
  by (simp add: int-to-bv-def)

lemma bv-to-int-msb0: 0 ≤ bv-to-int w1 ==> bv-msb w1 = 0
  by (rule bit-list-cases,simp-all)

lemma bv-to-int-msb1: bv-to-int w1 < 0 ==> bv-msb w1 = 1
  by (rule bit-list-cases,simp-all)

lemma bv-to-int-lower-limit-gt0:
  assumes w0: 0 < bv-to-int w
  shows      2 ^ (length (norm-signed w) - 2) ≤ bv-to-int w
proof -
  from w0
  have 0 ≤ bv-to-int w
    by simp
  hence [simp]: bv-msb w = 0
    by (rule bv-to-int-msb0)
  have 2 ^ (length (norm-signed w) - 2) ≤ bv-to-int (norm-signed w)
  proof (rule bit-list-cases [of w])
    assume w = []
    with w0
    show ?thesis
      by simp
  next
    fix w'
    assume weq: w = 0 # w'
    thus ?thesis
    proof (simp add: norm-signed-Cons,safe)
      assume norm-unsigned w' = []
      with weq and w0
      show False
        by (simp add: norm-empty-bv-to-nat-zero)
    qed
  qed

```

```

next
  assume w'0: norm-unsigned w' ≠ []
  have 0 < bv-to-nat w'
  proof (rule ccontr)
    assume ~ (0 < bv-to-nat w')
    hence bv-to-nat w' = 0
    by arith
    hence norm-unsigned w' = []
    by (simp add: bv-to-nat-zero-imp-empty)
  with w'0
  show False
  by simp
qed
with bv-to-nat-lower-limit [of w']
show 2 ^ (length (norm-unsigned w') - Suc 0) ≤ int (bv-to-nat w')
  by (simp add: int-nat-two-exp)
qed
next
fix w'
assume w = 1 # w'
from w0
have bv-msb w = 0
  by simp
with prems
show ?thesis
  by simp
qed
also have ... = bv-to-int w
  by simp
finally show ?thesis .
qed

lemma norm-signed-result: norm-signed w = [] ∨ norm-signed w = [1] ∨ bv-msb
(norm-signed w) ≠ bv-msb (tl (norm-signed w))
  apply (rule bit-list-cases [of w], simp-all)
  apply (case-tac bs, simp-all)
  apply (case-tac a, simp-all)
  apply (simp add: norm-signed-Cons)
  apply safe
  apply simp
proof -
fix l
assume msb: 0 = bv-msb (norm-unsigned l)
assume norm-unsigned l ≠ []
with norm-unsigned-result [of l]
have bv-msb (norm-unsigned l) = 1
  by simp
with msb
show False

```



```

    by simp
next
  fix xs
  assume p: 1 = bv-msb (tl (norm-signed (1 # xs)))
  have 1 ≠ bv-msb (tl (norm-signed (1 # xs)))
    by (rule bit-list-induct [of - xs], simp-all)
  with p
  show False
    by simp
qed

lemma bv-to-int-upper-limit-lem1:
  assumes w0: bv-to-int w < -1
  shows      bv-to-int w < - (2 ^ (length (norm-signed w) - 2))
proof -
  from w0
  have bv-to-int w < 0
    by simp
  hence msbw [simp]: bv-msb w = 1
    by (rule bv-to-int-msb1)
  have bv-to-int w = bv-to-int (norm-signed w)
    by simp
  also from norm-signed-result [of w]
  have ... < - (2 ^ (length (norm-signed w) - 2))
  proof (safe)
    assume norm-signed w = []
    hence bv-to-int (norm-signed w) = 0
      by simp
    with w0
    show ?thesis
      by simp
  next
    assume norm-signed w = [1]
    hence bv-to-int (norm-signed w) = -1
      by simp
    with w0
    show ?thesis
      by simp
  next
    assume bv-msb (norm-signed w) ≠ bv-msb (tl (norm-signed w))
    hence msb-tl: 1 ≠ bv-msb (tl (norm-signed w))
      by simp
    show bv-to-int (norm-signed w) < - (2 ^ (length (norm-signed w) - 2))
  proof (rule bit-list-cases [of norm-signed w])
    assume norm-signed w = []
    hence bv-to-int (norm-signed w) = 0
      by simp
    with w0
    show ?thesis

```

```

      by simp
    next
      fix w'
      assume nw: norm-signed w = 0 # w'
      from msbw
      have bv-msb (norm-signed w) = 1
        by simp
      with nw
      show ?thesis
        by simp
    next
      fix w'
      assume weq: norm-signed w = 1 # w'
      show ?thesis
      proof (rule bit-list-cases [of w'])
        assume w'eq: w' = []
        from w0
        have bv-to-int (norm-signed w) < -1
          by simp
        with w'eq and weq
        show ?thesis
          by simp
      next
        fix w''
        assume w'eq: w' = 0 # w''
        show ?thesis
          apply (simp add: weq w'eq)
          apply (subgoal-tac - int (bv-to-nat (bv-not w'')) + -1 < 0 + 0)
          apply (simp add: int-nat-two-exp)
          apply (rule add-le-less-mono)
          apply simp-all
          done
      next
        fix w''
        assume w'eq: w' = 1 # w''
        with weq and msb-tl
        show ?thesis
          by simp
      qed
    qed
  qed
  finally show ?thesis .
qed

lemma length-int-to-bv-upper-limit-gt0:
  assumes w0: 0 < i
  and wk: i ≤ 2 ^ (k - 1) - 1
  shows length (int-to-bv i) ≤ k
  proof (rule ccontr)

```

```

from  $w0\ wk$ 
have  $k1: 1 < k$ 
  by ( $cases\ k - 1, simp-all, arith$ )
assume  $\sim length\ (int-to-bv\ i) \leq k$ 
hence  $k < length\ (int-to-bv\ i)$ 
  by  $simp$ 
hence  $k \leq length\ (int-to-bv\ i) - 1$ 
  by  $arith$ 
hence  $a: k - 1 \leq length\ (int-to-bv\ i) - 2$ 
  by  $arith$ 
hence  $(2::int) \wedge (k - 1) \leq 2 \wedge (length\ (int-to-bv\ i) - 2)$  by  $simp$ 
also have  $\dots \leq i$ 
proof –
  have  $2 \wedge (length\ (norm-signed\ (int-to-bv\ i)) - 2) \leq bv-to-int\ (int-to-bv\ i)$ 
  proof ( $rule\ bv-to-int-lower-limit-gt0$ )
    from  $w0$ 
    show  $0 < bv-to-int\ (int-to-bv\ i)$ 
    by  $simp$ 
  qed
  thus  $?thesis$ 
  by  $simp$ 
qed
finally have  $2 \wedge (k - 1) \leq i$  .
with  $wk$ 
show  $False$ 
  by  $simp$ 
qed

```

```

lemma  $pos-length-pos$ :
  assumes  $i0: 0 < bv-to-int\ w$ 
  shows  $0 < length\ w$ 
proof –
  from  $norm-signed-result\ [of\ w]$ 
  have  $0 < length\ (norm-signed\ w)$ 
  proof ( $auto$ )
    assume  $ii: norm-signed\ w = []$ 
    have  $bv-to-int\ (norm-signed\ w) = 0$ 
    by ( $subst\ ii, simp$ )
    hence  $bv-to-int\ w = 0$ 
    by  $simp$ 
  with  $i0$ 
  show  $False$ 
  by  $simp$ 
next
  assume  $ii: norm-signed\ w = []$ 
  assume  $jj: bv-msb\ w \neq 0$ 
  have  $0 = bv-msb\ (norm-signed\ w)$ 
  by ( $subst\ ii, simp$ )
  also have  $\dots \neq 0$ 

```

```

      by (simp add: jj)
    finally show False by simp
  qed
  also have ... ≤ length w
    by (rule norm-signed-length)
  finally show ?thesis
.
qed

lemma neg-length-pos:
  assumes i0: bv-to-int w < -1
  shows      0 < length w
proof -
  from norm-signed-result [of w]
  have 0 < length (norm-signed w)
  proof (auto)
    assume ii: norm-signed w = []
    have bv-to-int (norm-signed w) = 0
      by (subst ii,simp)
    hence bv-to-int w = 0
      by simp
    with i0
    show False
      by simp
  next
    assume ii: norm-signed w = []
    assume jj: bv-msb w ≠ 0
    have 0 = bv-msb (norm-signed w)
      by (subst ii,simp)
    also have ... ≠ 0
      by (simp add: jj)
    finally show False by simp
  qed
  also have ... ≤ length w
    by (rule norm-signed-length)
  finally show ?thesis
.
qed

lemma length-int-to-bv-lower-limit-gt0:
  assumes wk: 2 ^ (k - 1) ≤ i
  shows      k < length (int-to-bv i)
proof (rule ccontr)
  have 0 < (2::int) ^ (k - 1)
    by (rule zero-less-power,simp)
  also have ... ≤ i
    by (rule wk)
  finally have i0: 0 < i
.

```

```

have lii0: 0 < length (int-to-bv i)
  apply (rule pos-length-pos)
  apply (simp,rule i0)
done
assume ~ k < length (int-to-bv i)
hence length (int-to-bv i) ≤ k
  by simp
with lii0
have a: length (int-to-bv i) - 1 ≤ k - 1
  by arith
have i < 2 ^ (length (int-to-bv i) - 1)
proof -
  have i = bv-to-int (int-to-bv i)
    by simp
  also have ... < 2 ^ (length (int-to-bv i) - 1)
    by (rule bv-to-int-upper-range)
  finally show ?thesis .
qed
also have (2::int) ^ (length (int-to-bv i) - 1) ≤ 2 ^ (k - 1) using a
  by simp
finally have i < 2 ^ (k - 1) .
with wk
show False
  by simp
qed

```

```

lemma length-int-to-bv-upper-limit-lem1:
  assumes w1: i < -1
  and wk: - (2 ^ (k - 1)) ≤ i
  shows length (int-to-bv i) ≤ k
proof (rule ccontr)
  from w1 wk
  have k1: 1 < k
    by (cases k - 1, simp-all, arith)
  assume ~ length (int-to-bv i) ≤ k
  hence k < length (int-to-bv i)
    by simp
  hence k ≤ length (int-to-bv i) - 1
    by arith
  hence a: k - 1 ≤ length (int-to-bv i) - 2
    by arith
  have i < - (2 ^ (length (int-to-bv i) - 2))
  proof -
    have i = bv-to-int (int-to-bv i)
      by simp
    also have ... < - (2 ^ (length (norm-signed (int-to-bv i)) - 2))
      by (rule bv-to-int-upper-limit-lem1, simp, rule w1)
    finally show ?thesis by simp
  qed
qed

```

```

also have ...  $\leq -(2 \wedge (k - 1))$ 
proof -
  have  $(2::int) \wedge (k - 1) \leq 2 \wedge (\text{length } (\text{int-to-bv } i) - 2)$  using a
  by simp
  thus ?thesis
  by simp
qed
finally have  $i < -(2 \wedge (k - 1))$  .
with wk
show False
by simp
qed

```

```

lemma length-int-to-bv-lower-limit-lem1:
  assumes wk:  $i < -(2 \wedge (k - 1))$ 
  shows  $k < \text{length } (\text{int-to-bv } i)$ 
proof (rule ccontr)
  from wk
  have  $i \leq -(2 \wedge (k - 1)) - 1$ 
  by simp
  also have ...  $< -1$ 
  proof -
    have  $0 < (2::int) \wedge (k - 1)$ 
    by (rule zero-less-power,simp)
    hence  $-((2::int) \wedge (k - 1)) < 0$ 
    by simp
    thus ?thesis by simp
  qed
  finally have i1:  $i < -1$  .
  have lli0:  $0 < \text{length } (\text{int-to-bv } i)$ 
  apply (rule neg-length-pos)
  apply (simp,rule i1)
  done
  assume  $\sim k < \text{length } (\text{int-to-bv } i)$ 
  hence  $\text{length } (\text{int-to-bv } i) \leq k$ 
  by simp
  with lli0
  have a:  $\text{length } (\text{int-to-bv } i) - 1 \leq k - 1$ 
  by arith
  hence  $(2::int) \wedge (\text{length } (\text{int-to-bv } i) - 1) \leq 2 \wedge (k - 1)$  by simp
  hence  $-((2::int) \wedge (k - 1)) \leq -(2 \wedge (\text{length } (\text{int-to-bv } i) - 1))$ 
  by simp
  also have ...  $\leq i$ 
  proof -
    have  $-(2 \wedge (\text{length } (\text{int-to-bv } i) - 1)) \leq \text{bv-to-int } (\text{int-to-bv } i)$ 
    by (rule bv-to-int-lower-range)
    also have ...  $= i$ 
    by simp
    finally show ?thesis .
  qed

```

```

qed
finally have  $-(2^k - 1) \leq i$  .
with  $wk$ 
show False
  by simp
qed

```

16.6 Signed Arithmetic Operations

16.6.1 Conversion from unsigned to signed

constdefs

```

utos :: bit list => bit list
utos w == norm-signed (0 # w)

```

lemma *utos-type* [*simp*]: $utos (norm-unsigned w) = utos w$
by (*simp add: utos-def norm-signed-Cons*)

lemma *utos-returntype* [*simp*]: $norm-signed (utos w) = utos w$
by (*simp add: utos-def*)

lemma *utos-length*: $length (utos w) \leq Suc (length w)$
by (*simp add: utos-def norm-signed-Cons*)

lemma *bv-to-int-utos*: $bv-to-int (utos w) = int (bv-to-nat w)$

proof (*simp add: utos-def norm-signed-Cons, safe*)

```

  assume  $norm-unsigned w = []$ 
  hence  $bv-to-nat (norm-unsigned w) = 0$ 
    by simp
  thus  $bv-to-nat w = 0$ 
    by simp

```

qed

16.6.2 Unary minus

constdefs

```

bv-uminus :: bit list => bit list
bv-uminus w == int-to-bv (- bv-to-int w)

```

lemma *bv-uminus-type* [*simp*]: $bv-uminus (norm-signed w) = bv-uminus w$
by (*simp add: bv-uminus-def*)

lemma *bv-uminus-returntype* [*simp*]: $norm-signed (bv-uminus w) = bv-uminus w$
by (*simp add: bv-uminus-def*)

lemma *bv-uminus-length*: $length (bv-uminus w) \leq Suc (length w)$

proof –

```

  have  $1 < -bv-to-int w \vee -bv-to-int w = 1 \vee -bv-to-int w = 0 \vee -bv-to-int w$ 
     $= -1 \vee -bv-to-int w < -1$ 
    by arith

```

```

thus ?thesis
proof safe
  assume p:  $1 < -\text{bv-to-int } w$ 
  have lw:  $0 < \text{length } w$ 
  apply (rule neg-length-pos)
  using p
  apply simp
  done
show ?thesis
proof (simp add: bv-uminus-def, rule length-int-to-bv-upper-limit-gt0, simp-all)
  from prems
  show  $\text{bv-to-int } w < 0$ 
    by simp
next
  have  $-(2^{(\text{length } w - 1)}) \leq \text{bv-to-int } w$ 
    by (rule bv-to-int-lower-range)
  hence  $-\text{bv-to-int } w \leq 2^{(\text{length } w - 1)}$ 
    by simp
  also from lw have  $\dots < 2^{\text{length } w}$ 
    by simp
  finally show  $-\text{bv-to-int } w < 2^{\text{length } w}$ 
    by simp
qed
next
  assume p:  $-\text{bv-to-int } w = 1$ 
  hence lw:  $0 < \text{length } w$ 
    by (cases w, simp-all)
  from p
  show ?thesis
    apply (simp add: bv-uminus-def)
    using lw
    apply (simp (no-asm) add: nat-to-bv-non0)
    done
next
  assume  $-\text{bv-to-int } w = 0$ 
  thus ?thesis
    by (simp add: bv-uminus-def)
next
  assume p:  $-\text{bv-to-int } w = -1$ 
  thus ?thesis
    by (simp add: bv-uminus-def)
next
  assume p:  $-\text{bv-to-int } w < -1$ 
  show ?thesis
    apply (simp add: bv-uminus-def)
    apply (rule length-int-to-bv-upper-limit-lem1)
    apply (rule p)
    apply simp
proof -

```



```

    have  $bv\text{-}to\text{-}int\ w < 2^{\wedge} (length\ w - 1)$ 
      by (rule bv-to-int-upper-range)
    also have  $\dots \leq 2^{\wedge} length\ w$  by simp
    finally show  $bv\text{-}to\text{-}int\ w \leq 2^{\wedge} length\ w$ 
      by simp
  qed
qed
qed

```

lemma *bv-uminus-length-utos*: $length\ (bv\text{-}uminus\ (utos\ w)) \leq Suc\ (length\ w)$

proof –

```

  have  $-bv\text{-}to\text{-}int\ (utos\ w) = 0 \vee -bv\text{-}to\text{-}int\ (utos\ w) = -1 \vee -bv\text{-}to\text{-}int\ (utos\ w) < -1$ 

```

```

  apply (simp add: bv-to-int-utos)

```

```

  by arith

```

```

  thus ?thesis

```

proof *safe*

```

  assume  $-bv\text{-}to\text{-}int\ (utos\ w) = 0$ 

```

```

  thus ?thesis

```

```

    by (simp add: bv-uminus-def)

```

next

```

  assume  $-bv\text{-}to\text{-}int\ (utos\ w) = -1$ 

```

```

  thus ?thesis

```

```

    by (simp add: bv-uminus-def)

```

next

```

  assume  $p: -bv\text{-}to\text{-}int\ (utos\ w) < -1$ 

```

```

  show ?thesis

```

```

  apply (simp add: bv-uminus-def)

```

```

  apply (rule length-int-to-bv-upper-limit-lem1)

```

```

  apply (rule  $p$ )

```

```

  apply (simp add: bv-to-int-utos)

```

```

  using bv-to-nat-upper-range [of  $w$ ]

```

```

  apply (simp add: int-nat-two-exp)

```

```

  done

```

qed

qed

constdefs

```

  bv-sadd :: [bit list, bit list] => bit list

```

```

  bv-sadd  $w1\ w2 == int\text{-}to\text{-}bv\ (bv\text{-}to\text{-}int\ w1 + bv\text{-}to\text{-}int\ w2)$ 

```

lemma *bv-sadd-type1* [*simp*]: $bv\text{-}sadd\ (norm\text{-}signed\ w1)\ w2 = bv\text{-}sadd\ w1\ w2$

```

  by (simp add: bv-sadd-def)

```

lemma *bv-sadd-type2* [*simp*]: $bv\text{-}sadd\ w1\ (norm\text{-}signed\ w2) = bv\text{-}sadd\ w1\ w2$

```

  by (simp add: bv-sadd-def)

```

lemma *bv-sadd-returntype* [*simp*]: $norm\text{-}signed\ (bv\text{-}sadd\ w1\ w2) = bv\text{-}sadd\ w1\ w2$

```

  by (simp add: bv-sadd-def)

```

lemma *adder-helper*:

assumes *lw*: $0 < \max (\text{length } w1) (\text{length } w2)$

shows $((2::\text{int}) ^ (\text{length } w1 - 1)) + (2 ^ (\text{length } w2 - 1)) \leq 2 ^ \max (\text{length } w1) (\text{length } w2)$

proof –

have $((2::\text{int}) ^ (\text{length } w1 - 1)) + (2 ^ (\text{length } w2 - 1)) \leq 2 ^ (\max (\text{length } w1) (\text{length } w2) - 1) + 2 ^ (\max (\text{length } w1) (\text{length } w2) - 1)$

apply (*cases length w1 ≤ length w2*)

apply (*auto simp add: max-def*)

apply *arith*

apply *arith*

done

also have $\dots = 2 ^ \max (\text{length } w1) (\text{length } w2)$

proof –

from *lw*

show *?thesis*

apply *simp*

apply (*subst power-Suc [symmetric]*)

apply (*simp del: power.simps*)

done

qed

finally show *?thesis* .

qed

lemma *bv-sadd-length*: $\text{length } (\text{bv-sadd } w1 \ w2) \leq \text{Suc } (\max (\text{length } w1) (\text{length } w2))$

proof –

let *?Q* = *bv-to-int w1 + bv-to-int w2*

have *helper*: *?Q* ≠ 0 ==> $0 < \max (\text{length } w1) (\text{length } w2)$

proof –

assume *p*: *?Q* ≠ 0

show $0 < \max (\text{length } w1) (\text{length } w2)$

proof (*simp add: less-max-iff-disj, rule*)

assume [*simp*]: *w1* = []

show *w2* ≠ []

proof (*rule ccontr, simp*)

assume [*simp*]: *w2* = []

from *p*

show *False*

by *simp*

qed

qed

qed

have $0 < ?Q \vee ?Q = 0 \vee ?Q = -1 \vee ?Q < -1$

by *arith*

thus *?thesis*

```

proof safe
  assume ?Q = 0
  thus ?thesis
    by (simp add: bv-sadd-def)
next
  assume ?Q = -1
  thus ?thesis
    by (simp add: bv-sadd-def)
next
  assume p: 0 < ?Q
  show ?thesis
    apply (simp add: bv-sadd-def)
    apply (rule length-int-to-bv-upper-limit-gt0)
    apply (rule p)
  proof simp
    from bv-to-int-upper-range [of w2]
    have bv-to-int w2 ≤ 2 ^ (length w2 - 1)
      by simp
    with bv-to-int-upper-range [of w1]
    have bv-to-int w1 + bv-to-int w2 < (2 ^ (length w1 - 1)) + (2 ^ (length w2
- 1))
      by (rule zadd-zless-mono)
    also have ... ≤ 2 ^ max (length w1) (length w2)
      apply (rule adder-helper)
      apply (rule helper)
      using p
      apply simp
    done
    finally show ?Q < 2 ^ max (length w1) (length w2)
      .
  qed
next
  assume p: ?Q < -1
  show ?thesis
    apply (simp add: bv-sadd-def)
    apply (rule length-int-to-bv-upper-limit-lem1,simp-all)
    apply (rule p)
  proof -
    have (2 ^ (length w1 - 1)) + 2 ^ (length w2 - 1) ≤ (2::int) ^ max (length
w1) (length w2)
      apply (rule adder-helper)
      apply (rule helper)
      using p
      apply simp
    done
    hence -((2::int) ^ max (length w1) (length w2)) ≤ -(2 ^ (length w1 - 1))
+ -(2 ^ (length w2 - 1))
      by simp
    also have -(2 ^ (length w1 - 1)) + -(2 ^ (length w2 - 1)) ≤ ?Q

```

```

    apply (rule add-mono)
    apply (rule bv-to-int-lower-range [of w1])
    apply (rule bv-to-int-lower-range [of w2])
  done
  finally show  $-(2^{\max (\text{length } w1) (\text{length } w2)}) \leq ?Q$  .
qed
qed
qed

constdefs
  bv-sub :: [bit list, bit list] => bit list
  bv-sub w1 w2 == bv-sadd w1 (bv-uminus w2)

lemma bv-sub-type1 [simp]: bv-sub (norm-signed w1) w2 = bv-sub w1 w2
  by (simp add: bv-sub-def)

lemma bv-sub-type2 [simp]: bv-sub w1 (norm-signed w2) = bv-sub w1 w2
  by (simp add: bv-sub-def)

lemma bv-sub-returntype [simp]: norm-signed (bv-sub w1 w2) = bv-sub w1 w2
  by (simp add: bv-sub-def)

lemma bv-sub-length: length (bv-sub w1 w2) ≤ Suc (max (length w1) (length w2))
proof (cases bv-to-int w2 = 0)
  assume p: bv-to-int w2 = 0
  show ?thesis
  proof (simp add: bv-sub-def bv-sadd-def bv-uminus-def p)
    have length (norm-signed w1) ≤ length w1
      by (rule norm-signed-length)
    also have ... ≤ max (length w1) (length w2)
      by (rule le-maxI1)
    also have ... ≤ Suc (max (length w1) (length w2))
      by arith
    finally show length (norm-signed w1) ≤ Suc (max (length w1) (length w2))
      .
  qed
next
  assume bv-to-int w2 ≠ 0
  hence 0 < length w2
  by (cases w2, simp-all)
  hence lmw: 0 < max (length w1) (length w2)
  by arith

  let ?Q = bv-to-int w1 - bv-to-int w2

  have 0 < ?Q ∨ ?Q = 0 ∨ ?Q = -1 ∨ ?Q < -1
    by arith
  thus ?thesis
  proof safe

```

```

    assume ?Q = 0
    thus ?thesis
      by (simp add: bv-sub-def bv-sadd-def bv-uminus-def)
next
    assume ?Q = -1
    thus ?thesis
      by (simp add: bv-sub-def bv-sadd-def bv-uminus-def)
next
    assume p: 0 < ?Q
    show ?thesis
      apply (simp add: bv-sub-def bv-sadd-def bv-uminus-def)
      apply (rule length-int-to-bv-upper-limit-gt0)
      apply (rule p)
    proof simp
      from bv-to-int-lower-range [of w2]
      have v2: - bv-to-int w2 ≤ 2 ^ (length w2 - 1)
        by simp
      have bv-to-int w1 + - bv-to-int w2 < (2 ^ (length w1 - 1)) + (2 ^ (length
w2 - 1))
        apply (rule zadd-zless-mono)
        apply (rule bv-to-int-upper-range [of w1])
        apply (rule v2)
        done
      also have ... ≤ 2 ^ max (length w1) (length w2)
        apply (rule adder-helper)
        apply (rule lmw)
        done
      finally show ?Q < 2 ^ max (length w1) (length w2)
        by simp
    qed
next
    assume p: ?Q < -1
    show ?thesis
      apply (simp add: bv-sub-def bv-sadd-def bv-uminus-def)
      apply (rule length-int-to-bv-upper-limit-lem1)
      apply (rule p)
    proof simp
      have (2 ^ (length w1 - 1)) + 2 ^ (length w2 - 1) ≤ (2::int) ^ max (length
w1) (length w2)
        apply (rule adder-helper)
        apply (rule lmw)
        done
      hence -((2::int) ^ max (length w1) (length w2)) ≤ -(2 ^ (length w1 - 1))
+ -(2 ^ (length w2 - 1))
        by simp
      also have -(2 ^ (length w1 - 1)) + -(2 ^ (length w2 - 1)) ≤ bv-to-int w1
+ -bv-to-int w2
        apply (rule add-mono)
        apply (rule bv-to-int-lower-range [of w1])

```

```

    using bv-to-int-upper-range [of w2]
    apply simp
  done
  finally show  $-(2^{\max (\text{length } w1) (\text{length } w2)}) \leq ?Q$ 
    by simp
qed
qed
qed

constdefs
  bv-smult :: [bit list, bit list] => bit list
  bv-smult w1 w2 == int-to-bv (bv-to-int w1 * bv-to-int w2)

lemma bv-smult-type1 [simp]: bv-smult (norm-signed w1) w2 = bv-smult w1 w2
  by (simp add: bv-smult-def)

lemma bv-smult-type2 [simp]: bv-smult w1 (norm-signed w2) = bv-smult w1 w2
  by (simp add: bv-smult-def)

lemma bv-smult-returntype [simp]: norm-signed (bv-smult w1 w2) = bv-smult w1
w2
  by (simp add: bv-smult-def)

lemma bv-smult-length: length (bv-smult w1 w2) ≤ length w1 + length w2
proof -
  let ?Q = bv-to-int w1 * bv-to-int w2

  have lmw: ?Q ≠ 0 ==> 0 < length w1 ∧ 0 < length w2
    by auto

  have 0 < ?Q ∨ ?Q = 0 ∨ ?Q = -1 ∨ ?Q < -1
    by arith
  thus ?thesis
proof (safe dest!: iffD1 [OF mult-eq-0-iff])
  assume bv-to-int w1 = 0
  thus ?thesis
    by (simp add: bv-smult-def)
next
  assume bv-to-int w2 = 0
  thus ?thesis
    by (simp add: bv-smult-def)
next
  assume p: ?Q = -1
  show ?thesis
    apply (simp add: bv-smult-def p)
    apply (cut-tac lmw)
    apply arith
    using p
    apply simp

```

```

done
next
  assume p: 0 < ?Q
  thus ?thesis
  proof (simp add: zero-less-mult-iff,safe)
    assume bi1: 0 < bv-to-int w1
    assume bi2: 0 < bv-to-int w2
    show ?thesis
      apply (simp add: bv-smult-def)
      apply (rule length-int-to-bv-upper-limit-gt0)
      apply (rule p)
  proof simp
    have ?Q < 2 ^ (length w1 - 1) * 2 ^ (length w2 - 1)
      apply (rule mult-strict-mono)
      apply (rule bv-to-int-upper-range)
      apply (rule bv-to-int-upper-range)
      apply (rule zero-less-power)
      apply simp
      using bi2
      apply simp
    done
    also have ... ≤ 2 ^ (length w1 + length w2 - Suc 0)
      apply simp
      apply (subst zpower-zadd-distrib [symmetric])
      apply simp
      apply arith
    done
    finally show ?Q < 2 ^ (length w1 + length w2 - Suc 0)
  .
qed
next
  assume bi1: bv-to-int w1 < 0
  assume bi2: bv-to-int w2 < 0
  show ?thesis
    apply (simp add: bv-smult-def)
    apply (rule length-int-to-bv-upper-limit-gt0)
    apply (rule p)
  proof simp
    have -bv-to-int w1 * -bv-to-int w2 ≤ 2 ^ (length w1 - 1) * 2 ^ (length w2
- 1)
      apply (rule mult-mono)
      using bv-to-int-lower-range [of w1]
      apply simp
      using bv-to-int-lower-range [of w2]
      apply simp
      apply (rule zero-le-power,simp)
      using bi2
      apply simp
    done

```

```

    hence ?Q ≤ 2 ^ (length w1 - 1) * 2 ^ (length w2 - 1)
      by simp
    also have ... < 2 ^ (length w1 + length w2 - Suc 0)
      apply simp
      apply (subst zpower-zadd-distrib [symmetric])
      apply simp
      apply (cut-tac lmw)
      apply arith
      apply (cut-tac p)
      apply arith
      done
    finally show ?Q < 2 ^ (length w1 + length w2 - Suc 0) .
  qed
next
  assume p: ?Q < -1
  show ?thesis
    apply (subst bv-smult-def)
    apply (rule length-int-to-bv-upper-limit-lem1)
    apply (rule p)
  proof simp
    have (2::int) ^ (length w1 - 1) * 2 ^ (length w2 - 1) ≤ 2 ^ (length w1 +
length w2 - Suc 0)
      apply simp
      apply (subst zpower-zadd-distrib [symmetric])
      apply simp
      apply (cut-tac lmw)
      apply arith
      apply (cut-tac p)
      apply arith
      done
    hence -((2::int) ^ (length w1 + length w2 - Suc 0)) ≤ -(2 ^ (length w1 -
1) * 2 ^ (length w2 - 1))
      by simp
    also have ... ≤ ?Q
  proof -
    from p
    have q: bv-to-int w1 * bv-to-int w2 < 0
      by simp
    thus ?thesis
  proof (simp add: mult-less-0-iff, safe)
    assume bi1: 0 < bv-to-int w1
    assume bi2: bv-to-int w2 < 0
    have -bv-to-int w2 * bv-to-int w1 ≤ ((2::int) ^ (length w2 - 1)) * (2 ^
(length w1 - 1))
      apply (rule mult-mono)
      using bv-to-int-lower-range [of w2]
      apply simp
      using bv-to-int-upper-range [of w1]

```



```

      apply simp
      apply (rule zero-le-power,simp)
      using bi1
      apply simp
    done
  hence  $-?Q \leq ((2::int)^(length\ w1 - 1)) * (2 ^ (length\ w2 - 1))$ 
    by (simp add: zmult-ac)
  thus  $-(((2::int)^(length\ w1 - Suc\ 0)) * (2 ^ (length\ w2 - Suc\ 0))) \leq$ 
?Q
    by simp
  next
  assume bi1:  $bv\text{-}to\text{-}int\ w1 < 0$ 
  assume bi2:  $0 < bv\text{-}to\text{-}int\ w2$ 
  have  $-bv\text{-}to\text{-}int\ w1 * bv\text{-}to\text{-}int\ w2 \leq ((2::int)^(length\ w1 - 1)) * (2 ^$ 
(length\ w2 - 1))
    apply (rule mult-mono)
    using bv-to-int-lower-range [of w1]
    apply simp
    using bv-to-int-upper-range [of w2]
    apply simp
    apply (rule zero-le-power,simp)
    using bi2
    apply simp
  done
  hence  $-?Q \leq ((2::int)^(length\ w1 - 1)) * (2 ^ (length\ w2 - 1))$ 
    by (simp add: zmult-ac)
  thus  $-(((2::int)^(length\ w1 - Suc\ 0)) * (2 ^ (length\ w2 - Suc\ 0))) \leq$ 
?Q
    by simp
  qed
qed
finally show  $-(2 ^ (length\ w1 + length\ w2 - Suc\ 0)) \leq ?Q$ 
.
qed
qed
qed

```

lemma *bv-msb-one*: $bv\text{-}msb\ w = 1 \implies 0 < bv\text{-}to\text{-}nat\ w$
 by (cases w,simp-all)

lemma *bv-smult-length-utos*: $length\ (bv\text{-}smult\ (utos\ w1)\ w2) \leq length\ w1 + length\ w2$

proof –

let $?Q = bv\text{-}to\text{-}int\ (utos\ w1) * bv\text{-}to\text{-}int\ w2$

have lmw : $?Q \neq 0 \implies 0 < length\ (utos\ w1) \wedge 0 < length\ w2$
 by auto

have $0 < ?Q \vee ?Q = 0 \vee ?Q = -1 \vee ?Q < -1$

```

    by arith
  thus ?thesis
proof (safe dest!: iffD1 [OF mult-eq-0-iff])
  assume bv-to-int (utos w1) = 0
  thus ?thesis
    by (simp add: bv-smult-def)
next
  assume bv-to-int w2 = 0
  thus ?thesis
    by (simp add: bv-smult-def)
next
  assume p: 0 < ?Q
  thus ?thesis
proof (simp add: zero-less-mult-iff,safe)
  assume biw2: 0 < bv-to-int w2
  show ?thesis
    apply (simp add: bv-smult-def)
    apply (rule length-int-to-bv-upper-limit-gt0)
    apply (rule p)
  proof simp
    have ?Q < 2 ^ length w1 * 2 ^ (length w2 - 1)
      apply (rule mult-strict-mono)
      apply (simp add: bv-to-int-utos int-nat-two-exp)
      apply (rule bv-to-nat-upper-range)
      apply (rule bv-to-int-upper-range)
      apply (rule zero-less-power,simp)
      using biw2
      apply simp
    done
    also have ... ≤ 2 ^ (length w1 + length w2 - Suc 0)
      apply simp
      apply (subst zpower-zadd-distrib [symmetric])
      apply simp
      apply (cut-tac lmw)
      apply arith
      using p
      apply auto
    done
    finally show ?Q < 2 ^ (length w1 + length w2 - Suc 0)
      .
  qed
next
  assume bv-to-int (utos w1) < 0
  thus ?thesis
    by (simp add: bv-to-int-utos)
qed
next
  assume p: ?Q = -1
  thus ?thesis

```

```

    apply (simp add: bv-smult-def)
    apply (cut-tac lmw)
    apply arith
    apply simp
    done
next
  assume p: ?Q < -1
  show ?thesis
    apply (subst bv-smult-def)
    apply (rule length-int-to-bv-upper-limit-lem1)
    apply (rule p)
  proof simp
    have  $(2::int) ^ \text{length } w1 * 2 ^ (\text{length } w2 - 1) \leq 2 ^ (\text{length } w1 + \text{length } w2 - \text{Suc } 0)$ 
    apply simp
    apply (subst zpower-zadd-distrib [symmetric])
    apply simp
    apply (cut-tac lmw)
    apply arith
    apply (cut-tac p)
    apply arith
    done
    hence  $-((2::int) ^ (\text{length } w1 + \text{length } w2 - \text{Suc } 0)) \leq -(2 ^ \text{length } w1 * 2 ^ (\text{length } w2 - 1))$ 
    by simp
    also have ... ≤ ?Q
  proof -
    from p
    have q:  $\text{bv-to-int } (\text{utos } w1) * \text{bv-to-int } w2 < 0$ 
    by simp
    thus ?thesis
    proof (simp add: mult-less-0-iff, safe)
      assume bi1:  $0 < \text{bv-to-int } (\text{utos } w1)$ 
      assume bi2:  $\text{bv-to-int } w2 < 0$ 
      have  $-\text{bv-to-int } w2 * \text{bv-to-int } (\text{utos } w1) \leq ((2::int) ^ (\text{length } w2 - 1)) * (2 ^ \text{length } w1)$ 
      apply (rule mult-mono)
      using bv-to-int-lower-range [of w2]
      apply simp
      apply (simp add: bv-to-int-utos)
      using bv-to-nat-upper-range [of w1]
      apply (simp add: int-nat-two-exp)
      apply (rule zero-le-power, simp)
      using bi1
      apply simp
      done
      hence  $-?Q \leq ((2::int) ^ \text{length } w1) * (2 ^ (\text{length } w2 - 1))$ 
      by (simp add: zmult-ac)
      thus  $-(((2::int) ^ \text{length } w1) * (2 ^ (\text{length } w2 - \text{Suc } 0))) \leq ?Q$ 

```

```

      by simp
    next
      assume bi1: bv-to-int (utos w1) < 0
      thus -(((2::int) ^ length w1) * (2 ^ (length w2 - Suc 0))) ≤ ?Q
        by (simp add: bv-to-int-utos)
      qed
    qed
  finally show -(2 ^ (length w1 + length w2 - Suc 0)) ≤ ?Q
  .
qed
qed
qed

```

```

lemma bv-smult-sym: bv-smult w1 w2 = bv-smult w2 w1
  by (simp add: bv-smult-def zmult-ac)

```

16.7 Structural operations

```

constdefs
  bv-select :: [bit list, nat] => bit
  bv-select w i == w ! (length w - 1 - i)
  bv-chop :: [bit list, nat] => bit list * bit list
  bv-chop w i == let len = length w in (take (len - i) w, drop (len - i) w)
  bv-slice :: [bit list, nat*nat] => bit list
  bv-slice w == λ(b,e). fst (bv-chop (snd (bv-chop w (b+1))) e)

lemma bv-select-rev:
  assumes notnull: n < length w
  shows      bv-select w n = rev w ! n
proof -
  have ∀ n. n < length w --> bv-select w n = rev w ! n
  proof (rule length-induct [of - w], auto simp add: bv-select-def)
    fix xs :: bit list
    fix n
    assume ind: ∀ ys::bit list. length ys < length xs --> (∀ n. n < length ys -->
ys ! (length ys - Suc n) = rev ys ! n)
    assume notx: n < length xs
    show xs ! (length xs - Suc n) = rev xs ! n
  proof (cases xs)
    assume xs = []
    with notx
    show ?thesis
    by simp
  next
    fix y ys
    assume [simp]: xs = y # ys
    show ?thesis
  proof (auto simp add: nth-append)
    assume noty: n < length ys

```

```

    from spec [OF ind, of ys]
    have  $\forall n. n < \text{length } ys \longrightarrow ys ! (\text{length } ys - \text{Suc } n) = \text{rev } ys ! n$ 
      by simp
    hence  $n < \text{length } ys \longrightarrow ys ! (\text{length } ys - \text{Suc } n) = \text{rev } ys ! n$ 
      ..
    hence  $ys ! (\text{length } ys - \text{Suc } n) = \text{rev } ys ! n$ 
      ..
    thus  $(y \# ys) ! (\text{length } ys - n) = \text{rev } ys ! n$ 
      by (simp add: nth-Cons' noty linorder-not-less [symmetric])
  next
    assume  $\sim n < \text{length } ys$ 
    hence  $x: \text{length } ys \leq n$ 
      by simp
    from notx
    have  $n < \text{Suc } (\text{length } ys)$ 
      by simp
    hence  $n \leq \text{length } ys$ 
      by simp
    with x
    have  $\text{length } ys = n$ 
      by simp
    thus  $y = [y] ! (n - \text{length } ys)$ 
      by simp
  qed
qed
qed
hence  $n < \text{length } w \longrightarrow \text{bv-select } w \ n = \text{rev } w ! n$ 
  ..
thus ?thesis
  ..
qed

lemma bv-chop-append:  $\text{bv-chop } (w1 @ w2) (\text{length } w2) = (w1, w2)$ 
  by (simp add: bv-chop-def Let-def)

lemma append-bv-chop-id:  $\text{fst } (\text{bv-chop } w \ l) @ \text{snd } (\text{bv-chop } w \ l) = w$ 
  by (simp add: bv-chop-def Let-def)

lemma bv-chop-length-fst [simp]:  $\text{length } (\text{fst } (\text{bv-chop } w \ i)) = \text{length } w - i$ 
  by (simp add: bv-chop-def Let-def, arith)

lemma bv-chop-length-snd [simp]:  $\text{length } (\text{snd } (\text{bv-chop } w \ i)) = \min i (\text{length } w)$ 
  by (simp add: bv-chop-def Let-def, arith)

lemma bv-slice-length [simp]:  $[[j \leq i; i < \text{length } w]] \Longrightarrow \text{length } (\text{bv-slice } w \ (i, j)) = i - j + 1$ 
  by (auto simp add: bv-slice-def, arith)

constdefs

```

length-nat :: *nat* => *nat*
length-nat *x* == *LEAST* *n*. *x* < 2 ^ *n*

lemma *length-nat*: *length* (*nat-to-bv* *n*) = *length-nat* *n*
apply (*simp* *add*: *length-nat-def*)
apply (*rule* *Least-equality* [*symmetric*])
prefer 2
apply (*rule* *length-nat-to-bv-upper-limit*)
apply *arith*
apply (*rule* *ccontr*)
proof –
assume ~ *n* < 2 ^ *length* (*nat-to-bv* *n*)
hence 2 ^ *length* (*nat-to-bv* *n*) ≤ *n*
by *simp*
hence *length* (*nat-to-bv* *n*) < *length* (*nat-to-bv* *n*)
by (*rule* *length-nat-to-bv-lower-limit*)
thus *False*
by *simp*
qed

lemma *length-nat-0* [*simp*]: *length-nat* 0 = 0
by (*simp* *add*: *length-nat-def* *Least-equality*)

lemma *length-nat-non0*:
assumes *n0*: 0 < *n*
shows *length-nat* *n* = *Suc* (*length-nat* (*n* div 2))
apply (*simp* *add*: *length-nat* [*symmetric*])
apply (*subst* *nat-to-bv-non0* [*of* *n*])
apply (*simp-all* *add*: *n0*)
done

constdefs
length-int :: *int* => *nat*
length-int *x* == if 0 < *x* then *Suc* (*length-nat* (*nat* *x*)) else if *x* = 0 then 0 else
Suc (*length-nat* (*nat* (–*x* – 1)))

lemma *length-int*: *length* (*int-to-bv* *i*) = *length-int* *i*
proof (*cases* 0 < *i*)
assume *i0*: 0 < *i*
hence *length* (*int-to-bv* *i*) = *length* (*norm-signed* (0 # *norm-unsigned* (*nat-to-bv* (*nat* *i*))))
by *simp*
also from *norm-unsigned-result* [*of* *nat-to-bv* (*nat* *i*)]
have ... = *Suc* (*length-nat* (*nat* *i*))
apply *safe*
apply (*simp* *del*: *norm-unsigned-nat-to-bv*)
apply (*drule* *norm-empty-bv-to-nat-zero*)
using *prems*
apply *simp*

```

    apply arith
    apply (cases norm-unsigned (nat-to-bv (nat i)))
    apply (drule norm-empty-bv-to-nat-zero [of nat-to-bv (nat i)])
    using prems
    apply simp
    apply simp
    using prems
    apply (simp add: length-nat [symmetric])
    done
  finally show ?thesis
    using i0
    by (simp add: length-int-def)
next
  assume  $\sim 0 < i$ 
  hence i0:  $i \leq 0$ 
    by simp
  show ?thesis
  proof (cases  $i = 0$ )
    assume  $i = 0$ 
    thus ?thesis
      by (simp add: length-int-def)
  next
    assume  $i \neq 0$ 
    with i0
    have i0:  $i < 0$ 
      by simp
    hence length (int-to-bv i) = length (norm-signed (1 # bv-not (norm-unsigned
      (nat-to-bv (nat (- i) - 1)))))
      by (simp add: int-to-bv-def nat-diff-distrib)
    also from norm-unsigned-result [of nat-to-bv (nat (- i) - 1)]
    have ... = Suc (length-nat (nat (- i) - 1))
      by safe
    apply (simp del: norm-unsigned-nat-to-bv)
    apply (drule norm-empty-bv-to-nat-zero [of nat-to-bv (nat (-i) - Suc 0)])
    using prems
    apply simp
    apply (cases  $- i - 1 = 0$ )
    apply simp
    apply (simp add: length-nat [symmetric])
    apply (cases norm-unsigned (nat-to-bv (nat (- i) - 1)))
    apply simp
    apply simp
    done
  finally
  show ?thesis
    using i0
    by (simp add: length-int-def nat-diff-distrib del: int-to-bv-lt0)
qed
qed

```

```

lemma length-int-0 [simp]: length-int 0 = 0
  by (simp add: length-int-def)

lemma length-int-gt0: 0 < i ==> length-int i = Suc (length-nat (nat i))
  by (simp add: length-int-def)

lemma length-int-lt0: i < 0 ==> length-int i = Suc (length-nat (nat (- i) - 1))
  by (simp add: length-int-def nat-diff-distrib)

lemma bv-chopI: [| w = w1 @ w2 ; i = length w2 |] ==> bv-chop w i = (w1, w2)
  by (simp add: bv-chop-def Let-def)

lemma bv-sliceI: [| j ≤ i ; i < length w ; w = w1 @ w2 @ w3 ; Suc i = length
w2 + j ; j = length w3 |] ==> bv-slice w (i, j) = w2
  apply (simp add: bv-slice-def)
  apply (subst bv-chopI [of w1 @ w2 @ w3 w1 w2 @ w3])
  apply simp
  apply simp
  apply simp
  apply (subst bv-chopI [of w2 @ w3 w2 w3], simp-all)
  done

lemma bv-slice-bv-slice:
  assumes ki: k ≤ i
  and    ij: i ≤ j
  and    jl: j ≤ l
  and    lw: l < length w
  shows   bv-slice w (j, i) = bv-slice (bv-slice w (l, k)) (j - k, i - k)
proof -
  def w1 == fst (bv-chop w (Suc l))
  def w2 == fst (bv-chop (snd (bv-chop w (Suc l))) (Suc j))
  def w3 == fst (bv-chop (snd (bv-chop (snd (bv-chop w (Suc l))) (Suc j))) i)
  def w4 == fst (bv-chop (snd (bv-chop (snd (bv-chop (snd (bv-chop w (Suc l)))
(Suc j))) i)) k)
  def w5 == snd (bv-chop (snd (bv-chop (snd (bv-chop (snd (bv-chop w (Suc l)))
(Suc j))) i)) k)

  note w-defs = w1-def w2-def w3-def w4-def w5-def

  have w-def: w = w1 @ w2 @ w3 @ w4 @ w5
    by (simp add: w-defs append-bv-chop-id)

  from ki ij jl lw
  show ?thesis
    apply (subst bv-sliceI [where ?j = i and ?i = j and ?w = w and ?w1.0 =
w1 @ w2 and ?w2.0 = w3 and ?w3.0 = w4 @ w5])
    apply simp-all
    apply (rule w-def)

```



```

    apply (simp add: w-defs min-def)
    apply (simp add: w-defs min-def)
    apply (subst bv-sliceI [where ?j = k and ?i = l and ?w = w and ?w1.0 =
w1 and ?w2.0 = w2 @ w3 @ w4 and ?w3.0 = w5])
    apply simp-all
    apply (rule w-def)
    apply (simp add: w-defs min-def)
    apply (simp add: w-defs min-def)
    apply (subst bv-sliceI [where ?j = i-k and ?i = j-k and ?w = w2 @ w3
@ w4 and ?w1.0 = w2 and ?w2.0 = w3 and ?w3.0 = w4])
    apply simp-all
    apply (simp-all add: w-defs min-def)
    apply arith+
    done
qed

```

```

lemma bv-to-nat-extend [simp]: bv-to-nat (bv-extend n 0 w) = bv-to-nat w
  apply (simp add: bv-extend-def)
  apply (subst bv-to-nat-dist-append)
  apply simp
  apply (induct n - length w, simp-all)
  done

```

```

lemma bv-msb-extend-same [simp]: bv-msb w = b ==> bv-msb (bv-extend n b w)
= b
  apply (simp add: bv-extend-def)
  apply (induct n - length w, simp-all)
  done

```

```

lemma bv-to-int-extend [simp]:
  assumes a: bv-msb w = b
  shows      bv-to-int (bv-extend n b w) = bv-to-int w
proof (cases bv-msb w)
  assume [simp]: bv-msb w = 0
  with a have [simp]: b = 0
    by simp
  show ?thesis
    by (simp add: bv-to-int-def)
next
  assume [simp]: bv-msb w = 1
  with a have [simp]: b = 1
    by simp
  show ?thesis
    apply (simp add: bv-to-int-def)
    apply (simp add: bv-extend-def)
    apply (induct n - length w, simp-all)
    done
qed

```

lemma *length-nat-mono* [*simp*]: $x \leq y \implies \text{length-nat } x \leq \text{length-nat } y$

proof (*rule ccontr*)

assume *xy*: $x \leq y$

assume $\sim \text{length-nat } x \leq \text{length-nat } y$

hence *lxy*: $\text{length-nat } y < \text{length-nat } x$

by *simp*

hence $\text{length-nat } y < (\text{LEAST } n. x < 2 \wedge n)$

by (*simp add: length-nat-def*)

hence $\sim x < 2 \wedge \text{length-nat } y$

by (*rule not-less-Least*)

hence *xx*: $2 \wedge \text{length-nat } y \leq x$

by *simp*

have *yy*: $y < 2 \wedge \text{length-nat } y$

apply (*simp add: length-nat-def*)

apply (*rule LeastI*)

apply (*subgoal-tac y < 2 ^ y, assumption*)

apply (*cases 0 ≤ y*)

apply (*induct y, simp-all*)

done

with *xx*

have $y < x$ **by** *simp*

with *xy*

show *False*

by *simp*

qed

lemma *length-nat-mono-int* [*simp*]: $x \leq y \implies \text{length-nat } x \leq \text{length-nat } y$

apply (*rule length-nat-mono*)

apply *arith*

done

lemma *length-nat-pos* [*simp, intro!*]: $0 < x \implies 0 < \text{length-nat } x$

by (*simp add: length-nat-non0*)

lemma *length-int-mono-gt0*: $[0 \leq x ; x \leq y] \implies \text{length-int } x \leq \text{length-int } y$

by (*cases x = 0, simp-all add: length-int-gt0 nat-le-eq-zle*)

lemma *length-int-mono-lt0*: $[x \leq y ; y \leq 0] \implies \text{length-int } y \leq \text{length-int } x$

apply (*cases y = 0, simp-all add: length-int-lt0*)

apply (*subgoal-tac nat (- y) - Suc 0 ≤ nat (- x) - Suc 0*)

apply (*simp add: length-nat-mono*)

apply *arith*

done

lemmas [*simp*] = *length-nat-non0*

lemma *nat-to-bv* (*number-of Numeral.Pls*) = []

by *simp*

consts

fast-bv-to-nat-helper :: [bit list, bin] => bin

primrec

fast-bv-to-nat-Nil: *fast-bv-to-nat-helper* [] bin = bin

fast-bv-to-nat-Cons: *fast-bv-to-nat-helper* (b#bs) bin = *fast-bv-to-nat-helper* bs
(bin BIT (bit-case bit.B0 bit.B1 b))

lemma *fast-bv-to-nat-Cons0*: *fast-bv-to-nat-helper* (0#bs) bin = *fast-bv-to-nat-helper* bs
(bin BIT bit.B0)

by *simp*

lemma *fast-bv-to-nat-Cons1*: *fast-bv-to-nat-helper* (1#bs) bin = *fast-bv-to-nat-helper* bs
(bin BIT bit.B1)

by *simp*

lemma *fast-bv-to-nat-def*: *bv-to-nat* bs == *number-of* (*fast-bv-to-nat-helper* bs *Natural.Pls*)

proof (*simp add: bv-to-nat-def*)

have $\forall \text{ bin. } \neg (\text{neg } (\text{number-of } \text{bin} :: \text{int})) \longrightarrow (\text{foldl } (\%bn \text{ b. } 2 * bn + \text{bitval } b) (\text{number-of } \text{bin}) \text{ bs}) = \text{number-of } (\text{fast-bv-to-nat-helper } \text{bs } \text{bin})$

apply (*induct bs,simp*)

apply (*case-tac a,simp-all*)

done

thus *foldl* ($\lambda bn \text{ b. } 2 * bn + \text{bitval } b$) 0 bs \equiv *number-of* (*fast-bv-to-nat-helper* bs *Natural.Pls*)

by (*simp del: nat-numeral-0-eq-0 add: nat-numeral-0-eq-0 [symmetric]*)

qed

declare *fast-bv-to-nat-Cons* [*simp del*]

declare *fast-bv-to-nat-Cons0* [*simp*]

declare *fast-bv-to-nat-Cons1* [*simp*]

setup *setup-word*

declare *bv-to-nat1* [*simp del*]

declare *bv-to-nat-helper* [*simp del*]

constdefs

bv-mapzip :: [bit => bit => bit, bit list, bit list] => bit list

bv-mapzip f w1 w2 == let g = *bv-extend* (max (length w1) (length w2)) 0
in map (*split* f) (*zip* (g w1) (g w2))

lemma *bv-length-bv-mapzip* [*simp*]: length (*bv-mapzip* f w1 w2) = max (length w1) (length w2)

by (*simp add: bv-mapzip-def Let-def split: split-max*)

```

lemma bv-mapzip-Nil [simp]: bv-mapzip f [] [] = []
  by (simp add: bv-mapzip-def Let-def)

lemma bv-mapzip-Cons [simp]: length w1 = length w2 ==> bv-mapzip f (x#w1)
(y#w2) = f x y # bv-mapzip f w1 w2
  by (simp add: bv-mapzip-def Let-def)

end

```

17 Zorn: Zorn’s Lemma

```

theory Zorn
imports Main
begin

```

The lemma and section numbers refer to an unpublished article [1].

```

constdefs
  chain    :: 'a set set => 'a set set set
  chain S == {F. F ⊆ S & (∀ x ∈ F. ∀ y ∈ F. x ⊆ y | y ⊆ x)}

  super    :: ['a set set, 'a set set] => 'a set set set
  super S c == {d. d ∈ chain S & c ⊂ d}

  maxchain :: 'a set set => 'a set set set
  maxchain S == {c. c ∈ chain S & super S c = {}}

  succ     :: ['a set set, 'a set set] => 'a set set
  succ S c ==
    if c ∉ chain S | c ∈ maxchain S
    then c else SOME c'. c' ∈ super S c

consts
  TFin :: 'a set set => 'a set set set

```

```

inductive TFin S
intros
  succI:      x ∈ TFin S ==> succ S x ∈ TFin S
  Pow-UnionI: Y ∈ Pow(TFin S) ==> Union(Y) ∈ TFin S
monos      Pow-mono

```

17.1 Mathematical Preamble

```

lemma Union-lemma0:
  (∀ x ∈ C. x ⊆ A | B ⊆ x) ==> Union(C) ⊆ A | B ⊆ Union(C)
  by blast

```

This is theorem *increasingD2* of ZF/Zorn.thy

```

lemma Abrial-axiom1:  $x \subseteq \text{succ } S \ x$ 
  apply (unfold succ-def)
  apply (rule split-if [THEN iffD2])
  apply (auto simp add: super-def maxchain-def psubset-def)
  apply (rule swap, assumption)
  apply (rule someI2, blast+)
done

```

```

lemmas TFin-UnionI = TFin.Pow-UnionI [OF PowI]

```

```

lemma TFin-induct:
  [|  $n \in \text{TFin } S$ ;
    !! $x$ . [|  $x \in \text{TFin } S$ ;  $P(x)$  |] ==>  $P(\text{succ } S \ x)$ ;
    !! $Y$ . [|  $Y \subseteq \text{TFin } S$ ;  $\text{Ball } Y \ P$  |] ==>  $P(\text{Union } Y)$  |]
  ==>  $P(n)$ 
  apply (erule TFin.induct)
  apply blast+
done

```

```

lemma succ-trans:  $x \subseteq y \implies x \subseteq \text{succ } S \ y$ 
  apply (erule subset-trans)
  apply (rule Abrial-axiom1)
done

```

Lemma 1 of section 3.1

```

lemma TFin-linear-lemma1:
  [|  $n \in \text{TFin } S$ ;  $m \in \text{TFin } S$ ;
     $\forall x \in \text{TFin } S. x \subseteq m \implies x = m \mid \text{succ } S \ x \subseteq m$ 
  |] ==>  $n \subseteq m \mid \text{succ } S \ m \subseteq n$ 
  apply (erule TFin-induct)
  apply (erule-tac [2] Union-lemma0)
  apply (blast del: subsetI intro: succ-trans)
done

```

Lemma 2 of section 3.2

```

lemma TFin-linear-lemma2:
   $m \in \text{TFin } S \implies \forall n \in \text{TFin } S. n \subseteq m \implies n=m \mid \text{succ } S \ n \subseteq m$ 
  apply (erule TFin-induct)
  apply (rule impI [THEN ballI])

```

case split using *TFin-linear-lemma1*

```

  apply (rule-tac n1 = n and m1 = x in TFin-linear-lemma1 [THEN disjE],
    assumption+)
  apply (erule-tac x = n in bspec, assumption)
  apply (blast del: subsetI intro: succ-trans, blast)

```

second induction step

```

  apply (rule impI [THEN ballI])
  apply (rule Union-lemma0 [THEN disjE])

```

```

apply (rule-tac [3] disjI2)
prefer 2 apply blast
apply (rule ballI)
apply (rule-tac n1 = n and m1 = x in TFin-linear-lemma1 [THEN disjE],
  assumption+, auto)
apply (blast intro!: Abrial-axiom1 [THEN subsetD])
done

```

Re-ordering the premises of Lemma 2

```

lemma TFin-subsetD:
  [| n  $\subseteq$  m; m  $\in$  TFin S; n  $\in$  TFin S |] ==> n=m | succ S n  $\subseteq$  m
by (rule TFin-linear-lemma2 [rule-format])

```

Consequences from section 3.3 – Property 3.2, the ordering is total

```

lemma TFin-subset-linear: [| m  $\in$  TFin S; n  $\in$  TFin S |] ==> n  $\subseteq$  m | m  $\subseteq$  n
apply (rule disjE)
apply (rule TFin-linear-lemma1 [OF - TFin-linear-lemma2])
apply (assumption+, erule disjI2)
apply (blast del: subsetI
  intro: subsetI Abrial-axiom1 [THEN subset-trans])
done

```

Lemma 3 of section 3.3

```

lemma eq-succ-upper: [| n  $\in$  TFin S; m  $\in$  TFin S; m = succ S m |] ==> n  $\subseteq$ 
m
apply (erule TFin-induct)
apply (drule TFin-subsetD)
apply (assumption+, force, blast)
done

```

Property 3.3 of section 3.3

```

lemma equal-succ-Union: m  $\in$  TFin S ==> (m = succ S m) = (m = Union(TFin
S))
apply (rule iffI)
apply (rule Union-upper [THEN equalityI])
apply (rule-tac [2] eq-succ-upper [THEN Union-least])
apply (assumption+)
apply (erule ssubst)
apply (rule Abrial-axiom1 [THEN equalityI])
apply (blast del: subsetI intro: subsetI TFin-UnionI TFin.succI)
done

```

17.2 Hausdorff’s Theorem: Every Set Contains a Maximal Chain.

NB: We assume the partial ordering is \subseteq , the subset relation!

```

lemma empty-set-mem-chain: ({ } :: 'a set set)  $\in$  chain S
by (unfold chain-def) auto

```

```

lemma super-subset-chain:  $\text{super } S \ c \subseteq \text{chain } S$ 
  by (unfold super-def) blast

lemma maxchain-subset-chain:  $\text{maxchain } S \subseteq \text{chain } S$ 
  by (unfold maxchain-def) blast

lemma mem-super-Ex:  $c \in \text{chain } S - \text{maxchain } S \implies ? d. d \in \text{super } S \ c$ 
  by (unfold super-def maxchain-def) auto

lemma select-super:  $c \in \text{chain } S - \text{maxchain } S \implies$ 
   $(\epsilon c'. c': \text{super } S \ c): \text{super } S \ c$ 
  apply (erule mem-super-Ex [THEN exE])
  apply (rule someI2, auto)
  done

lemma select-not-equals:  $c \in \text{chain } S - \text{maxchain } S \implies$ 
   $(\epsilon c'. c': \text{super } S \ c) \neq c$ 
  apply (rule notI)
  apply (drule select-super)
  apply (simp add: super-def psubset-def)
  done

lemma succI3:  $c \in \text{chain } S - \text{maxchain } S \implies \text{succ } S \ c = (\epsilon c'. c': \text{super } S \ c)$ 
  by (unfold succ-def) (blast intro!: if-not-P)

lemma succ-not-equals:  $c \in \text{chain } S - \text{maxchain } S \implies \text{succ } S \ c \neq c$ 
  apply (frule succI3)
  apply (simp (no-asm-simp))
  apply (rule select-not-equals, assumption)
  done

lemma TFin-chain-lemma4:  $c \in \text{TFin } S \implies (c :: 'a \text{ set set}): \text{chain } S$ 
  apply (erule TFin-induct)
  apply (simp add: succ-def select-super [THEN super-subset-chain[THEN sub-
setD]])
  apply (unfold chain-def)
  apply (rule CollectI, safe)
  apply (drule bspec, assumption)
  apply (rule-tac [2] m1 = Xa and n1 = X in TFin-subset-linear [THEN disjE],
blast+)
  done

theorem Hausdorff:  $\exists c. (c :: 'a \text{ set set}): \text{maxchain } S$ 
  apply (rule-tac x = Union (TFin S) in exI)
  apply (rule classical)
  apply (subgoal-tac succ S (Union (TFin S)) = Union (TFin S) ))
  prefer 2
  apply (blast intro!: TFin-UnionI equal-succ-Union [THEN iffD2, symmetric])

```

```

apply (cut-tac subset-refl [THEN TFin-UnionI, THEN TFin-chain-lemma4])
apply (drule DiffI [THEN succ-not-equals], blast+)
done

```

17.3 Zorn’s Lemma: If All Chains Have Upper Bounds Then There Is a Maximal Element

lemma *chain-extend*:

```

  [| c ∈ chain S; z ∈ S;
    ∀ x ∈ c. x ≤ (z :: 'a set) |] ==> {z} ∪ c ∈ chain S
by (unfold chain-def) blast

```

lemma *chain-Union-upper*: [| c ∈ chain S; x ∈ c |] ==> x ⊆ Union(c)
by (unfold chain-def) auto

lemma *chain-ball-Union-upper*: c ∈ chain S ==> ∀ x ∈ c. x ⊆ Union(c)
by (unfold chain-def) auto

lemma *maxchain-Zorn*:

```

  [| c ∈ maxchain S; u ∈ S; Union(c) ⊆ u |] ==> Union(c) = u
apply (rule ccontr)
apply (simp add: maxchain-def)
apply (erule conjE)
apply (subgoal-tac ({u} ∪ c) ∈ super S c)
apply simp
apply (unfold super-def psubset-def)
apply (blast intro: chain-extend dest: chain-Union-upper)
done

```

theorem *Zorn-Lemma*:

```

  ∀ c ∈ chain S. Union(c) ∈ S ==> ∃ y ∈ S. ∀ z ∈ S. y ⊆ z --> y = z
apply (cut-tac Hausdorff maxchain-subset-chain)
apply (erule exE)
apply (drule subsetD, assumption)
apply (drule bspec, assumption)
apply (rule-tac x = Union (c) in bexI)
apply (rule ballI, rule impI)
apply (blast dest!: maxchain-Zorn, assumption)
done

```

17.4 Alternative version of Zorn’s Lemma

lemma *Zorn-Lemma2*:

```

  ∀ c ∈ chain S. ∃ y ∈ S. ∀ x ∈ c. x ⊆ y
  ==> ∃ y ∈ S. ∀ x ∈ S. (y :: 'a set) ⊆ x --> y = x
apply (cut-tac Hausdorff maxchain-subset-chain)
apply (erule exE)
apply (drule subsetD, assumption)
apply (drule bspec, assumption, erule bexE)

```



```

apply (rule-tac  $x = y$  in beXI)
  prefer 2 apply assumption
apply clarify
apply (rule ccontr)
apply (frule-tac  $z = x$  in chain-extend)
  apply (assumption, blast)
apply (unfold maxchain-def super-def psubset-def)
apply (blast elim!: equalityCE)
done

```

Various other lemmas

```

lemma chainD: [ $c \in \text{chain } S; x \in c; y \in c$ ]  $\implies x \subseteq y \mid y \subseteq x$ 
  by (unfold chain-def) blast

```

```

lemma chainD2:  $\llbracket c :: 'a \text{ set set} \rrbracket. c \in \text{chain } S \implies c \subseteq S$ 
  by (unfold chain-def) blast

```

end

18 Product-ord: Order on product types

```

theory Product-ord
imports Main
begin

```

```

instance * :: (ord,ord) ord ..

```

```

defs (overloaded)
  prod-le-def:  $(x \leq y) \equiv (\text{fst } x < \text{fst } y) \mid (\text{fst } x = \text{fst } y \ \& \ \text{snd } x \leq \text{snd } y)$ 
  prod-less-def:  $(x < y) \equiv (\text{fst } x < \text{fst } y) \mid (\text{fst } x = \text{fst } y \ \& \ \text{snd } x < \text{snd } y)$ 

```

```

lemmas prod-ord-defs = prod-less-def prod-le-def

```

```

instance * :: (order,order) order
  apply (intro-classes, unfold prod-ord-defs)
  by (auto intro: order-less-trans)

```

```

instance *:: (linorder,linorder)linorder
  by (intro-classes, unfold prod-le-def, auto)

```

end

19 Char-ord: Order on characters

```

theory Char-ord
imports Product-ord

```

begin

Conversions between nibbles and integers in $[0..15]$.

consts

nibble-to-int:: *nibble* \Rightarrow *int*
int-to-nibble:: *int* \Rightarrow *nibble*

primrec

nibble-to-int Nibble0 = 0
nibble-to-int Nibble1 = 1
nibble-to-int Nibble2 = 2
nibble-to-int Nibble3 = 3
nibble-to-int Nibble4 = 4
nibble-to-int Nibble5 = 5
nibble-to-int Nibble6 = 6
nibble-to-int Nibble7 = 7
nibble-to-int Nibble8 = 8
nibble-to-int Nibble9 = 9
nibble-to-int NibbleA = 10
nibble-to-int NibbleB = 11
nibble-to-int NibbleC = 12
nibble-to-int NibbleD = 13
nibble-to-int NibbleE = 14
nibble-to-int NibbleF = 15

defs

int-to-nibble-def:
int-to-nibble *x* \equiv (let *y* = *x* mod 16 in
 if *y* = 0 then Nibble0 else
 if *y* = 1 then Nibble1 else
 if *y* = 2 then Nibble2 else
 if *y* = 3 then Nibble3 else
 if *y* = 4 then Nibble4 else
 if *y* = 5 then Nibble5 else
 if *y* = 6 then Nibble6 else
 if *y* = 7 then Nibble7 else
 if *y* = 8 then Nibble8 else
 if *y* = 9 then Nibble9 else
 if *y* = 10 then NibbleA else
 if *y* = 11 then NibbleB else
 if *y* = 12 then NibbleC else
 if *y* = 13 then NibbleD else
 if *y* = 14 then NibbleE else
 NibbleF)

lemma *int-to-nibble-nibble-to-int*: *int-to-nibble*(*nibble-to-int* *x*) = *x*
by (cases *x*) (auto simp: *int-to-nibble-def* *Let-def*)

lemma *inj-nibble-to-int*: *inj* *nibble-to-int*

by (*rule inj-on-inverseI*) (*rule int-to-nibble-nibble-to-int*)

lemmas *nibble-to-int-eq* = *inj-nibble-to-int* [*THEN inj-eq*]

lemma *nibble-to-int-ge-0*: $0 \leq \text{nibble-to-int } x$
by (*cases x*) *auto*

lemma *nibble-to-int-less-16*: *nibble-to-int x* < 16
by (*cases x*) *auto*

Conversion between chars and int pairs.

consts

char-to-int-pair :: *char* \Rightarrow *int* \times *int*

primrec

char-to-int-pair (*Char a b*) = (*nibble-to-int a*, *nibble-to-int b*)

lemma *inj-char-to-int-pair*: *inj char-to-int-pair*
apply (*rule inj-onI*)
apply (*case-tac x*, *case-tac y*)
apply (*auto simp: nibble-to-int-eq*)
done

lemmas *char-to-int-pair-eq* = *inj-char-to-int-pair* [*THEN inj-eq*]

Instantiation of order classes

instance *char* :: *ord* ..

defs (**overloaded**)

char-le-def: $c \leq d \equiv (\text{char-to-int-pair } c \leq \text{char-to-int-pair } d)$

char-less-def: $c < d \equiv (\text{char-to-int-pair } c < \text{char-to-int-pair } d)$

lemmas *char-ord-defs* = *char-less-def char-le-def*

instance *char* :: *order*

apply *intro-classes*

apply (*unfold char-ord-defs*)

apply (*auto simp: char-to-int-pair-eq order-less-le*)

done

instance *char::linorder*

apply *intro-classes*

apply (*unfold char-le-def*)

apply *auto*

done

end

20 Commutative-Ring: Proving equalities in commutative rings

```

theory Commutative-Ring
imports Main
uses (comm-ring.ML)
begin

```

Syntax of multivariate polynomials (pol) and polynomial expressions.

```

datatype 'a pol =
  Pc 'a
  | Pinj nat 'a pol
  | PX 'a pol nat 'a pol

```

```

datatype 'a polex =
  Pol 'a pol
  | Add 'a polex 'a polex
  | Sub 'a polex 'a polex
  | Mul 'a polex 'a polex
  | Pow 'a polex nat
  | Neg 'a polex

```

Interpretation functions for the shadow syntax.

```

consts
  Ipol :: 'a::{comm-ring,recpower} list  $\Rightarrow$  'a pol  $\Rightarrow$  'a
  Ipolex :: 'a::{comm-ring,recpower} list  $\Rightarrow$  'a polex  $\Rightarrow$  'a

```

```

primrec
  Ipol l (Pc c) = c
  Ipol l (Pinj i P) = Ipol (drop i l) P
  Ipol l (PX P x Q) = Ipol l P * (hd l) ^ x + Ipol (drop 1 l) Q

```

```

primrec
  Ipolex l (Pol P) = Ipol l P
  Ipolex l (Add P Q) = Ipolex l P + Ipolex l Q
  Ipolex l (Sub P Q) = Ipolex l P - Ipolex l Q
  Ipolex l (Mul P Q) = Ipolex l P * Ipolex l Q
  Ipolex l (Pow p n) = Ipolex l p ^ n
  Ipolex l (Neg P) = - Ipolex l P

```

Create polynomial normalized polynomials given normalized inputs.

```

constdefs
  mkPinj :: nat  $\Rightarrow$  'a pol  $\Rightarrow$  'a pol
  mkPinj x P  $\equiv$  (case P of
    Pc c  $\Rightarrow$  Pc c |
    Pinj y P  $\Rightarrow$  Pinj (x + y) P |
    PX p1 y p2  $\Rightarrow$  Pinj x P)

```

constdefs

```

mkPX :: 'a::{comm-ring,recpower} pol ⇒ nat ⇒ 'a pol ⇒ 'a pol
mkPX P i Q == (case P of
  Pc c ⇒ (if (c = 0) then (mkPinj 1 Q) else (PX P i Q)) |
  Pinj j R ⇒ PX P i Q |
  PX P2 i2 Q2 ⇒ (if (Q2 = (Pc 0)) then (PX P2 (i+i2) Q) else (PX P i Q))
)

```

Defining the basic ring operations on normalized polynomials

consts

```

add :: 'a::{comm-ring,recpower} pol × 'a pol ⇒ 'a pol
mul :: 'a::{comm-ring,recpower} pol × 'a pol ⇒ 'a pol
neg :: 'a::{comm-ring,recpower} pol ⇒ 'a pol
sqr :: 'a::{comm-ring,recpower} pol ⇒ 'a pol
pow :: 'a::{comm-ring,recpower} pol × nat ⇒ 'a pol

```

Addition

recdef *add measure* ($\lambda(x, y). \text{size } x + \text{size } y$)

```

add (Pc a, Pc b) = Pc (a + b)
add (Pc c, Pinj i P) = Pinj i (add (P, Pc c))
add (Pinj i P, Pc c) = Pinj i (add (P, Pc c))
add (Pc c, PX P i Q) = PX P i (add (Q, Pc c))
add (PX P i Q, Pc c) = PX P i (add (Q, Pc c))
add (Pinj x P, Pinj y Q) =
  (if x=y then mkPinj x (add (P, Q))
   else (if x>y then mkPinj y (add (Pinj (x-y) P, Q))
         else mkPinj x (add (Pinj (y-x) Q, P))) )
add (Pinj x P, PX Q y R) =
  (if x=0 then add(P, PX Q y R)
   else (if x=1 then PX Q y (add (R, P))
         else PX Q y (add (R, Pinj (x - 1) P))))
add (PX P x R, Pinj y Q) =
  (if y=0 then add(PX P x R, Q)
   else (if y=1 then PX P x (add (R, Q))
         else PX P x (add (R, Pinj (y - 1) Q))))
add (PX P1 x P2, PX Q1 y Q2) =
  (if x=y then mkPX (add (P1, Q1)) x (add (P2, Q2))
   else (if x>y then mkPX (add (PX P1 (x-y) (Pc 0), Q1)) y (add (P2, Q2))
         else mkPX (add (PX Q1 (y-x) (Pc 0), P1)) x (add (P2, Q2))) )

```

Multiplication

recdef *mul measure* ($\lambda(x, y). \text{size } x + \text{size } y$)

```

mul (Pc a, Pc b) = Pc (a*b)
mul (Pc c, Pinj i P) = (if c=0 then Pc 0 else mkPinj i (mul (P, Pc c)))
mul (Pinj i P, Pc c) = (if c=0 then Pc 0 else mkPinj i (mul (P, Pc c)))
mul (Pc c, PX P i Q) =
  (if c=0 then Pc 0 else mkPX (mul (P, Pc c)) i (mul (Q, Pc c)))
mul (PX P i Q, Pc c) =
  (if c=0 then Pc 0 else mkPX (mul (P, Pc c)) i (mul (Q, Pc c)))

```

```

mul (Pinj x P, Pinj y Q) =
  (if x=y then mkPinj x (mul (P, Q))
   else (if x>y then mkPinj y (mul (Pinj (x-y) P, Q))
         else mkPinj x (mul (Pinj (y-x) Q, P)) ))
mul (Pinj x P, PX Q y R) =
  (if x=0 then mul(P, PX Q y R)
   else (if x=1 then mkPX (mul (Pinj x P, Q)) y (mul (R, P))
         else mkPX (mul (Pinj x P, Q)) y (mul (R, Pinj (x - 1) P))))
mul (PX P x R, Pinj y Q) =
  (if y=0 then mul(PX P x R, Q)
   else (if y=1 then mkPX (mul (Pinj y Q, P)) x (mul (R, Q))
         else mkPX (mul (Pinj y Q, P)) x (mul (R, Pinj (y - 1) Q))))
mul (PX P1 x P2, PX Q1 y Q2) =
  add (mkPX (mul (P1, Q1)) (x+y) (mul (P2, Q2)),
       add (mkPX (mul (P1, mkPinj 1 Q2)) x (Pc 0), mkPX (mul (Q1, mkPinj 1
P2)) y (Pc 0)) )
(hints simp add: mkPinj-def split: pol.split)

```

Negation

primrec

```

neg (Pc c) = Pc (-c)
neg (Pinj i P) = Pinj i (neg P)
neg (PX P x Q) = PX (neg P) x (neg Q)

```

Substraction

constdefs

```

sub :: 'a::{comm-ring,recpower} pol ⇒ 'a pol ⇒ 'a pol
sub p q ≡ add (p, neg q)

```

Square for Fast Exponentiation

primrec

```

sqr (Pc c) = Pc (c * c)
sqr (Pinj i P) = mkPinj i (sqr P)
sqr (PX A x B) = add (mkPX (sqr A) (x + x) (sqr B),
                      mkPX (mul (mul (Pc (1 + 1), A), mkPinj 1 B)) x (Pc 0))

```

Fast Exponentiation

lemma pow-wf: $\text{odd } n \implies (n::\text{nat}) \text{ div } 2 < n$ **by** (cases n) auto

recdef pow measure ($\lambda(x, y). y$)

```

pow (p, 0) = Pc 1
pow (p, n) = (if even n then (pow (sqr p, n div 2)) else mul (p, pow (sqr p, n
div 2)))
(hints simp add: pow-wf)

```

lemma pow-if:

```

pow (p,n) =
  (if n = 0 then Pc 1 else if even n then pow (sqr p, n div 2)
   else mul (p, pow (sqr p, n div 2)))

```

by (*cases n*) *simp-all*

Normalization of polynomial expressions

consts *norm* :: 'a::{comm-ring,recpower} *pol* \Rightarrow 'a *pol*

primrec

norm (*Pol P*) = *P*
norm (*Add P Q*) = *add* (*norm P*, *norm Q*)
norm (*Sub p q*) = *sub* (*norm p*) (*norm q*)
norm (*Mul P Q*) = *mul* (*norm P*, *norm Q*)
norm (*Pow p n*) = *pow* (*norm p*, *n*)
norm (*Neg P*) = *neg* (*norm P*)

mkPinj preserve semantics

lemma *mkPinj-ci*: *Ipol l* (*mkPinj a B*) = *Ipol l* (*Pinj a B*)

by (*induct B*) (*auto simp add: mkPinj-def ring-eq-simps*)

mkPX preserves semantics

lemma *mkPX-ci*: *Ipol l* (*mkPX A b C*) = *Ipol l* (*PX A b C*)

by (*cases A*) (*auto simp add: mkPX-def mkPinj-ci power-add ring-eq-simps*)

Correctness theorems for the implemented operations

Negation

lemma *neg-ci*: $\bigwedge l. \text{Ipol } l \text{ (neg } P) = -(\text{Ipol } l \text{ } P)$

by (*induct P*) *auto*

Addition

lemma *add-ci*: $\bigwedge l. \text{Ipol } l \text{ (add } (P, Q)) = \text{Ipol } l \text{ } P + \text{Ipol } l \text{ } Q$

proof (*induct P Q rule: add.induct*)

case (*6 x P y Q*)

show ?*case*

proof (*rule linorder-cases*)

assume *x < y*

with 6 show ?*case* **by** (*simp add: mkPinj-ci ring-eq-simps*)

next

assume *x = y*

with 6 show ?*case* **by** (*simp add: mkPinj-ci*)

next

assume *x > y*

with 6 show ?*case* **by** (*simp add: mkPinj-ci ring-eq-simps*)

qed

next

case (*7 x P Q y R*)

have *x = 0 \vee x = 1 \vee x > 1* **by** *arith*

moreover

{ **assume** *x = 0* **with 7 have** ?*case* **by** *simp* }

moreover

{ **assume** *x = 1* **with 7 have** ?*case* **by** (*simp add: ring-eq-simps*) }

```

moreover
{ assume  $x > 1$  from 7 have ?case by (cases  $x$ ) simp-all }
ultimately show ?case by blast
next
case (8  $P\ x\ R\ y\ Q$ )
have  $y = 0 \vee y = 1 \vee y > 1$  by arith
moreover
{ assume  $y = 0$  with 8 have ?case by simp }
moreover
{ assume  $y = 1$  with 8 have ?case by simp }
moreover
{ assume  $y > 1$  with 8 have ?case by simp }
ultimately show ?case by blast
next
case (9  $P1\ x\ P2\ Q1\ y\ Q2$ )
show ?case
proof (rule linorder-cases)
  assume  $a: x < y$  hence EX  $d. d + x = y$  by arith
  with 9  $a$  show ?case by (auto simp add: mkPX-ci power-add ring-eq-simps)
next
  assume  $a: y < x$  hence EX  $d. d + y = x$  by arith
  with 9  $a$  show ?case by (auto simp add: power-add mkPX-ci ring-eq-simps)
next
  assume  $x = y$ 
  with 9 show ?case by (simp add: mkPX-ci ring-eq-simps)
qed
qed (auto simp add: ring-eq-simps)

```

Multiplication

```

lemma mul-ci:  $\bigwedge l. \text{Ipol } l\ (\text{mul } (P, Q)) = \text{Ipol } l\ P * \text{Ipol } l\ Q$ 
by (induct  $P\ Q$  rule: mul.induct)
  (simp-all add: mkPX-ci mkPinj-ci ring-eq-simps add-ci power-add)

```

Substraction

```

lemma sub-ci:  $\text{Ipol } l\ (\text{sub } p\ q) = \text{Ipol } l\ p - \text{Ipol } l\ q$ 
by (simp add: add-ci neg-ci sub-def)

```

Square

```

lemma sqr-ci:  $\bigwedge ls. \text{Ipol } ls\ (\text{sqr } p) = \text{Ipol } ls\ p * \text{Ipol } ls\ p$ 
by (induct  $p$ ) (simp-all add: add-ci mkPinj-ci mkPX-ci mul-ci ring-eq-simps
power-add)

```

Power

```

lemma even-pow:  $\text{even } n \implies \text{pow } (p, n) = \text{pow } (\text{sqr } p, n \text{ div } 2)$  by (induct  $n$ )
simp-all

```

```

lemma pow-ci:  $\bigwedge p. \text{Ipol } ls\ (\text{pow } (p, n)) = (\text{Ipol } ls\ p) ^ n$ 
proof (induct  $n$  rule: nat-less-induct)

```



```

case (1 k)
have two:2 = Suc (Suc 0) by simp
show ?case
proof (cases k)
  case (Suc l)
  show ?thesis
  proof cases
    assume EL: even l
    have Suc l div 2 = l div 2
      by (simp add: nat-number even-nat-plus-one-div-two [OF EL])
    moreover
    from Suc have l < k by simp
    with 1 have  $\forall p. \text{Ipol } ls \text{ (pow (p, l))} = \text{Ipol } ls \text{ } p \wedge l$  by simp
    moreover
    note Suc EL even-nat-plus-one-div-two [OF EL]
    ultimately show ?thesis by (auto simp add: mul-ci power-Suc even-pow)
  next
    assume OL: odd l
    with prems have  $\llbracket \forall m < \text{Suc } l. \forall p. \text{Ipol } ls \text{ (pow (p, m))} = \text{Ipol } ls \text{ } p \wedge m; k = \text{Suc } l; \text{odd } l \rrbracket \implies \forall p. \text{Ipol } ls \text{ (sqr } p) \wedge (\text{Suc } l \text{ div } 2) = \text{Ipol } ls \text{ } p \wedge \text{Suc } l$ 
    proof(cases l)
      case (Suc w)
      from prems have EW: even w by simp
      from two have two-times:(2 * (w div 2))= w
        by (simp only: even-nat-div-two-times-two[OF EW])
      have A:  $\bigwedge p. (\text{Ipol } ls \text{ } p * \text{Ipol } ls \text{ } p) = (\text{Ipol } ls \text{ } p) \wedge (\text{Suc } (\text{Suc } 0))$ 
        by (simp add: power-Suc)
      from A two [symmetric] have ALL p.  $(\text{Ipol } ls \text{ } p * \text{Ipol } ls \text{ } p) = (\text{Ipol } ls \text{ } p) \wedge 2$ 
        by simp
      with prems show ?thesis
        by (auto simp add: power-mult[symmetric, of - 2 -] two-times mul-ci sqr-ci)
    qed simp
  with prems show ?thesis by simp
  qed
next
  case 0
  then show ?thesis by simp
  qed
qed

```

Normalization preserves semantics

lemma norm-ci: $\text{Ipolex } l \text{ } Pe = \text{Ipol } l \text{ (norm } Pe)$
by (induct Pe) (simp-all add: add-ci sub-ci mul-ci neg-ci pow-ci)

Reflection lemma: Key to the (incomplete) decision procedure

lemma norm-eq:
assumes eq: $\text{norm } P1 = \text{norm } P2$
shows $\text{Ipolex } l \text{ } P1 = \text{Ipolex } l \text{ } P2$
proof –

```

from eq have Ipol l (norm P1) = Ipol l (norm P2) by simp
thus ?thesis by (simp only: norm-ci)
qed

```

Code generation

```

use comm-ring.ML
setup CommRing.setup

end

```

21 List-Prefix: List prefixes and postfixes

```

theory List-Prefix
imports Main
begin

```

21.1 Prefix order on lists

```

instance list :: (type) ord ..

```

defs (overloaded)

```

prefix-def:  $xs \leq ys == \exists zs. ys = xs @ zs$ 
strict-prefix-def:  $xs < ys == xs \leq ys \wedge xs \neq (ys::'a\ list)$ 

```

```

instance list :: (type) order
by intro-classes (auto simp add: prefix-def strict-prefix-def)

```

```

lemma prefixI [intro?]:  $ys = xs @ zs ==> xs \leq ys$ 
by (unfold prefix-def) blast

```

```

lemma prefixE [elim?]:  $xs \leq ys ==> (!zs. ys = xs @ zs ==> C) ==> C$ 
by (unfold prefix-def) blast

```

```

lemma strict-prefixI' [intro?]:  $ys = xs @ z \# zs ==> xs < ys$ 
by (unfold strict-prefix-def prefix-def) blast

```

```

lemma strict-prefixE' [elim?]:
  assumes lt:  $xs < ys$ 
  and r:  $!!z zs. ys = xs @ z \# zs ==> C$ 
  shows C

```

proof –

```

from lt obtain us where  $ys = xs @ us$  and  $xs \neq ys$ 
by (unfold strict-prefix-def prefix-def) blast
with r show ?thesis by (auto simp add: neq-Nil-conv)

```

qed

```

lemma strict-prefixI [intro?]:  $xs \leq ys ==> xs \neq ys ==> xs < (ys::'a\ list)$ 
by (unfold strict-prefix-def) blast

```

lemma *strict-prefixE* [*elim?*]:
 $xs < ys \implies (xs \leq ys \implies xs \neq (ys::'a \text{ list}) \implies C) \implies C$
by (*unfold strict-prefix-def*) *blast*

21.2 Basic properties of prefixes

theorem *Nil-prefix* [*iff*]: $[] \leq xs$
by (*simp add: prefix-def*)

theorem *prefix-Nil* [*simp*]: $(xs \leq []) = (xs = [])$
by (*induct xs*) (*simp-all add: prefix-def*)

lemma *prefix-snoc* [*simp*]: $(xs \leq ys @ [y]) = (xs = ys @ [y] \vee xs \leq ys)$
proof

assume $xs \leq ys @ [y]$
then obtain zs **where** $zs @ [y] = xs @ zs$..
show $xs = ys @ [y] \vee xs \leq ys$
proof (*cases zs rule: rev-cases*)
assume $zs = []$
with zs **have** $xs = ys @ [y]$ **by** *simp*
thus ?thesis ..
next
fix z zs' **assume** $zs = zs' @ [z]$
with zs **have** $ys = xs @ zs'$ **by** *simp*
hence $xs \leq ys$..
thus ?thesis ..

qed

next

assume $xs = ys @ [y] \vee xs \leq ys$
thus $xs \leq ys @ [y]$
proof
assume $xs = ys @ [y]$
thus ?thesis **by** *simp*

next

assume $xs \leq ys$
then obtain zs **where** $ys = xs @ zs$..
hence $ys @ [y] = xs @ (zs @ [y])$ **by** *simp*
thus ?thesis ..

qed

qed

lemma *Cons-prefix-Cons* [*simp*]: $(x \# xs \leq y \# ys) = (x = y \wedge xs \leq ys)$
by (*auto simp add: prefix-def*)

lemma *same-prefix-prefix* [*simp*]: $(xs @ ys \leq xs @ zs) = (ys \leq zs)$
by (*induct xs*) *simp-all*

lemma *same-prefix-nil* [*iff*]: $(xs @ ys \leq xs) = (ys = [])$

proof –

have $(xs @ ys \leq xs @ []) = (ys \leq [])$ **by** (*rule same-prefix-prefix*)

thus *?thesis* **by** *simp*

qed

lemma *prefix-prefix [simp]*: $xs \leq ys \implies xs \leq ys @ zs$

proof –

assume $xs \leq ys$

then obtain *us* **where** $ys = xs @ us$..

hence $ys @ zs = xs @ (us @ zs)$ **by** *simp*

thus *?thesis* ..

qed

lemma *append-prefixD*: $xs @ ys \leq zs \implies xs \leq zs$

by (*auto simp add: prefix-def*)

theorem *prefix-Cons*: $(xs \leq y \# ys) = (xs = [] \vee (\exists zs. xs = y \# zs \wedge zs \leq ys))$

by (*cases xs*) (*auto simp add: prefix-def*)

theorem *prefix-append*:

$(xs \leq ys @ zs) = (xs \leq ys \vee (\exists us. xs = ys @ us \wedge us \leq zs))$

apply (*induct zs rule: rev-induct*)

apply *force*

apply (*simp del: append-assoc add: append-assoc [symmetric]*)

apply *simp*

apply *blast*

done

lemma *append-one-prefix*:

$xs \leq ys \implies \text{length } xs < \text{length } ys \implies xs @ [ys ! \text{length } xs] \leq ys$

apply (*unfold prefix-def*)

apply (*auto simp add: nth-append*)

apply (*case-tac zs*)

apply *auto*

done

theorem *prefix-length-le*: $xs \leq ys \implies \text{length } xs \leq \text{length } ys$

by (*auto simp add: prefix-def*)

lemma *prefix-same-cases*:

$(xs_1::'a \text{ list}) \leq ys \implies xs_2 \leq ys \implies xs_1 \leq xs_2 \vee xs_2 \leq xs_1$

apply (*simp add: prefix-def*)

apply (*erule exE*)**+**

apply (*simp add: append-eq-append-conv-if split: if-splits*)

apply (*rule disjI2*)

apply (*rule-tac x = drop (size xs₂) xs₁ in exI*)

apply *clarify*

apply (*drule sym*)

apply (*insert append-take-drop-id [of length xs₂ xs₁]*)

```

  apply simp
  apply (rule disjI1)
  apply (rule-tac x = drop (size xs1) xs2 in exI)
  apply clarify
  apply (insert append-take-drop-id [of length xs1 xs2])
  apply simp
done

```

```

lemma set-mono-prefix:
  xs ≤ ys ==> set xs ⊆ set ys
by (auto simp add: prefix-def)

```

21.3 Parallel lists

```

constdefs
  parallel :: 'a list => 'a list => bool    (infixl || 50)
  xs || ys == ¬ xs ≤ ys ∧ ¬ ys ≤ xs

```

```

lemma parallelI [intro]: ¬ xs ≤ ys ==> ¬ ys ≤ xs ==> xs || ys
by (unfold parallel-def) blast

```

```

lemma parallelE [elim]:
  xs || ys ==> (¬ xs ≤ ys ==> ¬ ys ≤ xs ==> C) ==> C
by (unfold parallel-def) blast

```

```

theorem prefix-cases:
  (xs ≤ ys ==> C) ==>
  (ys < xs ==> C) ==>
  (xs || ys ==> C) ==> C
by (unfold parallel-def strict-prefix-def) blast

```

```

theorem parallel-decomp:
  xs || ys ==> ∃ as b bs c cs. b ≠ c ∧ xs = as @ b # bs ∧ ys = as @ c # cs
proof (induct xs rule: rev-induct)

```

```

  case Nil
  hence False by auto
  thus ?case ..

```

```

next
  case (snoc x xs)
  show ?case
  proof (rule prefix-cases)
    assume le: xs ≤ ys
    then obtain ys' where ys: ys = xs @ ys' ..
    show ?thesis
    proof (cases ys')
      assume ys' = [] with ys have xs = ys by simp
      with snoc have [x] || [] by auto
      hence False by blast
      thus ?thesis ..
    qed
  qed

```

```

next
  fix c cs assume ys': ys' = c # cs
  with snoc ys have xs @ [x] || xs @ c # cs by (simp only:)
  hence x ≠ c by auto
  moreover have xs @ [x] = xs @ x # [] by simp
  moreover from ys ys' have ys = xs @ c # cs by (simp only:)
  ultimately show ?thesis by blast
qed
next
  assume ys < xs hence ys ≤ xs @ [x] by (simp add: strict-prefix-def)
  with snoc have False by blast
  thus ?thesis ..
next
  assume xs || ys
  with snoc obtain as b bs c cs where neg: (b::'a) ≠ c
    and xs: xs = as @ b # bs and ys: ys = as @ c # cs
    by blast
  from xs have xs @ [x] = as @ b # (bs @ [x]) by simp
  with neg ys show ?thesis by blast
qed
qed

```

21.4 Postfix order on lists

constdefs

```

postfix :: 'a list => 'a list => bool ((-/ >>= -) [51, 50] 50)
xs >>= ys == ∃ zs. xs = zs @ ys

```

```

lemma postfix-refl [simp, intro!]: xs >>= xs
  by (auto simp add: postfix-def)
lemma postfix-trans: [xs >>= ys; ys >>= zs] ⟹ xs >>= zs
  by (auto simp add: postfix-def)
lemma postfix-antisym: [xs >>= ys; ys >>= xs] ⟹ xs = ys
  by (auto simp add: postfix-def)

```

```

lemma Nil-postfix [iff]: xs >>= []
  by (simp add: postfix-def)
lemma postfix-Nil [simp]: ([] >>= xs) = (xs = [])
  by (auto simp add: postfix-def)

```

```

lemma postfix-ConsI: xs >>= ys ⟹ x#xs >>= ys
  by (auto simp add: postfix-def)
lemma postfix-ConsD: xs >>= y#ys ⟹ xs >>= ys
  by (auto simp add: postfix-def)

```

```

lemma postfix-appendI: xs >>= ys ⟹ zs @ xs >>= ys
  by (auto simp add: postfix-def)
lemma postfix-appendD: xs >>= zs @ ys ⟹ xs >>= ys
  by (auto simp add: postfix-def)

```

```

lemma postfix-is-subset-lemma:  $xs = zs @ ys \implies \text{set } ys \subseteq \text{set } xs$ 
  by (induct zs, auto)
lemma postfix-is-subset:  $xs >>= ys \implies \text{set } ys \subseteq \text{set } xs$ 
  by (unfold postfix-def, erule exE, erule postfix-is-subset-lemma)

lemma postfix-ConsD2-lemma [rule-format]:  $x\#xs = zs @ y\#ys \longrightarrow xs >>= ys$ 
  by (induct zs, auto intro!: postfix-appendI postfix-ConsI)
lemma postfix-ConsD2:  $x\#xs >>= y\#ys \implies xs >>= ys$ 
  by (auto simp add: postfix-def dest!: postfix-ConsD2-lemma)

lemma postfix2prefix:  $(xs >>= ys) = (\text{rev } ys <= \text{rev } xs)$ 
  apply (unfold prefix-def postfix-def, safe)
  apply (rule-tac  $x = \text{rev } zs$  in exI, simp)
  apply (rule-tac  $x = \text{rev } zs$  in exI)
  apply (rule rev-is-rev-conv [THEN iffD1], simp)
done

end

```

22 List-lexord: Lexicographic order on lists

```

theory List-lexord
imports Main
begin

```

```

instance list :: (ord) ord ..
defs (overloaded)
  list-le-def:  $(xs::('a::ord) \text{ list}) \leq ys \equiv (xs < ys \vee xs = ys)$ 
  list-less-def:  $(xs::('a::ord) \text{ list}) < ys \equiv (xs, ys) \in \text{lexord } \{(u,v). u < v\}$ 

```

```

lemmas list-ord-defs = list-less-def list-le-def

```

```

instance list :: (order) order
  apply (intro-classes, unfold list-ord-defs)
  apply (rule disjI2, safe)
  apply (blast intro: lexord-trans transI order-less-trans)
  apply (rule-tac  $r1 = \{(a::'a,b). a < b\}$  in lexord-irreflexive [THEN notE])
  apply simp
  apply (blast intro: lexord-trans transI order-less-trans)
  apply (rule-tac  $r1 = \{(a::'a,b). a < b\}$  in lexord-irreflexive [THEN notE])
  apply simp
  apply assumption
done

```

```

instance list::(linorder)linorder
  apply (intro-classes, unfold list-le-def list-less-def, safe)
  apply (cut-tac  $x = x$  and  $y = y$  and  $r = \{(a,b). a < b\}$  in lexord-linear)

```

```

apply force
apply simp
done

lemma not-less-Nil[simp]:  $\sim(x < [])$ 
by (unfold list-less-def) simp

lemma Nil-less-Cons[simp]:  $[] < a \# x$ 
by (unfold list-less-def) simp

lemma Cons-less-Cons[simp]:  $(a \# x < b \# y) = (a < b \mid a = b \ \& \ x < y)$ 
by (unfold list-less-def) simp

lemma le-Nil[simp]:  $(x \leq []) = (x = [])$ 
by (unfold list-ord-defs, cases x) auto

lemma Nil-le-Cons [simp]:  $([] \leq x)$ 
by (unfold list-ord-defs, cases x) auto

lemma Cons-le-Cons[simp]:  $(a \# x \leq b \# y) = (a < b \mid a = b \ \& \ x \leq y)$ 
by (unfold list-ord-defs) auto

end

```

References

- [1] Abrial and Laffitte. Towards the mechanization of the proofs of some classical theorems of set theory. Unpublished.
- [2] J. Avigad and K. Donnelly. Formalizing O notation in Isabelle/HOL. In D. Basin and M. Rusiowitch, editors, *Automated Reasoning: second international conference, IJCAR 2004*, pages 357–371. Springer, 2004.
- [3] A. Oberschelp. *Rekursionstheorie*. BI-Wissenschafts-Verlag, 1993.
- [4] C. Paulin-Mohring. Inductive definitions in the system Coq: Rules and properties. In M. Bezem and J. Groote, editors, *Typed Lambda Calculi and Applications*, LNCS 664, pages 328–345. Springer, 1993.